

Harrington

STORZ CONNECT

Hydrant Storz

Intake Valves

Storz Elbows

Storz Adapters

Gate Valves

Ball Valves

Siamese Valves

Suction Hose

Suction Strainers

Threaded Adapters

Storz Equipment



Since 1988 - Making the Right Connections!

TABLE OF CONTENTS

SECTION #	MODEL	DESCRIPTION	PAGE #
INTAKE VALVES			
1	H500S	PISTON INTAKE VALVES - 45° ELBOW	4
	H1000	BALL INTAKE VALVES - 30° ELBOW	5
WYE - 2-WAY & 3-WAY VALVES			
2	H200	WYE 2-WAY - LDH - BALL VALVE & LONG HANDLE	6
	H201	WYE 2-WAY LEADER-LINE "SMALL" BALL VALVE	7
	H201F	WYE 2-WAY LEADER-LINE "FORESTRY" BALL VALVE	8
	H202	WYE 2-WAY LEADER-LINE "MID-SIZE" BALL VALVE	8
	H300	WYE 3-WAY BALL VALVE - LDH	9
	H600	WYE 3-WAY "SUPER-FLOW" BALL VALVE - LDH - RELIEF VALVE	10
WATER THIEFS			
3	H301	WATER THIEF - 3-WAY - "SMALL" BALL VALVES (1" TO 3")	11
	H301	WATER THIEF - 3-WAY - LDH BALL VALVES (4" TO 6")	11-12
	H400	WATER THIEF - 5-WAY - LDH BALL VALVES	13
HYDRANT VALVES			
4	H700	HYDRANT VALVES - HYDRA-ASSIST	14
	HHBV	HYDRANT BALL VALVE - 2.5"	15
	HHGV	HYDRANT GATE VALVE - 2.5"	16
GATE VALVES & SUPER-FLOW VALVES			
5	H800	GATE VALVE - 4" - STRAIGHT	16-17
	H810	GATE VALVE - 4" - 25° ELBOW - RELIEF VALVE	18
	H811	GATE VALVE - 4" - 25° ELBOW	19
	FLANGE	GATE VALVE - 4" - H800F, H810F, H811F - FLANGE VALVES	20
	H860	SUPER-FLOW 6" - STRAIGHT - GATE VALVE & H860F - FLANGE VALVES	21
BUTTERFLY VALVES			
6	HSBFV	BUTTERFLY VALVE - FS/LH x STORZ	22
	HTBFV	BUTTERFLY VALVE - NHFS LONG HANDLE x NHM	23
SIAMESE VALVES			
7	HJ20	JUMBO SIAMESE - DOUBLE CLAPPERED (HJ22 -- NON-CLAPPERED)	24
	H220	SIAMESE - 2-WAY - SINGLE CLAPPERED (H220LC -- NON-CLAPPERED)	25
	H330	SIAMESE - 3-WAY - SINGLE CLAPPERED	26
	H440	SIAMESE - 4-WAY - SINGLE CLAPPERED	26
ELBOW ADAPTERS			
8	H30E	ELBOW ADAPTER - 30° - SMALL - FS X MALE	27
		ELBOW ADAPTER - 30° - STORZ X FS & RIGID ROCKER LUG	27-29
		ELBOW ADAPTER - 30° - STORZ x PART-TIME SWIVEL STORZ	29
		ELBOW ADAPTER - 30° - STORZ x FS LONG HANDLE	30
STORZ HYDRANT ADAPTERS			
9	HPHA	HYDRANT ADAPTER - STORZ - W/CAP	31
	HIHS	HYDRANT ADAPTER - INTEGRAL NOZZLE - W/CAP	32
STORZ STRAIGHT ADAPTERS			
10	HSFS	STORZ STRAIGHT ADAPTER x FM SWIVEL RL OR LONG HANDLE	33-35
	HSFR	STORZ STRAIGHT ADAPTER x FM RIGID	35-37
	HSMR	STORZ STRAIGHT ADAPTER x MALE	37-39
FLANGE STORZ ADAPTERS			
11	HFL-FF	FLANGE x STORZ ADAPTER - FLAT FACE - FLANGE	40
	HFL-RF	FLANGE x STORZ ADAPTER - RAISED FACE - FLANGE	
	HFL-FF	FLANGE x ADAPTER - MALE or FM THREADED	41
	HFL-RF	FLANGE x ADAPTER - MALE NH THREADED	

12	STORZ ADAPTERS		
	HSTS	ADAPTER - STORZ x STORZ RIGID	42
	HSFR	ADAPTER - STORZ x BSP FM RIGID (including HFTS)	43-44
13	STORZ ACCESSORIES		
	HSAS	ADAPTER SCREEN - STORZ	44
	HBC	STORZ CAPS	44
14	THREADED ADAPTERS		
	H35	ADAPTER - DOUBLE FEMALE - DFM SWIVEL - ROCKER LUG	45
	H36	ADAPTER - DOUBLE MALE - ROCKER LUG	46
	H37	ADAPTER - FEMALE RIGID x MALE - ROCKER LUG	47
	H53	ADAPTER - FEMALE SWIVEL x FEMALE RIGID - ROCKER LUG	49
	H53L	ADAPTER - FEMALE SWIVEL LONG HANDLE x FEMALE RIGID ROCKER LUG	51
	H54	ADAPTER - FEMALE SWIVEL ROCKER LUG x MALE ROCKER LUG	53
	H54L	ADAPTER - MALE ROCKER LUG x FEMALE SWIVEL LONG HANDLE	54
	H56L	ADAPTER - FEMALE RIGID LONG HANDLE x MALE	56
H57L	ADAPTER - DOUBLE FEMALE - LONG HANDLES	57	
15	CAPS - THREADED		
	HTBC	THREADED FEMALE BLIND CAP	59
	HTP	THREADED MALE PLUG	59
16	SUCTION HOSE		
	HSH	SUCTION HOSE PVC - THREADED	60-61
	HSHS	SUCTION HOSE PVC - STORZ	62-63
17	SUCTION STRAINERS		
	HTBS	BARREL STRAINER - FEMALE RIGID & HSBS STORZ	64
	HWMB	BASKET STRAINER & DIFFUSER - FEMALE RIGID - NH & NPSH	64
	HTLLS	LOW LEVEL STRAINER, JET SIPHON, NH & HSLLS STORZ	65
	HTFBS	FLOATING STRAINER, NH THREADED & HSFBS STORZ	65
	HPSE90	SUCTION ELBOW & HFE FLUSHING ELBOW	66
18	WILDLAND AND MARINE EQUIPMENT		
	HHSN	WILDLAND & MARINE NOZZLE	67
19	FOAM EQUIPMENT		
	HFI	FOAM EDUCTOR	68
	HHFN	FOAM NOZZLE - LOW EXPANSION & HMFN - MEDIUM EXPANSION	69
20	WRENCHES, HOLDERS, AND MOUNTINGS		
	HSSW/	SPANNER & HYDRANT WRENCHES (ONLY)	70
	HSW	COMBINATION SPANNER & HYDRANT WRENCH & HOLDERS	71
		HOLDERS & MOUNTINGS (ONLY)	72
	HSMB	STORZ MOUNTING BRACKETS & HPM - POST MOUNT	72-73
	HTMB	THREADED MOUNTING BRACKETS	73
21	SPECIAL EQUIPMENT		
	HHR	FIRE HOSE ROLLER	74
	HHW	FIRE HOSE WASHER	74
	HWS	WATER CURTAIN NOZZLE	74
	H37	HAZ-MAT REDUCER ADAPTER - NH x GHT & BLEEDER CAP W/VALVE	75
	STORZ SEALS AND THREAD GASKETS - HSSS - HSPS - HNHG - HBSPG	75-76	
22	SPARE PARTS		
		REFER TO PARTS LISTING	77

H500S - Piston Intake Valve - 45° Elbow - Relief Valve - S/Steel



The Harrington Model H500S 5" piston intake valve shall be designed for pumper intake control. The valve features a variety of Storz and NH connections in sizes from 4" to 6" with gray powder coating. Each unit is constructed of anodized aluminum, with a stainless-steel piston, sleeve & spindle, and includes a 45° integrated elbow. The valve shall be operated with a handwheel with folding handle. The valve shall be hydrostatically tested to 900 PSI. The valve shall have friction loss of less than 2.5 PSI at 1,000 GPM flow. An adjustable relief valve shall be installed with increments of 25 PSI from 75 PSI to 250 PSI, pre-set at 125 PSI. An aluminum air bleeder valve shall be installed. 5-year corrosion warranty.

APPROXIMATE DIMENSIONS: 10.5"L x 8"W x 17"H

H500S-40-45NH	5" Piston Intake Valve 45° Elbow 4" Storz/Lok x 4.5" NH FS R/L Rif Vlv S/S Internals	\$4,019.00
H500S-40-50NH	5" Piston Intake Valve 45° Elbow 4" Storz/Lok x 5" NH FS R/L Rif Vlv S/S Internals	\$3,963.00
H500S-40-60NH	5" Piston Intake Valve 45° Elbow 4" Storz/Lok x 6" NH FS S/Handle Rif Vlv S/S Internals	\$3,969.00
H500S-40-60NH/Cap	5" Piston Intake Valve 45° Elbow 4" Storz/Lok Cap/Cbl x 6" NH FS S/Handle Rif Vlv S/S Internals	\$4,191.00
H500S-40NHFS-60NH	5" Piston Intake Valve 45° Elbow 4" NH FS x 6" NH FS S/Handle Rif Vlv S/S Internals	\$3,906.00
H500S-40NHM-60NH	5" Piston Intake Valve 45° Elbow 4" NH Male x 6" NH FS S/Handle Rif Vlv S/S Internals	\$3,719.00
H500S-50-45NH	5" Piston Intake Valve 45° Elbow 5" Storz/Lok x 4.5" NH FS R/L Rif Vlv S/S Internals	\$3,950.00
H500S-50-45NH/FTS	5" Piston Intake Valve 45° Elbow 5" Storz/Lok (FTS) x 4.5" NH FS R/L Rif Vlv S/S Internals	\$4,450.00
H500S-50-50NH	5" Piston Intake Valve 45° Elbow 5" Storz/Lok x 5" NH FS R/L Rif Vlv S/S Internals	\$3,894.00
H500S-50-50NH/FTS	5" Piston Intake Valve 45° Elbow 5" Storz/Lok (FTS) x 5" NH FS R/L Rif Vlv S/S Internals	\$4,395.00
H500S-50-60NH	5" Piston Intake Valve 45° Elbow 5" Storz/Lok x 6" NH FS S/Handle Rif Vlv S/S Internals	\$3,900.00
H500S-50-60NH/Cap	5" Piston Intake Valve 45° Elbow 5" Storz/Lok Cap/Cbl x 6" NH FS S/Handle Rif Vlv S/S Internals	\$4,200.00
H500S-50-60NH/FTS	5" Piston Intake Valve 45° Elbow 5" Storz/Lok (FTS) x 6" NH FS S/Handle Rif Vlv S/S Internals	\$4,400.00
H500S-50-60NPSH	5" Piston Intake Valve 45° Elbow 5" Storz/Lok x 6" NPSH R/L FS Rif Vlv S/S Internals	\$3,900.00
H500S-50NHM-60NH	5" Piston Intake Valve 45° Elbow 5" NH male x 6" NH FS S/Handle Rif Vlv S/S Internals	\$3,750.00
H500S-60-45NH	5" Piston Intake Valve 45° Elbow 6" Storz/Lok x 4.5" NH FS R/L Rif Vlv S/S Internals	\$4,138.00
H500S-60-50NH	5" Piston Intake Valve 45° Elbow 6" Storz/Lok x 5" NH FS R/L Rif Vlv S/S Internals	\$4,138.00
H500S-60-60NH	5" Piston Intake Valve 45° Elbow 6" Storz/Lok x 6" NH FS S/Handle Rif Vlv S/S Internals	\$4,138.00
H500S-60NHFS-60NH	5" Piston Intake Valve 45° Elbow 6" NH FS RL x 6" NH FS S/Handle Rif Vlv S/S Internals	\$4,050.00
H500S-60NHM-60NH	5" Piston Intake Valve 45° Elbow 6" NH male x 6" NH FS S/Handle Rif Vlv S/S Internals	\$3,763.00



H1000- Ball Intake Valve - 45° Elbow - Relief Valve

The Harrington Model H1000 5" Low-Pro full flow ball-type intake valve shall be designed for pumper intake control. The valve features a variety of Storz and NH inlet connections in sizes from 4" to 6". The ball intake valve shall be constructed of anodized aluminum (gray powder coating) and shall have a 45° integrated elbow. The valve shall be operated with a handwheel with a folding handle; the handwheel can be located on either the right or left side of a valve. The valve shall be hydrostatically tested to 900M PSI. A visual indicator on top of the ball valve in 'red color' shall be provided to note position of ball valve. The valve shall have friction loss of less than 1 PSI at 1,000 GPM flow. The valve shall be hydrostatically tested to 900 PSI. An adjustable relief valve shall be installed with increments of 25 PSI from 75 PSI to 250 PSI, pre-set at 125 PSI. A quarter-turn stainless steel. 750" air bleeder valve shall be positioned on either side of the valve gear box. 5-year corrosion warranty.



APPROXIMATE DIMENSIONS: 12"L x 8"W x 16"H H1000S - Ball Intake Valve - 45° Elbow - Relief Valve

H1000-40-45NH	5" Ball Intake Vlv 30° Elbow 4" Storz/Lok x 4.5" NH FS R/L Rif Vlv	\$4,835.00
H1000-40-50NH	5" Ball Intake Vlv 30° Elbow 4" Storz/Lok x 5" NH FS R/L Rif Vlv	\$4,795.00
H1000-40-60NH	5" Ball Intake Vlv 30° Elbow 4" Storz/Lok x 6" NH FS S/Handle Rif Vlv	\$4,795.00
H1000-40-60NH/Cap	5" Ball Intake Vlv 30° Elbow 4" Storz/Lok Cap/Cbl x 6" NH FS S/Handle Rif Vlv	\$5,016.00
H1000-40NHFS-60NH	5" Ball Intake Vlv 30° Elbow 4" NH R/L FS x 6" NH FS S/Handle Rif Vlv	\$4,730.00
H1000-40NHM-60NH	5" Ball Intake Vlv 30° Elbow 4" NH male x 6" NH FS S/Handle Rif Vlv	\$4,595.00
H1000-45NHM-45NH	5" Ball Intake Vlv 30° Elbow 4.5" NH male x 4.5" NH FS S/Handle Rif Vlv	\$4,730.00
H1000-45NHFS-60NH	5" Ball Intake Vlv 30° Elbow 4.5" NH FS x 6" NH FS S/Handle Rif Vlv	\$4,730.00
H1000-45NHM-60NH	5" Ball Intake Vlv 30° Elbow 4.5" NH male x 6" NH FS S/Handle Rif Vlv	\$4,595.00
H1000-50-45NH	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok x 4.5" NH FS S/Handle Rif Vlv	\$4,795.00
H1000-50-45NH/FTS	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok (FTS) x 4.5" NH FS S/Handle Rif Vlv	\$5,295.00
H1000-50-50NH	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok x 5" NH FS S/Handle Rif Vlv	\$4,763.00
H1000-50-50NH/FTS	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok (FTS) x 5" NH FS S/Handle Rif Vlv	\$5,265.00
H1000-50-50NPSH	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok x 5" NPSH FS R/L Rif Vlv	\$4,763.00
H1000-50NHFS-50NH	5" Ball Intake Vlv 30° Elbow 5" NH FS x 5" NH FS S/Handle Rif Vlv	\$4,745.00
H1000-50NHM-50NH	5" Ball Intake Vlv 30° Elbow 5" NH male x 5" NH FS S/Handle Rif Vlv	\$4,605.00
H1000-50ST-60FF/ NORV/CAP	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok Cap/Cbl x 6" Flat Face Flange No Relief Valve	\$5,045.00
H1000-50-60NH	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok x 6" NH FS S/Handle Rif Vlv	\$4,765.00
H1000-50-60NH/Cap	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok Cap/Cbl x 6" NH FS S/Handle Rif Vlv	\$5,060.00
H1000-50-60NH/FTS	5" Ball Intake Vlv 30° Elbow 5" Storz/Lok (FTS) x 6" NH FS S/Handle Rif Vlv	\$5,265.00
H1000-50NHFS-60NH	5" Ball Intake Vlv 30° Elbow 5" NH FS x 6" NH FS S/Handle Rif Vlv	\$4,745.00
H1000-50NHM-60NH	5" Ball Intake Vlv 30° Elbow 5" NH male x 6" NH FS S/Handle Rif Vlv	\$4,605.00
H1000-60-45NH	5" Ball Intake Vlv 30° Elbow 6" Storz/Lok x 4.5" NH FS R/L Rif Vlv	\$4,910.00
H1000-60-50NH	5" Ball Intake Vlv 30° Elbow 6" Storz/Lok x 5" NH FS R/L Rif Vlv	\$4,910.00
H1000-60-60NH	5" Ball Intake Vlv 30° Elbow 6" Storz/Lok x 6" NH FS S/Handle Rif Vlv	\$4,910.00
H1000-60NHFS-60NH	5" Ball Intake Vlv 30° Elbow 6" NH FS x 6" NH FS S/Handle Rif Vlv	\$4,960.00
H1000-60NHM-60NH	5" Ball Intake Vlv 30° Elbow 6" NH male x 6" NH FS S/Handle Rif Vlv	4,625.00
H1000-60NHM-60FF/ NORV/CAP	5" Ball Intake Vlv 30° Elbow 6" NH male Cap/Cbl x 6" Flat-Face Flange No Relief Vavle	5,185.00



H200 - 2-Way LDH Wye Ball Valve



The Harrington Model H200 mid-size 2-way wye ball valve shall be designed for feeding two (2) lines from an LDH line; the design permits supply water from either direction. The valve shall include two (2) hard anodized ball valves with stainless-steel tappets for corrosion resistance, aluminum control handles, and powder-coated red in color. The valve shall feature a variety of Storz and NH connections in sizes from 2.5" to 6". The valve shall have NH female swivels with rocker lugs or LHs. Storz connections with 4" and larger sizes shall have locking devices.

APPROXIMATE DIMENSIONS: 10.5"L x 9"W x 10"H

H200-25NHFS-25NHM	2-Way LDH Wye Ball Valve	2.5" NH FS R/L x (2) 2.5" NH male	\$1,206.00
H200-40-25NH	2-Way LDH Wye Ball Valve	4" Storz/Lok x (2) 2.5" NH male	\$1,250.00
H200-40-25NHFS	2-Way LDH Wye Ball Valve	4" Storz/Lok x (2) 2.5" NH FS R/L	\$1,475.00
H200-40NHFS-25NHM	2-Way LDH Wye Ball Valve	4" NH FS R/L x (2) 2.5" NH male	\$1,288.00
H200-40NHFS-25NHFS	2-Way LDH Wye Ball Valve	4" NH FS R/L x (2) 2.5" NH FS R/L	\$1,513.00
H200-40NPTF-25NHM	2-Way LDH Wye Ball Valve	4" NPT female rigid x (2) 2.5" NH male	\$1,119.00
H200-40NPTF-25NHFS	2-Way LDH Wye Ball Valve	4" NPT female rigid x (2) 2.5" NH FS R/L	\$1,344.00
H200-40-25ST	2-Way LDH Wye Ball Valve	4" Storz/Lok x (2) 2.5" Storz	\$1,388.00
H200-40-30ST	2-Way LDH Wye Ball Valve	4" Storz/Lok x (2) 3" Storz	\$1,375.00
H200-45NHFS-25NH	2-Way LDH Wye Ball Valve	4.5" NH FS R/L x (2) 2.5" NH male	\$1,269.00
H200-45NHFS-25NHFS	2-Way LDH Wye Ball Valve	4.5" NH FS R/L x (2) 2.5" NH FS R/L	\$1,494.00
H200-50-25NH	2-Way LDH Wye Ball Valve	5" Storz/Lok x (2) 2.5" NH male	\$1,456.00
H200-50-25NH/FTS	2-Way LDH Wye Ball Valve	5" Storz/Lok (FTS) x (2) 2.5" NH male	\$1,906.00
H200-50-25NHFS	2-Way LDH Wye Ball Valve	5" Storz/Lok x (2) 2.5" NH FS R/L	\$1,681.00
H200-50-25NHFS/FTS	2-Way LDH Wye Ball Valve	5" Storz/Lok (FTS) x (2) 2.5" NH FS R/L	\$2,131.00
H200-50NHFS-25NHM	2-Way LDH Wye Ball Valve	5" NH FS R/L x (2) 2.5" NH male	\$1,338.00
H200-50NHFS-25NHFS	2-Way LDH Wye Ball Valve	5" NH FS R/L x (2) 2.5" NH FS R/L	\$1,563.00
H200-50-25ST	2-Way LDH Wye Ball Valve	5" Storz/Lok x (2) 2.5" Storz	\$1,706.00
H200-50-30NHM	2-Way LDH Wye Ball Valve	5" Storz/Lok x (2) 3" NH male	\$1,819.00
H200-50-30NHFS	2-Way LDH Wye Ball Valve	5" Storz/Lok x (2) 3" NH FS R/L	\$1,944.00
H200-50-30ST	2-Way LDH Wye Ball Valve	5" Storz/Lok x (2) 3" Storz	\$1,581.00
H200-60-25NH	2-Way LDH Wye Ball Valve	6" Storz/Lok x (2) 2.5" NH male	\$1,563.00
H200-60-25ST	2-Way LDH Wye Ball Valve	6" Storz/Lok x (2) 2.5" Storz	\$1,700.00
H200-60-25NHFS	2-Way LDH Wye Ball Valve	6" Storz/Lok x (2) 2.5" NH FS R/L	\$1,788.00
H200-60NHFS-25NHM	2-Way LDH Wye Ball Valve	6" NH FS R/L x (2) 2.5" NH male	\$1,406.00
H200-60NHFS-25NHFS	2-Way LDH Wye Ball Valve	6" NH FS R/L x (2) 2.5" NH FS R/L	\$1,631.00



H200 - 2-Way LDH Wye Ball Valve - Female LH or Male

H200-40NHLH-25NH	2-Way LDH Wye Ball Valve 4" NH FS LH x (2) 2.5" NH male	\$1,288.00
H200-40NHLH-25NHFS	2-Way LDH Wye Ball Valve 4" NH FS LH x (2) 2.5" NH FS R/L	\$1,513.00
H200-45NHLH-25NH	2-Way LDH Wye Ball Valve 4.5" NH FS LH x (2) 2.5" NH male	\$1,281.00
H200-45NHLH-25NHFS	2-Way LDH Wye Ball Valve 4.5" NH FS LH x (2) 2.5" NH FS R/L	\$1,506.00
H200-50NHLH-25NH	2-Way LDH Wye Ball Valve 5" NH FS LH x (2) 2.5" NH male	\$1,319.00
H200-50NHLH-25NHFS	2-Way LDH Wye Ball Valve 5" NH FS LH x (2) 2.5" NH FS R/L	\$1,544.00
H200-60NHLH-25NH	2-Way LDH Wye Ball Valve 6" NH FS LH x (2) 2.5" NH male	\$1,413.00
H200-60NHLH-25NHFS	2-Way LDH Wye Ball Valve 6" NH FS LH x (2) 2.5" NH FS R/L	\$1,638.00

H201 - Small 2-Way Leader-Line Wye Ball Valve - FS x Male



The Harrington Model H201 medium 2-way wye ball valve shall be designed for forestry and high-rise packs and permits feeding from either direction. The valve shall include two (2) hard anodized ball valves with plastic tappets for lightweight & corrosion resistance with aluminum control handles. The lightweight aluminum valve body shall be powder-coated red in color. Two types of handles available: a) Standard LHs b) High Rise short handles. The valve features NH or Storz connections in sizes from 1.5" to 2.5"; female swivel connections shall have rocker lugs.



APPROXIMATE DIMENSIONS: 10.5"L x 9"W x 8"H

H201-10NHFS-10NH	2-Way Leader-Line Wye Ball Valve 1" NH FS R/L x (2) 1" NH male	\$1,100.00
H201-10NHFS-10NH/HR	2-Way Leader-Line Wye Ball Valve 1" NH FS R/L x (2) 1" NH male HR Handles	\$1,100.00
H201-15NHFS-GHT	2-Way Leader-Line Wye Ball Valve 1.5" NH FS R/L x (2) GHT male	\$1,094.00
H201-15NHFS-10NH	2-Way Leader-Line Wye Ball Valve 1.5" NH FS R/L x (2) 1" NH male	\$1,113.00
H201-15NHFS-10NH/HR	2-Way Leader-Line Wye Ball Valve 1.5" NH FS R/L x (2) 1" NH male HR Handles	\$1,113.00
H201-15NHFS-15NH	2-Way Leader-Line Wye Ball Valve 1.5" NH FS R/L x (2) 1.5" NH male	\$1,113.00
H201-15NHFS-15NH/HR	2-Way Leader-Line Wye Ball Valve 1.5" NH FS R/L x (2) 1.5" NH male HR Handles	\$1,113.00
H201-15NHFS-15NHFS	2-Way Leader-Line Wye Ball Valve 1.5" NH FS R/L x (2) 1.5" NH FS R/L	\$1,181.00
H201-20-20ST	2-Way Leader-Line Wye Ball Valve 2" Storz x (2) 2" Storz	\$950.00
H201-25NHFS-10NH	2-Way Leader-Line Wye Ball Valve 2.5" NH FS R/L x (2) 1" NH male	\$1,119.00
H201-25NHFS-10NH/HR	2-Way Leader-Line Wye Ball Valve 2.5" NH FS R/L x (2) 1" NH male HR Handles	\$1,119.00
H201-25NHFS-15NH	2-Way Leader-Line Wye Ball Valve 2.5" NH FS R/L x (2) 1.5" NH male	\$1,113.00
H201-25NHFS-15NH/HR	2-Way Leader-Line Wye Ball Valve 2.5" NH FS R/L x (2) 1.5" NH male HR Handles	\$1,113.00
H201-25NHFS-15NPSH	2-Way Leader-Line Wye Ball Valve 2.5" NH FS R/L x (2) 1.5" NPSH male	\$1,113.00
H201-25NHFS-15ST	2-Way Leader-Line Wye Ball Valve 2.5" NH FS R/L x (2) 1.5" Storz	\$1,155.00
H201-25NHFS-15ST/HR	2-Way Leader-Line Wye Ball Valve 2.5" NH FS R/L x (2) 1.5" Storz HR Handles	\$1,155.00
H201-25-25ST	2-Way Leader-Line Wye Ball Valve 2.5" Storz x (2) 2.5" Storz	\$1,006.00



H201F - Small 2-Way Leader-Line Wye Ball Valve - Forestry



The Harrington Model H201F small 2- way wye ball valve shall be designed for forestry and permits feeding from either direction. The valve shall include two (2) hard anodized ball valves with stainless steel tappets for corrosion resistance, and aluminum control handles. The lightweight aluminum valve body shall be powder- coated red in color. Intake connections can be either 1" and 1.5" NH female swivel with rocker lugs. Discharge connections can be NH, NPSH, special threads, or garden hose male threads.

APPROXIMATE DIMENSIONS: 10.5"L x 9"W x 8"H

H201F-10NHFS-10NHM	2-Way Ball Valve 1" NH FS x (2) 1" NH male (Forestry)	\$881.00
H201F-10NHFS-10NPSHM	2-Way Ball Valve 1" NH FS x (2) 1" NPSH male (Forestry)	\$881.00
H201F-15NHFS-10NHM	2-Way Ball Valve 1.5" NH FS x (2) 1" NH male (Forestry)	\$938.00
H201F-15NHFS-15NHM	2-Way Ball Valve 1.5" NH FS x (2) 1.5" NH male (Forestry)	\$1,006.00

H202 - Mid Size 2-Way Leader-Line Wye Ball Valve



The Harrington Model H202 mid-size 2-way wye ball valves (known as a "leader-line-wye") shall be designed for feeding two lines from one line and permits feeding from either direction. The valve shall include two (2) hard anodized ball valves with stainless-steel tappets for corrosion resistance and aluminum control handles. The lightweight aluminum valve body shall be powder-coated red in color. Two types of handles available: a) Standard LHs b) High Rise short handles. The valves feature NH and Storz connections, inlet size 2.5" and 3"; NH female swivel connections shall have rocker lugs.



APPROXIMATE DIMENSIONS: 10.5"HR HANDLES L x 9"W x 8"H

H202-25NHFS-15NH	2-Way Leader-Line Wye Ball Valve Mid-Size	2.5" NH FS x (2) 1.5" NH male	\$1,375.00
H202-25NHFS-15NH/HR	2-Way Leader-Line Wye Ball Valve Mid-Size Handles	2.5" NH FS x (2) 1.5" NH male HR	\$1,375.00
H202-25NPSHFS-15NH	2-Way Leader-Line Wye Ball Valve Mid-Size	2.5" NPSH FS x (2) 1.5" NH male	\$1,375.00
H202-25NHFS-25NH	2-Way Leader-Line Wye Ball Valve Mid-Size	2.5" NH FS x (2) 2.5" NH male	\$1,265.00
H202-25NHFS-25NH/HR	2-Way Leader-Line Wye Ball Valve Mid-Size Handles	2.5" NH FS x (2) 2.5" NH male HR	\$1,265.00
H202-25NHM-25NHFS	2-Way Leader-Line Wye Ball Valve Mid-Size	2.5" NH male x (2) 2.5" NH FS	\$1,450.00
H202-25-25ST	2-Way Leader-Line Wye Ball Valve Mid-Size	2.5" Storz x (2) 2.5" Storz	\$1,320.00
H202-30NHFS-15NH	2-Way Leader-Line Wye Ball Valve Mid-Size	3" NH FS x (2) 1.5" NH male	\$1,605.00
H202-30NHFS-25NH	2-Way Leader-Line Wye Ball Valve Mid-Size	3" NH FS x (2) 2.5" NH male	\$1,300.00
H202-30-30ST	2-Way Leader-Line Wye Ball Valve Mid-Size	3" Storz x (2) 3" Storz	\$1,175.00



H300 - 3-Way LDH Wye Ball Valve - Relief Valve

The Harrington Model H300 mid -size 3-way wye ball valve shall be designed for feeding three (3) lines from an LDH line or supplying an LDH line with three (3) smaller lines the design permits feeding from either direction. The valve shall include three (3) hard anodized ball valves with stainless steel tappets for corrosion resistance and aluminum control handles. The aluminum valve body shall be powder coated gray in color. The valves feature a variety of inlet connections in Storz and NH and in sizes from 4" to 6". Units with NH female swivels shall have rocker lugs or LHs. Storz units with 4" and larger sizes have locking devices. An adjustable relief valve shall be installed with increments of 25 PSI from 75 PSI to 250 PSI, pre -set at 125 PSI.



APPROXIMATE DIMENSIONS: 13.5"L x 13"W x 11"H

H300-40-25NH	3-Way LDH Wye Ball Valve 4" Storz/Lok x (3) 2.5" NH male Rif Vlv	\$2,575.00
H300-40-25NHFS	3-Way LDH Wye Ball Valve 4" Storz/Lok x (3) 2.5" NH FS Rif Vlv	\$2,894.00
H300-40-25ST	3-Way LDH Wye Ball Valve 4" Storz/Lok x (3) 2.5" Storz Rif Vlv	\$2,763.00
H300-40-30ST	3-Way LDH Wye Ball Valve 4" Storz/Lok x (3) 3" Storz Rif Vlv	\$2,744.00
H300-40NHFS-25NH	3-Way LDH Wye Ball Valve 4" NH FS R/L x (3) 2.5" NH male Rif Vlv	\$2,519.00
H300-40NHFS-25NHFS	3-Way LDH Wye Ball Valve 4" NH FS R/L x (3) 2.5" NH FS Rif Vlv	\$2,838.00
H300-45NHFS-25NH	3-Way LDH Wye Ball Valve 4.5" NH FS R/L x (3) 2.5" NH male Rif Vlv	\$2,531.00
H300-50-25NH	3-Way LDH Wye Ball Valve 5" Storz/Lok x (3) 2.5" NH male Rif Vlv	\$2,506.00
H300-50-25NH/FTS	3-Way LDH Wye Ball Valve 5" Storz/Lok (FTS) x (3) 2.5" NH male Rif Vlv	\$2,956.00
H300-50-25NHFS	3-Way LDH Wye Ball Valve 5" Storz/Lok x (3) 2.5" NH FS Rif Vlv	\$2,819.00
H300-50-25NHFS/FTS	3-Way LDH Wye Ball Valve 5" Storz/Lok (FTS) x (3) 2.5" NH FS Rif Vlv	\$3,269.00
H300-50-25ST	3-Way LDH Wye Ball Valve 5" Storz/Lok x (3) 2.5" Storz Rif Vlv	\$2,694.00
H300-50-30ST	3-Way LDH Wye Ball Valve 5" Storz/Lok x (3) 3" Storz Rif Vlv	\$2,675.00
H300-50NHFS-25NH	3-Way LDH Wye Ball Valve 5" NH FS R/L x (3) 2.5" NH male Rif Vlv	\$2,544.00
H300-50NHFS-25NHFS	3-Way LDH Wye Ball Valve 5" NH FS R/L x (3) 2.5" NH FS Rif Vlv	\$2,856.00
H300-60-25NH	3-Way LDH Wye Ball Valve 6" Storz/Lok inlet x (3) 2.5" NH male Rif Vlv	\$2,750.00
H300-60-25NHFS	3-Way LDH Wye Ball Valve 6" Storz/Lok x (3) 2.5" NH FS Rif Vlv	\$3,194.00
H300-60-25ST	3-Way LDH Wye Ball Valve 6" Storz/Lok x (3) 2.5" Storz Rif Vlv	\$3,538.00
H300-60-30ST	3-Way LDH Wye Ball Valve 6" Storz/Lok x (3) 3" Storz Rif Vlv	\$3,519.00
H300-60NHFS-25NH	3-Way LDH Wye Ball Valve 6" NH FS R/L x (3) 2.5" NH male Rif Vlv	\$2,663.00
H300-60NHFS-25NHFS	3-Way LDH Wye Ball Valve 6" NH FS R/L x (3) 2.5" NH FS Rif Vlv	\$2,975.00



H600 - Super-Flow 2-Way LDH Wye Ball Valve - Relief Valve



The Harrington Model H600 2-way LDH 'SUPER-FLOW' ball valve shall be designed with a one (1) LDH inlet to supply two (2) outlets OR two (2) LDH supply lines and one (1) LDH outlet and the design permits water flow in either direction. The SUPER-FLOW ball valve shall have low friction-loss due to a high flow waterway design. The valve shall include two (2) hard anodized ball valves, with stainless-steel tappets for corrosion resistance and aluminum control handles. The aluminum valve body shall be powder-coated gray in color. The valve inlet and outlet connections are available in Storz and NH and in sizes from 4" to 6". Units with NH female swivel inlets shall have rocker lugs or LHs. All Storz connections 4" and larger shall have locking devices. An adjustable relief valve shall be installed with increments of 25 PSI from 75 PSI to 250 PSI, pre-set at 125 PSI.

APPROXIMATE DIMENSIONS: 18"L x 16"W x 12"H

H600-40-40ST	2-Way Super-Flow LDH Wye Ball Valve	4" Storz/Lok x (2) 4" Storz/Lok Rif Vlv	\$5,819.00
H600-40NHFS-40NHM	2-Way Super-Flow LDH Wye Ball Valve	4" NH FS x (2) 4" NH male Rif Vlv	\$5,275.00
H600-45NHFS-40NHM	2-Way Super-Flow LDH Wye Ball Valve	4.5" NH FS x (2) 4" NH male Rif Vlv	\$5,256.00
H600-45NHFS-50ST	2-Way Super-Flow LDH Wye Ball Valve	4.5" NH FS x (2) 5" Storz/Lok Rif Vlv	\$5,631.00
H600-50-40ST	2-Way Super-Flow LDH Wye Ball Valve	5" Storz/Lok x (2) 4" Storz/Lok Rif Vlv	\$5,750.00
H600-50-50ST	2-Way Super-Flow LDH Wye Ball Valve	5" Storz/Lok x (2) 5" Storz/Lok Rif Vlv	\$5,606.00
H600-50-50ST/FTS	2-Way Super-Flow LDH Wye Ball Valve	5" Storz/Lok (FTS) x (2) 5" Storz/Lok Rif Vlv	\$6,056.00
H600-50NHFS-50NHM	2-Way Super-Flow LDH Wye Ball Valve	5" NH FS x (2) 5" NH male Rif Vlv	\$5,350.00
H600-60-40ST	2-Way Super-Flow LDH Wye Ball Valve	6" Storz/Lok x (2) 4" Storz/Lok Rif Vlv	\$5,988.00
H600-60NHFS-40ST	2-Way Super-Flow LDH Wye Ball Valve	6" NH FS x (2) 4" Storz/Lok Rif Vlv	\$5,900.00
H600-60NPSHFS-40ST	2-Way Super-Flow LDH Wye Ball Valve	6" NPSH FS x (2) 4" Storz/Lok Rif Vlv	\$5,900.00
H600-60-50ST	2-Way Super-Flow LDH Wye Ball Valve	6" Storz/Lok x (2) 5" Storz/Lok Rif Vlv	\$5,850.00
H600-60NHFS-50ST	2-Way Super-Flow LDH Wye Ball Valve	6" NH FS x (2) 5" Storz/Lok Rif Vlv	\$5,756.00
H600-60NPSHFS-50ST	2-Way Super-Flow LDH Wye Ball Valve	6" NPSH FS x (2) 5" Storz/Lok Rif Vlv	\$5,756.00
H600-60-60ST	2-Way Super-Flow LDH Wye Ball Valve	6" Storz/Lok x (2) 6" Storz/Lok Rif Vlv	\$6,344.00
H600-60NHFS-60NHM	2-Way Super-Flow LDH Wye Ball Valve	6" NH FS x (2) 6" NH male Rif Vlv	\$5,506.00



H301 - 1" to 3" 3-Way Water-Thief Ball Valve

The Harrington Model H301 small 3-way 'water-thief' ball valve shall be designed for high-rise applications, with one (1) supply inlet and three (3) outlet lines. The valve shall include three (3) hard anodized ball valves, with stainless-steel tappets for corrosion resistance and aluminum control handles. The lightweight aluminum valve body shall be powder-coated red in color. The valve inlet connections are available in Storz and NH and in sizes from 1.5" to 3". Units with NH female swivels shall have rocker lugs. All Storz connections 4" and larger shall have locking devices.



APPROXIMATE DIMENSIONS: 12"L x 12"W x 10"H

H301-15NHFS-15NH	3-Way Water-Thief Ball Valve 1.5" NH FS R/L x (3) 1.5" NH male	\$1,638.00
H301-25NHFS-15NH	3-Way Water-Thief Ball Valve 2.5" NH FS R/L x (3) 1.5" NH male	\$1,644.00
H301-25-15ST	3-Way Water-Thief Ball Valve 2.5" Storz x (3) 1.5" Storz	\$1,850.00
H301-25NHFS-25NH-15NH	3-Way Water-Thief Ball Valve 2.5" NH FS x (1) 2.5" NH male & (2) 1.5" NH male	\$1,575.00
H301-25-25-15ST	3-Way Water-Thief Ball Valve 2.5" Storz x (1) 2.5" Storz & (2) 1.5" Storz	\$1,513.00
H301-25NHFS-25NH	3-Way Water-Thief Ball Valve 2.5" NH FS x (3) 2.5" NH male	\$1,675.00
H301-25-25ST	3-Way Water-Thief Ball Valve 2.5" Storz x (3) 2.5" Storz	\$1,513.00
H301-30NHFS-25NH-15NH	3-Way Water-Thief Ball Valve 3" NH FS x (1) 2.5" NH male & (2) 1.5" NH male	\$1,713.00
H301-30NHFS-25NHM	3-Way Water-Thief Ball Valve 3" NH FS x (3) 2.5" NH male	\$1,813.00
H301-30-25ST	3-Way Water-Thief Ball Valve 3" Storz x (3) 2.5" Storz	\$1,506.00

H301 - 4" to 6" 3-Way LDH Water-Thief Ball Valve - Relief Valve

The Harrington Model H301 3-way LDH 'water-thief' ball valve shall be designed with one (1) inlet with two (2) smaller outlets and one (1) 'straight-through' LDH outlet. The valve shall include three (3) hard anodized ball valves, with stainless steel tappets for corrosion resistance and aluminum control handles. The aluminum valve body shall be powder coated gray in color. The valve inlet connections are available in Storz and NH and in sizes from 4" to 6". Units with NH female swivel inlets shall have rocker lugs. All Storz connections 4" and larger shall have locking devices. A relief valve shall be installed under the inlet, with adjustable in increments of 25 PSI from 75 PSI to 250 PSI, pre-set at 125 PSI.



APPROXIMATE DIMENSIONS: 16"L x 16"W x 13"

H301-40-40-25NH	3-Way LDH Water-Thief Ball Valve 4" Storz/Lok x (1) 4" Storz/Lok & (2) 2.5" NH male Rlf Vlv	\$4,594.00
H301-40NHFS-40NHM-25NH	3-Way LDH Water-Thief Ball Valve 4" NH FS x (1) 4" NH male & (2) 2.5" NH male Rlf Vlv	\$4,431.00



H301-40-40-25NHFS	3-Way LDH Water-Thief Ball Valve 4" Storz/Lok x (1) 4" Storz/Lok & (2) 2.5" NH FS Rif Vlv	\$4,756.00
H301-45NHFS-40-25NH	3-Way LDH Water-Thief Ball Valve 4.5" NH FS x (1) 4" Storz/Lok & (2) 2.5" NH male Rif Vlv	\$4,563.00
H301-45NHFS-45NHM-25NH	3-Way LDH Water-Thief Ball Valve 4.5" NH FS x (1) 4.5" NH male & (2) 2.5" NH male Rif Vlv	\$4,475.00
H301-50-40-25NH	3-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 4" Storz/Lok & (2) 2.5" NH male Rif Vlv	\$4,519.00
H301-50-40-25NHFS	3-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 4" Storz/Lok & (2) 2.5" NH FS Rif Vlv	\$4,688.00
H301-50-50-25NH	3-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (2) 2.5" NH male Rif Vlv	\$4,725.00
H301-50-50-25NH/FTS	3-Way LDH Water-Thief Ball Valve 5" Storz/Lok (FTS) x (1) 5" Storz/Lok & (2) 2.5" NH male Rif Vlv	\$5,175.00
H301-50-50-25ST	3-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (2) 2.5" Storz Rif Vlv	\$4,913.00
H301-50-50-30ST	3-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (2) 3" Storz Rif Vlv	\$4,888.00
H301-60-60-25NH	3-Way LDH Water-Thief Ball Valve 6" Storz/Lok x (1) 6" Storz/Lok & (2) 2.5" NH male Rif Vlv	\$5,081.00
H301-60NHFS-60NHM-25NH	3-Way LDH Water-Thief Ball Valve 6" NH FS x (1) 6" NH male & (2) 2.5" NH male Rif Vlv	\$4,669.00
H301-60NHFS-60NHM-25NHFS	3-Way LDH Water-Thief Ball Valve 6" NH FS x (1) 6" NH male & (2) 2.5" NH FS Rif Vlv	\$4,813.00

SPECIAL THREADS: available on request. 1" to 6" = \$20.00



See Page 73 Post Mount



H400 - 5-Way LDH Water-Thief Ball Valve - Relief Valve

The Harrington Model H400 5-way LDH 'water-thief' ball valve shall be designed with one (1) LDH inlet with four (4) smaller outlets and one (1) 'straight-through' LDH outlet. The valve shall include four (4) hard anodized ball valves, with stainless-steel tappets for corrosion resistance and aluminum control handles. The aluminum valve body shall be powder-coated gray in color. The valve inlet connections are available in Storz and NH and in sizes from 4" to 6". Smaller outlets are available in 2.5" and 3" size. Units with NH female swivel inlets shall have rocker lugs. Storz connections 4" and larger shall have locking devices. A relief valve shall be installed under the inlet, with adjustable in increments of 25 PSI from 75 PSI to 250 PSI, pre-set at 125 PSI.



APPROXIMATE DIMENSIONS: 17"L x 24"W x 13"H

H400-40-40-25NH	5-Way LDH Water-Thief Ball Valve 4" Storz/Lok x (1) 4" Storz/Lok & (4) 2.5" NH male Rlf Vlv	\$5,206.00
H400-40-40-25NHFS	5-Way LDH Water-Thief Ball Valve 4" Storz/Lok x (1) 4" Storz/Lok & (4) 2.5" NH FS Rlf Vlv	\$5,656.00
H400-40NHFS-40NHM-25NH	5-Way LDH Water-Thief Ball Valve 4" NH FS x (1) 4" NH male & (4) 2.5" NH male Rlf Vlv	\$4,794.00
H400-45NHFS-45NHM-25NH	5-Way LDH Water-Thief Ball Valve 4.5" NH FS x (1) 4.5" NH male & (4) 2.5" NH male Rlf Vlv	\$5,081.00
H400-50-40-25NH	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 4" Storz/Lok & (4) 2.5" NH male Rlf Vlv	\$5,131.00
H400-50-40-25NHFS	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 4" Storz/Lok & (4) 2.5" NH FS Rlf Vlv	\$5,581.00
H400-50-50-25NH	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (4) 2.5" NH male Rlf Vlv	\$5,338.00
H400-50-50-25NH/FTS	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok (FTS) x (1) 5" Storz/Lok & (4) 2.5" NH male Rlf Vlv	\$5,788.00
H400-50-50-25NHFS	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (4) 2.5" NH FS Rlf Vlv	\$5,788.00
H400-50-50-25NPSH	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (4) 2.5" NPSH male Rlf Vlv	\$5,338.00
H400-50-50-25ST	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (4) 2.5" Storz Rlf Vlv	\$5,555.00
H400-50-50-30ST	5-Way LDH Water-Thief Ball Valve 5" Storz/Lok x (1) 5" Storz/Lok & (4) 3" Storz Rlf Vlv	\$5,775.00
H400-60-60-25NH	5-Way LDH Water-Thief Ball Valve 6" Storz/Lok x (1) 6" Storz/Lok & (4) 2.5" NH male Rlf Vlv	\$5,688.00
H400-60-60-25NPSH	5-Way LDH Water-Thief Ball Valve 6" Storz/Lok x (1) 6" Storz/Lok & (4) 2.5" NPSH male Rlf Vlv	\$5,688.00
H400-60-60-25ST	5-Way LDH Water-Thief Ball Valve 6" Storz/Lok x (1) 6" Storz/Lok & (4) 2.5" Storz Rlf Vlv	\$5,969.00
H400-60-60-30ST	5-Way LDH Water-Thief Ball Valve 6" Storz/Lok x (1) 6" Storz/Lok & (4) 3" Storz Rlf Vlv	\$5,944.00



H700 - “HYDRANT-ASSIST” LDH Hydrant Ball Valve

The Harrington Model H700 “Hydrant-Assist” valve shall be designed with a one (1) LDH inlet and three (3) additional LDH connections for the following applications:



A) The valves are designed for boosting pressure on ‘long hose lays’
- OR -

B) For boosting low hydrant pressures:

1) The Hydrant-Assist valve enables the ‘first-in pumper’ to lay LDH directly from the hydrant to

the fire; when hose lay is completed, start water flowing from the hydrant.

2) If additional pressure is required, another pumper can connect to the Hydrant-Assist valve and start pumping to raise water pressure and flow without interrupting the established water supply.

The lightweight aluminum valve has low friction-loss due to a high- flow waterway design: friction loss at 1000 GPM is 3.3 PSI. Maximum working pressure: 250 PSI. The valve includes an ‘emergency shut- off valve’ with a hard anodized ball and aluminum control handle. The aluminum valve body shall be powder coated gray in color. The valve inlet and outlet connections are available in Storz and NH and in sizes from 4” to 5”. NH female swivel inlets have LHs. Storz connections shall have locking devices. Warranty: 2 years.

APPROXIMATE DIMENSIONS: 12.75”L x 17”W x 13” H

H700-40-40NH	5” Hydrant-Assist Ball Valve	4” NH FS LH x (3) 4” Storz/Lok	\$5,625.00
H700-40-40ST	5” Hydrant-Assist Ball Valve	4” Storz/Lok (PTS) x (3) 4” Storz/Lok	\$5,831.00
H700-40-45NH	5” Hydrant-Assist Ball Valve	4.5” NH FS LH x (3) 4” Storz/Lok	\$5,442.00
H700-40-50NH	5” Hydrant-Assist Ball Valve	5” NH FS LH x (3) 4” Storz/Lok	\$5,644.00
H700-45-40-45-40	5” Hydrant-Assist Ball Valve	4.5” NH FS LH x 4” Storz/Lok, 4.5” NHM & 4” Storz/Lok	\$5,413.00
H700-50-40NH	5” Hydrant-Assist Ball Valve	4” NH FS LH x (3) 5” Storz/Lok	\$5,413.00
H700-50-40ST	5” Hydrant-Assist Ball Valve	4” Storz/Lok (PTS) x (3) 5” Storz/Lok	\$5,613.00
H700-50-45NH	5” Hydrant-Assist Ball Valve	4.5” NH FS LH x (3) 5” Storz/Lok	\$5,200.00
H700-45-50-45-50	5” Hydrant-Assist Ball Valve	4.5” NH FS LH x 5” Storz/Lok, 4.5” NHM & 5” Storz/Lok	\$5,450.00
H700-50-50NH	5” Hydrant-Assist Ball Valve	5” NH FS LH x (3) 5” Storz/Lok	\$5,425.00
H700-50-50ST	5” Hydrant-Assist Ball Valve	5” Storz/Lok (PTS) x (3) 5” Storz/Lok	\$5,556.00



HHBV - 2.5" Hydrant Ball Valve

The Harrington Model HHBV 2.5" fire hydrant quarter-turn ball valve shall be designed for dual fire hydrant connections, tanker refill connections, in-line water flow applications, and other portable uses for control of water flow. Each unit includes a hard -anodized 2" water-way ball valve, with stainless-steel tappets for corrosion resistance, and aluminum control handle. The lightweight anodized aluminum valve body shall be powder-coated gray in color. Valves feature NH, NPSH, NPT, special -thread, rigid, and Storz connections and sizes. Female swivel connections have rocker lugs or LHs. Storz connections over 4" have locking devices. Valves have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 5.5"L x 4"W x 7"H

HHBV-25NHM-25NH	2.5" Hydrant Ball Valve 2.5" NH male x 2.5" NH FS	\$800.00
HHBV-25NHM-25NHLH	2.5" Hydrant Ball Valve 2.5" NH male x 2.5" NH female LH swivel	\$831.00
HHBV-25NHM-25NPSH	2.5" Hydrant Ball Valve 2.5" NH male x 2.5" NPSH FS	\$800.00
HHBV-25NPTM-25NH	2.5" Hydrant Ball Valve 2.5" NPT male x 2.5" NH FS	\$931.00
HHBV-25NPTM-25NPSH	2.5" Hydrant Ball Valve 2.5" NPT male x 2.5" NPSH FS	\$931.00
HHBV-25-xxx-25-xxx	2.5" Hydrant Ball Valve 2.5" special thread male x 2.5" special thread FS	\$956.00
HHBV-25NHFS-25NHFS	2.5" Hydrant Ball Valve 2.5" NH FS x 2.5" NH FS	\$931.00
HHBV-25NHM-25NPTF	2.5" Hydrant Ball Valve 2.5" NH male x 2.5" NPT female rigid	\$800.00
HHBV-25-25NH	2.5" Hydrant Ball Valve 2.5" Storz x 2.5" NH FS	\$919.00
HHBV-25-25NPSH	2.5" Hydrant Ball Valve 2.5" Storz x 2.5" NPSH FS	\$919.00
HHBV-30-25NH	2.5" Hydrant Ball Valve 3" Storz x 2.5" NH FS	\$913.00
HHBV-30-25NPSH	2.5" Hydrant Ball Valve 3" Storz x 2.5" NPSH FS	\$913.00
HHBV-40-25NH	2.5" Hydrant Ball Valve 4" Storz/Lok x 2.5" NH FS	\$1,156.00
HHBV-40-25NHLH	2.5" Hydrant Ball Valve 4" Storz/Lok x 2.5" NH FS LH	\$1,188.00
HHBV-40-25NHM	2.5" Hydrant Ball Valve 4" Storz/Lok x 2.5" NH male	\$1,069.00
HHBV-50-25NH	2.5" Hydrant Ball Valve 5" Storz/Lok x 2.5" NH FS	\$1,256.00
HHBV-50-25NHM	2.5" Hydrant Ball Valve 5" Storz/Lok x 2.5" NH male	\$1,175.00



HHGV - 2.5" Hydrant Gate Valve



The Harrington Model HHGV 2.5" fire hydrant gate valve shall be designed for fire hydrant connections and portable uses for water flow control. The 2.25" waterway gate valve shall have a non-rising stem, with aluminum spindle, and rotating hand -wheel control handle for slow-close and easy opening & closing operation. The lightweight anodized aluminum valve body shall be powder -coated gray in color. Valve shall feature 2.5" NH, NPSH, NPT, special thread, rigid, and Storz connections. Female swivel connections have rocker lugs. The valve shall have a maximum of 250 PSI working pressure.

APPROXIMATE DIMENSIONS: 6"L x 5"W x 9"H

HHGV-25NHM-25NH	2.5" Hydrant Gate Valve	2.5" NH male x 2.5" NH FS	\$744.00
HHGV-25-xxxM-25-xxx	2.5" Hydrant Gate Valve	2.5" special thread male x 2.5" special thread FS	\$888.00
HHGV-HD-25NHM-25NH	2.5" Hydrant Gate Valve	2.5" NH male x 2.5" NH FS (HEAVY DUTY)	\$855.00
HHGV-HD-25-xxxM-25-xxx	2.5" Hydrant Gate Valve	2.5" special thread male x 2.5" special thread FS (Heavy Duty)	\$969.00
HHGV-25NHM-25NPSH	2.5" Hydrant Gate Valve	2.5" NH male x 2.5" NPSH FS	\$744.00
HHGV-25NHM-25NPTF	2.5" Hydrant Gate Valve	2.5" NH male x 2.5" NPT female rigid	\$819.00
HHGV-25NPTM-25NPSHFS	2.5" Hydrant Gate Valve	2.5" NPT male x 2.5" NPSH FS	\$860.00
HHGV-25NHFS-25NHFS	2.5" Hydrant Gate Valve	2.5" NH FS x 2.5" NH FS	\$975.00

Standard Gate Valves

H800 - 4" Straight LDH Gate Valve



The Harrington Model H800 straight gate valve shall be designed for hydrant discharge control. The valve shall have a 4" waterway and handwheel gate control with non- rising stem, stainless-steel spindle, and anodized gate. Valve shall be compliant to NFPA standards for slow-close & opening operation. Low friction loss of 0.5 PSI at 1000 GPM. The lightweight anodized aluminum valve body shall be powder coated gray in color. The valve features NH, NPSH, NPT threads and/or Storz 4" and larger with locking connections. Female swivel connections have rocker lugs or LHs. Bleeder valve shall be .250" brass. The valve shall have a maximum of 250 PSI working pressure. .

APPROXIMATE DIMENSIONS: 10.5"L x 6"W x 14"H



H800-40-40NH	4" Straight LDH Gate Valve 4" Storz/Lok x 4" NH FS R/L	\$2,175.00
H800-40-40NHLH	4" Straight LDH Gate Valve 4" Storz/Lok x 4" NH FS LH	\$2,188.00
H800-40-40NPSH	4" Straight LDH Gate Valve 4" Storz/Lok x 4" NPSH FS R/L	\$2,175.00
H800-40-40NPSHLH	4" Straight LDH Gate Valve 4" Storz/Lok x 4" NPSH FS LH	\$2,188.00
H800-40-40ST	4" Straight LDH Gate Valve 4" Storz/Lok (PTS) x 4" Storz/Lok	\$2,388.00
H800-40NHFS-40NHFS	4" Straight LDH Gate Valve 4" NH FS R/L x 4" NH FS R/L	\$2,213.00
H800-40NPSHFS-40NPSHFS	4" Straight LDH Gate Valve 4" NPSH FS R/L x 4" NPSH FS R/L	\$2,213.00
H800-40NHM-40NH	4" Straight LDH Gate Valve 4" NH male x 4" NH FS R/L	\$2,075.00
H800-40NHM-40NHLH	4" Straight LDH Gate Valve 4" NH male x 4" NH FS LH	\$2,081.00
H800-40NHM-40NPSH	4" Straight LDH Gate Valve 4" NH male x 4" NPSH FS R/L	\$2,075.00
H800-40NPTM-40NPSH	4" Straight LDH Gate Valve 4" NPT male x 4" NPSH FS R/L	\$2,113.00
H800-40-45NH	4" Straight LDH Gate Valve 4" Storz/Lok x 4.5" NH FS R/L	\$2,156.00
H800-40-45NHLH	4" Straight LDH Gate Valve 4" Storz/Lok x 4.5" NH FS LH	\$2,169.00
H800-40NHM-45NH	4" Straight LDH Gate Valve 4" NH male x 4.5" NH FS R/L	\$2,050.00
H800-40NHM-45NHLH	4" Straight LDH Gate Valve 4" NH male x 4.5" NH FS LH	\$2,063.00
H800-40-50NH	4" Straight LDH Gate Valve 4" Storz/Lok x 5" NH FS R/L	\$2,219.00
H800-40-60NH	4" Straight LDH Gate Valve 4" Storz/Lok x 6" NH FS R/L	\$2,313.00
H800-40-60NH/Cap	4" Straight LDH Gate Valve 4" Storz/Lok Cap/Cbl x 6" NH FS R/L	\$2,500.00
H800-40-60NHLH	4" Straight LDH Gate Valve 4" Storz/Lok x 6" NH FS LH	\$2,319.00
H800-40-60NPSH	4" Straight LDH Gate Valve 4" Storz/Lok x 6" NPSH FS R/L	\$2,313.00
H800-45NHM-45NH	4" Straight LDH Gate Valve 4.5" NH male x 4.5" NH FS R/L	\$2,081.00
H800-45NHM-45NHLH	4" Straight LDH Gate Valve 4.5" NH male x 4.5" NH FS LH	\$2,094.00
H800-50-40NH	4" Straight LDH Gate Valve 5" Storz/Lok x 4" NH FS R/L	\$2,363.00
H800-50-40NHLH	4" Straight LDH Gate Valve 5" Storz/Lok x 4" NH FS LH	\$2,388.00
H800-50-45NH	4" Straight LDH Gate Valve 5" Storz/Lok x 4.5" NH FS R/L	\$2,356.00
H800-50-45NHLH	4" Straight LDH Gate Valve 5" Storz/Lok x 4.5" NH FS LH	\$2,369.00
H800-50-50NH	4" Straight LDH Gate Valve 5" Storz/Lok x 5" NH FS R/L	\$2,425.00
H800-50-50ST	4" Straight LDH Gate Valve 5" Storz/Lok (PTS) x 5" Storz/Lok	\$2,531.00
H800-50NHM-50NH	4" Straight LDH Gate Valve 5" NH male x 5" NH FS R/L	\$2,100.00
H800-50-60NH	4" Straight LDH Gate Valve 5" Storz/Lok x 6" NH FS R/L	\$2,513.00
H800-50-60NH/Cap	4" Straight LDH Gate Valve 5" Storz/Lok Cap/Cbl x 6" NH FS R/L	\$2,756.00
H800-50-60NHLH	4" Straight LDH Gate Valve 5" Storz/Lok x 6" NH FS LH	\$2,519.00
H800-50-60NPSH	4" Straight LDH Gate Valve 5" Storz/Lok x 6" NPSH FS R/L	\$2,513.00
H800-50-60NPSHLH	4" Straight LDH Gate Valve 5" Storz/Lok x 6" NPSH FS LH	\$2,519.00
H800-60-60NH	4" Straight LDH Gate Valve 6" Storz/Lok x 6" NH FS R/L	\$2,619.00
H800-60-60NHLH	4" Straight LDH Gate Valve 6" Storz/Lok x 6" NH FS LH	\$2,625.00
H800-60NHM-60NH	4" Straight LDH Gate Valve 6" NH male x 6" NH FS R/L	\$2,300.00
H800-60NHM-60NHLH	4" Straight LDH Gate Valve 6" NH male x 6" NH FS LH	\$2,313.00
H800-60NHM-60NPSH	4" Straight LDH Gate Valve 6" NH male x 6" NPSH FS R/L	\$2,300.00



H810 - 4" LDH Gate Valve - 25° Elbow - Relief Valve



The Harrington Model H810 -RV LDH fire hydrant gate valve shall incorporate a 25° elbow, 4" waterway, handwheel gate control with non -rising stem, stainless-steel spindle, and anodized gate. Valve shall meet NFPA standards for slow -close & opening operation. It shall have low friction loss of 0.8 PSI at 1000 GPM. The lightweight hard -coat anodized aluminum valve body shall be powder -coated gray in color. An adjustable relief valve shall be installed with increments of 25 PSI from 75 PSI to 250 PSI, pre -set at 125 PSI. The valve shall feature NH or NPSH threads and/or Storz 4" and larger with locking connections. Female swivel connections have rocker lugs or long handles. Bleeder valve shall be .250" brass. The valve have a maximum of 250 PSI working pressure.

APPROXIMATE DIMENSIONS: 12.5"L x 7"W x 15"H

H810-40-40NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4" NH FS R/L Rif Vlv	\$3,100.00
H810-40-40NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4" NH FS LH Rif Vlv	\$3,113.00
H810-40-40NPSH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4" NPSH FS R/L Rif Vlv	\$3,100.00
H810-40-40ST	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4" Storz/Lok (PTS) Rif Vlv	\$3,319.00
H810-40NHM-40NH	4" LDH Gate Valve 25° Elbow 4" NH male x 4" NH FS R/L Rif Vlv	\$3,000.00
H810-40NHM-40NPSH	4" LDH Gate Valve 25° Elbow 4" NH male x 4" NPSH FS R/L Rif Vlv	\$3,000.00
H810-40-45NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4.5" NH FS R/L Rif Vlv	\$3,081.00
H810-40-45NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4.5" NH FS LH Rif Vlv	\$3,094.00
H810-40-50NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 5" NH FS R/L Rif Vlv	\$3,150.00
H810-40-50NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 5" NH FS LH Rif Vlv	\$3,150.00
H810-40-60NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 6" NH FS R/L Rif Vlv	\$3,238.00
H810-40-60NH/Cap	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 6" NH FS R/L Rif Vlv Cap	\$3,425.00
H810-40-60NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 6" NH FS LH Rif Vlv	\$3,244.00
H810-45NHM-45NH	4" LDH Gate Valve 25° Elbow 4.5" NH male x 4.5" NH FS R/L Rif Vlv	\$3,006.00
H810-50-40NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4" NH FS R/L Rif Vlv	\$3,306.00
H810-50-40NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4" NH FS LH Rif Vlv	\$3,319.00
H810-50-40NPSH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4" NPSH FS R/L Rif Vlv	\$3,306.00
H810-50-45NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4.5" NH FS R/L Rif Vlv	\$3,281.00
H810-50-45NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4.5" NH FS LH Rif Vlv	\$3,300.00
H810-50-50NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" NH FS R/L Rif Vlv	\$3,350.00
H810-50-50NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" NH FS LH Rif Vlv	\$3,350.00
H810-50-50NPSH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" NPSH FS R/L Rif Vlv	\$3,350.00
H810-50-50ST	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" Storz/Lok Rif Vlv	\$3,456.00
H810-50NHM-50NH	4" LDH Gate Valve 25° Elbow 5" NH male (PTS) x 5" NH FS R/L Rif Vlv	\$3,044.00
H810-50NHM-50NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" NH FS LH Rif Vlv	\$3,044.00
H810-50-60NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 6" NH FS R/L Rif Vlv	\$3,444.00
H810-50-60NH/Cap	4" LDH Gate Valve 25° Elbow 5" Storz/Lok Cap/Cbl x 6" NH FS R/L Rif Vlv	\$3,688.00
H810-50-60NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 6" NH FS LH Rif Vlv	\$3,456.00
H810-50-60NPSH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 6" NPSH FS R/L Rif Vlv	\$3,444.00
H810-60-60NH	4" LDH Gate Valve 25° Elbow 6" Storz/Lok x 6" NH FS R/L Rif Vlv	\$3,550.00
H810-60-60NPSH	4" LDH Gate Valve 25° Elbow 6" Storz/Lok x 6" NPSH FS R/L Rif Vlv	\$3,550.00
H810-60NHFS-60NH	4" LDH Gate Valve 25° Elbow 6" NH FS R/L x 6" NH FS R/L Rif Vlv	3,388.00
H810-60NHM-60NH	4" LDH Gate Valve 25° Elbow 6" NH male x 6" NH FS R/L Rif Vlv	3,231.00



H811 - 4" LDH Gate Valve - 25° Elbow

The Harrington Model H811 LDH fire hydrant gate valve shall incorporate a 25° elbow with 4" waterway, handwheel gate control with non-rising stem, stainless steel spindle, and anodized gate. The valve shall meet NFPA standards for slow-close & opening operation. Low friction loss of 0.8 PSI at 1000 GPM. The lightweight anodized aluminum valve body shall be powder coated gray in color. The valve feature NH or NPSH threads and/or Storz 4" and larger with locking connections. Female swivel connections have rocker lugs or LHs. Bleeder valve shall be .250" brass. Valve shall have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 12.5"L x 7"W x 15"H

H811-40-40NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4" NH FS R/L	\$2,313.00
H811-40-40NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4" NH FS LH	\$2,325.00
H811-40-40NPSH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4" NPSH FS R/L	\$2,313.00
H811-40-40ST	4" LDH Gate Valve 25° Elbow 4" Storz/Lok (PTS) x 4" Storz/Lok	\$2,525.00
H811-40NHM-40NH	4" LDH Gate Valve 25° Elbow 4" NH male x 4" NH FS R/L	\$2,206.00
H811-40NHM-40NPSH	4" LDH Gate Valve 25° Elbow 4" NH male x 4" NPSH FS R/L	\$2,206.00
H811-40-45NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4.5" NH FS R/L	\$2,294.00
H811-40-45NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 4.5" NH FS LH	\$2,306.00
H811-40-50NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 5" NH FS R/L	\$2,356.00
H811-40-50NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 5" NH FS LH	\$2,356.00
H811-40-50NPSH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 5" NPSH FS R/L	\$2,356.00
H811-40-60NH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 6" NH FS R/L	\$2,450.00
H811-40-60NH/Cap	4" LDH Gate Valve 25° Elbow 4" Storz/Lok Cap/Cbl x 6" NH FS R/L	\$2,638.00
H811-40-60NHLH	4" LDH Gate Valve 25° Elbow 4" Storz/Lok x 6" NH FS LH	\$2,456.00
H811-45NHM-45NH	4" LDH Gate Valve 25° Elbow 4.5" NH male x 4.5" NH FS R/L	\$2,219.00
H811-50-40NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4" NH FS R/L	\$2,513.00
H811-50-40NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4" NH FS LH	\$2,525.00
H811-50-45NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4.5" NH FS R/L	\$2,494.00
H811-50-45NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 4.5" NH FS LH	\$2,506.00
H811-50-50NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" NH FS R/L	\$2,556.00
H811-50-50NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" NH FS LH	\$2,525.00
H811-50-50NPSH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 5" NPSH FS R/L	\$2,556.00
H811-50-50ST	4" LDH Gate Valve 25° Elbow 5" Storz/Lok (PTS) x 5" Storz/Lok	\$2,594.00
H811-50NHM-50NH	4" LDH Gate Valve 25° Elbow 5" NH male x 5" NH FS R/L	\$2,256.00
H811-50-60NH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 6" NH FS R/L	\$2,650.00
H811-50-60NH/Cap	4" LDH Gate Valve 25° Elbow 5" Storz/Lok Cap/Cbl x 6" NH FS R/L	\$2,894.00
H811-50-60NHLH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 6" NH FS LH	\$2,456.00
H811-50-60NPSH	4" LDH Gate Valve 25° Elbow 5" Storz/Lok x 6" NPSH FS R/L	\$2,650.00
H811-60NHM-60NH	4" LDH Gate Valve 25° Elbow 6" NH male x 6" NH FS R/L	\$2,438.00



H800F - 4" Straight LDH Gate Valve - FLANGED



The Harrington Model H800F straight gate valve shall have a 4" flanged waterway inlet, with handwheel gate control with non-rising stem, stainless steel spindle, and anodized gate. The valve shall be compliant to NFPA standards for slow-close & opening operation. Low friction loss of 0.5 PSI at 1000 GPM. The lightweight anodized aluminum valve body shall be powder-coated gray in color. The valve features a flanged inlet and NH, NPSH, NPT threads and/or Storz 4" and larger with locking discharge connections. Female swivel connections have rocker lugs or LHs. Bleeder valve shall be .250" brass. The valve shall have a maximum of 250 PSI working pressure.

APPROXIMATE DIMENSIONS: 10.5"L x 6"W x 14"H

H800-40-40FF/Cap	4" Straight LDH Gate Valve 4" Flat-Face Flange x 4" Storz/Lok Cap/Cbl	\$2,311.00
H800-40-40RF/Cap	4" Straight LDH Gate Valve 4" Raised-Face Flange x 4" Storz/Lok Cap/Cbl	\$2,311.00
H800-50-40FF/Cap	4" Straight LDH Gate Valve 4" Flat-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,490.00
H800-50-40RF/Cap	4" Straight LDH Gate Valve 4" Raised-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,490.00
H800-50-60FF/Cap	4" Straight LDH Gate Valve 6" Flat-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,715.00
H800-50-60RF/Cap	4" Straight LDH Gate Valve 6" Raised-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,715.00

H811F - 4" LDH Gate Valve - 25° Elbow - FLANGED

H811-40-40FF/Cap	4" LDH Gate Valve 25° Elbow 4" Flat-Face Flange x 4" Storz/Lok Cap/Cbl	\$2,345.00
H811-40-40RF/Cap	4" LDH Gate Valve 25° Elbow 4" Raised-Face Flange x 4" Storz/Lok Cap/Cbl	\$2,345.00
H811-50-40FF/Cap	4" LDH Gate Valve 25° Elbow 4" Flat-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,605.00
H811-50-40RF/Cap	4" LDH Gate Valve 25° Elbow 4" Raised-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,605.00
H811-50-60FF/Cap	4" LDH Gate Valve 25° Elbow 6" Flat-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,855.00
H811-50-60RF/Cap	4" LDH Gate Valve 25° Elbow 6" Raised-Face Flange x 5" Storz/Lok Cap/Cbl	\$2,855.00



SPECIAL THREADS: available on request. 1" to 6" = \$20.00



H860 - Super-Flow Straight 6" Gate Valve

The Harrington Model H860 LDH fire hydrant straight gate valve shall have a 6" high-flow waterway, handwheel gate control with non-rising stem, stainless-steel spindle, and anodized gate. Valve meets NFPA standards for slow-close & opening operation, with a low friction loss of 0.1PSI at 1000 GPM. The lightweight anodized aluminum valve body shall be powder-coated gray in color. The valve features 4.5" to 6" NH or NPSH threads and/or Storz 4" and larger with locking connections. Female swivel connections have rocker lugs or LHs. Bleeder valve shall be .750" quarter-turn stainless-steel. Valve shall have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 10"L x 8.5"W x 16"H

H860-45NHM-45NH	6" Super-Flow Straight Gate Valve 4.5" NH male x 4.5" NH FS R/L	\$4,606.00
H860-50-45NH	6" Super-Flow Straight Gate Valve 5" Storz/Lok x 4.5" NH FS R/L	\$4,875.00
H860-50-45NHLH	6" Super-Flow Straight Gate Valve 5" Storz/Lok x 4.5" NH FS LH	\$4,888.00
H860-50-50NH	6" Super-Flow Straight Gate Valve 5" Storz/Lok x 5" NH FS R/L	\$4,813.00
H860-50-60NH	6" Super-Flow Straight Gate Valve 5" Storz/Lok x 6" NH FS R/L	\$4,813.00
H860-50-60NH/Cap	6" Super-Flow Straight Gate Valve 5" Storz/Lok Cap/Cbl x 6" NH FS R/L	\$5,056.00
H860-50-60NHLH	6" Super-Flow Straight Gate Valve 5" Storz/Lok x 6" NH FS LH	\$4,813.00
H860-50-60NPSH	6" Super-Flow Straight Gate Valve 5" Storz/Lok x 6" NPSH FS R/L	\$4,813.00
H860-50-60NPSHLH	6" Super-Flow Straight Gate Valve 5" Storz/Lok x 6" NPSH FS LH	\$4,813.00
H860-60-60NH	6" Super-Flow Straight Gate Valve 6" Storz/Lok x 6" NH FS R/L	\$4,656.00
H860-60-60NH/Cap	6" Super-Flow Straight Gate Valve 6" Storz/Lok Cap/Cbl x 6" NH FS R/L	\$5,000.00
H860-60-60NPSH	6" Super-Flow Straight Gate Valve 6" Storz/Lok x 6" NPSH FS R/L	\$4,656.00
H860-60NHM-60NH	6" Super-Flow Straight Gate Valve 6" NH male x 6" NH FS R/L	\$4,663.00
H860-60NHM-60NPSH	6" Super-Flow Straight Gate Valve 6" NH male x 6" NPSH FS R/L	\$4,663.00

H860F - Super Flow Straight 6" Gate Valve - Flanged

The Harrington Model H860F LDH fire hydrant "flanged" straight gate valve shall have a 6" high-flow waterway, handwheel gate control with non-rising stem, stainless-steel spindle, and anodized gate. Valve meets NFPA standards for slow-close & opening operation, with a low friction loss of 0.1 PSI at 1000 GPM. The lightweight hard-coat anodized aluminum valve body shall be powder-coated gray in color. The inlet is "flanged" and outlets available in 4.5" to 6" NH or NPSH threads or Storz 4" and larger with locking connections. Female swivel connections have rocker lugs or LHs. Bleeder valve shall be .750" quarter-turn stainless-steel. Valve shall have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 10"L x 8.5"W x 16"H

H860-50-60FF/CAP	6" Super-Flow Straight Gate Valve 6" Flat-Face Flange x 5" Storz/Lok Cap	5,255.00
H860-50-60RF/CAP	6" Super-Flow Straight Gate Valve 6" Raised-Face Flange x 5" Storz/Lok Cap	5,255.00
H860-60-60FF/CAP	6" Super-Flow Straight Gate Valve 6" Flat-Face Flange x 6" Storz/Lok Cap	5,180.00
H860-60-60RF/CAP	6" Super-Flow Straight Gate Valve 6" Raised-Face Flange x 6" Storz/Lok Cap	5,180.00



HSBFV - Butterfly Valve - Storz

The Harrington Model HSBFV butterfly valve shall be designed for multiple applications in sizes from 4" to 6" NH female swivel with LHs and Storz locking connections or special flange connections. Butterfly valves have a full-flow waterway. The valve body shall be ductile iron and powder-coated blue in color. Each hard anodized Storz and NH lightweight aluminum adapters are bolted to the butterfly valve body with six (6) stainless-steel bolts. The valves shall have either a squeeze handle (for non pressurized applications as 'quick dumps', or pumper drafting control), or gear-type handwheel control with stainless-steel spindle, and brass butterfly (for pressurized applications). The handwheel control option is compliant to NFPA standards for slow-close & opening operation. The bleeder valve shall be stainless-steel. The valve have a maximum of 250 PSI working pressure.

MADE IN THE USA.



HSBFV-40-40NHLH	Butterfly Valve 4" Storz x 4" NH FS LH	\$4,123.00
HSBFV-40-40NPSHLH	Butterfly Valve 4" Storz x 4" NPSH FS LH	\$4,123.00
HSBFV-40-45NHLH	Butterfly Valve 4" Storz x 4.5" NH FS LH	\$4,108.00
HSBFV-40-50NHLH	Butterfly Valve 4" Storz x 5" NH FS LH	\$4,100.00
HSBFV-40-60NHLH	Butterfly Valve 4" Storz x 6" NH FS LH	\$4,162.00
HSBFV-50-40NHLH	Butterfly Valve 5" Storz x 4" NH FS LH	\$4,046.00
HSBFVH-50-45NHLH	Butterfly Valve 5" Storz x 4.5" NH FS LH Handwheel	\$4,991.00
HSBFV-50-50NHLH	Butterfly Valve 5" Storz x 5" NH FS LH	\$4,007.00
HSBFVH-50-50NHLH	Butterfly Valve 5" Storz x 5" NH FS LH Handwheel	\$4,976.00
HSBFV-50-60NHLH	Butterfly Valve 5" Storz x 6" NH FS LH	\$4,077.00
HSBFVH-50-60NHLH	Butterfly Valve 5" Storz x 6" NH FS LH Handwheel	\$5,045.00
HSBFV-60-40NHLH	Butterfly Valve 6" Storz x 4" NH FS LH	\$4,038.00
HSBFV-60-45NHLH	Butterfly Valve 6" Storz x 4.5" NH FS LH	\$4,015.00
HSBFV-60-50NHLH	Butterfly Valve 6" Storz x 5" NH FS LH	\$4,007.00
HSBFV-60-60NHLH	Butterfly Valve 6" Storz x 6" NH FS LH	\$4,069.00



HTBFV - Butterfly Valve - Threaded



The Harrington Model HTBFV butterfly valve shall be designed for multiple applications in sizes from 4" to 6" NH female swivel with LHs x NH male adapters or special flange connections. Butterfly valves have a full-flow waterway. The valve body shall be ductile iron and powder-coated blue in color. Hard anodized lightweight aluminum adapters are bolted to the butterfly valve body with six (6) stainless-steel bolts. Valves have either a squeeze handle (for non-pressurized applications as 'quick dumps', or pumper drafting control), or gear-type handwheel control, with stainless-steel spindle and brass butterfly (for pressurized applications). The handwheel control option is compliant to NFPA standards for slow close & opening operation. The bleeder valve shall be stainless-steel. The valve have a maximum of 250 PSI working pressure. **MADE IN THE USA.**

HTBFV-40NHM-40NHLH	Butterfly Valve 4" NH male x 4" NH FS LH	\$3,697.00
HTBFVH-40NHM-40NHLH	Butterfly Valve 4" NH male x 4" NH FS LH Handwheel	\$4,666.00
HTBFV-40NHM-40NPSHLH	Butterfly Valve 4" NH male x 4" NPSH FS LH	\$3,697.00
HTBFV-40NPSHM-40NPSHLH	Butterfly Valve 4" NPSH male x 4" NPSH FS LH	\$3,697.00
HTBFVH-40NPSHM-40NPSHLH	Butterfly Valve 4" NPSH male x 4" NPSH FS LH Handwheel	\$4,666.00
HTBFV-40NHM-45NHLH	Butterfly Valve 4" NH male x 4.5" NH FS LH	\$3,666.00
HTBFV-40NHM-50NHLH	Butterfly Valve 4" NH male x 5" NH FS LH	\$3,658.00
HTBFV-40NHM-60NHLH	Butterfly Valve 4" NH male x 6" NH FS LH	\$3,728.00
HTBFV-45NHM-40NHLH	Butterfly Valve 4.5" NH male x 4" NH FS LH	\$3,697.00
HTBFV-45NHM-45NHLH	Butterfly Valve 4.5" NH male x 4.5" NH FS LH	\$3,666.00
HTBFV-45NHM-50NHLH	Butterfly Valve 4.5" NH male x 5" NH FS LH	\$3,658.00
HTBFV-45NHM-60NHLH	Butterfly Valve 4.5" NH male x 6" NH FS LH	\$3,728.00
HTBFV-50NHM-40NHLH	Butterfly Valve 5" NH male x 4" NH FS LH	\$3,697.00
HTBFV-50NHM-45NHLH	Butterfly Valve 5" NH male x 4.5" NH FS LH	\$3,697.00
HTBFV-50NHM-50NHLH	Butterfly Valve 5" NH male x 5" NH FS LH	\$3,658.00
HTBFV-50NHM-50NPSHLH	Butterfly Valve 5" NH male x 5" NPSH FS LH	\$3,658.00
HTBFV-50NHM-60NHLH	Butterfly Valve 5" NH male x 6" NH FS LH	\$3,728.00
HTBFV-60NHM-60NHLH	Butterfly Valve 6" NH male x 6" NH FS LH	\$3,500.00
HTBFVH-60NHM-60-NHLH	Butterfly Valve 6" NH male x 6" NH FS LH Handwheel	\$4,728.00



HJ20 - 2-Way Jumbo Siamese - Double Clappered

The Harrington Model #HJ20 two-way “Jumbo” siamese valve shall be designed for supplying one (1) LDH line from two (2) LDH lines -- which are individually “clappered”. The lightweight anodized aluminum valve body shall be powder-coated gray in color. The valve shall have NH & NPSH threaded connections & 4”, 5”, and 6” Storz locking connections. A large rubber top mounted carrying handle shall be provided. The clappers are stainless steel assemblies, with “forged heads”, aluminum balls in swivel races. The valve shall have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 18”L x 14”W x 9”H

HJ20-40-40ST	2-Way Siamese Jumbo Clappered (2) 4” Storz/Lok inlet x 4” Storz/Lok outlet	\$3,356.00
HJ20-40ST-40ST/ HABV	2-Way Siamese Jumbo Non-Clappered 4” Storz/Lok inlet .750” Bleeder x (2) 4” Storz/Lok outlet	\$3,800.00
HJ20-50-40ST	2-Way Siamese Jumbo Clappered (2) 4” Storz/Lok inlet x 5” Storz/Lok outlet	\$3,288.00
HJ20-50-50ST	2-Way Siamese Jumbo Clappered (2) 5” Storz/Lok inlet x 5” Storz/Lok outlet	\$3,525.00
HJ20-50ST-50ST/ HABV	2-Way Siamese Jumbo Non-Clappered 5” Storz/Lok inlet .750” Bleeder x (2) 4” Storz/Lok outlet	\$3,825.00
HJ20-60-50ST	2-Way Siamese Jumbo Clappered (2) 5” Storz/Lok inlet x 6” Storz/Lok outlet	\$3,769.00

HJ22 - 2-Way Jumbo Siamese - Non-Clappered

The Harrington Model #HJ22 two-way “Jumbo” siamese valve shall be designed for supplying one (1) LDH line from the (2) LDH lines -- which are “non-clappered”. The lightweight anodized aluminum valve body shall be powder-coated gray in color. The valve shall have NH & NPSH threaded connections and 4”, 5” and 6” Storz locking connections. Valve shall have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 18”L X 14”W X 9”H

HJ22-40-40ST	2-Way Siamese Jumbo Non-Clappered 4” Storz/Lok inlet x (2) 4” Storz/Lok outlet	\$3,680.00
HJ22-40NHFS- 40NHFS	2-Way Siamese Jumbo Non-Clappered 4” FS R/L inlet x (2) 4” FS R/L outlet	\$3,465.00
HJ22-50-50ST	2-Way Siamese Jumbo Non-Clappered 5” Storz/Lok inlet x (2) 5” Storz/Lok outlet	\$3,955.00
HJ22-60-50ST	2-Way Siamese Jumbo Non-Clappered 6” Storz inlet x (2) 5” Storz outlet	\$3,805.00
HJ22-60-60ST	2-Way Siamese Jumbo Non-Clappered 6” Storz inlet x (2) 6” Storz outlet	\$3,505.00
HJ22-60NHFS-50ST	2-Way Siamese Jumbo Non-Clappered 6” NH FS R/L inlet x (2) 5” Storz/Lok outlet	\$3,805.00
HJ22-60NHFS- 60NHM	2-Way Siamese Jumbo Non-Clappered 6” NH FS R/L inlet x (2) 6” NH male outlet	\$3,285.00
HJ22-60NHLH- 60NHM	2-Way Siamese Jumbo Non-Clappered 6” NH FS LH inlet x (2) 6” NH male outlet	\$3,285.00
HJ22-60NPSHFS- 60NHM	2-Way Siamese Jumbo Non-Clappered 6” NPSH FS R/L inlet x (2) 6” NH male outlet	\$3,285.00
HJ22-60RF-50ST	2-Way Siamese Jumbo Non-Clappered 6” 150# raised-face flange x (2) 5” Storz/Lok	\$3,490.00
HJ22-60FF-50ST	2-Way Siamese Jumbo Non-Clappered 6” 150# flat-face flange x (2) 5” Storz/Lok	\$3,490.00
HJ22-60RF-60ST	2-Way Siamese Jumbo Non-Clappered 6” 150# raised-face flange x (2) 6” Storz/Lok	\$4,220.00
HJ22-60FF-60ST	2-Way Siamese Jumbo Non-Clappered 6” 150# flat-face flange x (2) 6” Storz/Lok	\$4,220.00



H220 - 2-Way Siamese - Single Clappered



The Harrington Model H220 two-way 'single clappered' siamese valve shall be designed for supplying one (1) LDH line from two (2) lines. The one clapper design shall close-off the non-pressurized inlet while permitting flow from the pressurized inlet. The lightweight anodized aluminum body shall be powder-coated red in color. The valve has NH, NPSH, and Storz connections available in various sizes, with rocker lugs on female swivel connections. Locking provisions on 4" and larger Storz connections. The clappers are stainless-steel assemblies, with "forged heads". The valves have a maximum of 250 PSI working pressure.

APPROXIMATE DIMENSIONS: 10.5"L x 9.5"W x 8"H

H220-25NHM-25NHFS	2-Way Siamese Single Clappered	2.5" NH male outlet x (2) 2.5" NH FS inlets	\$856.00
H220-40-25NH	2-Way Siamese Single Clappered	4" Storz/Lok outlet x (2) 2.5" NH FS inlets	\$1,100.00
H220-40-25NHM	2-Way Siamese Single Clappered	4" Storz/Lok outlet x (2) 2.5" NH male inlets	\$925.00
H220-40SW-25NH	2-Way Siamese Single Clappered	4" Storz/Lok (PTS) outlet x (2) 2.5" NH FS inlets	\$1,275.00
H220-40-25ST	2-Way Siamese Single Clappered	4" Storz/Lok outlet x (2) 2.5" Storz inlets	\$900.00
H220-40NHFS-25NHFS	2-Way Siamese Single Clappered	4" NH FS outlet x (2) 2.5" NH FS inlets	\$1,056.00
H220-40NPSHFS-25NHFS	2-Way Siamese Single Clappered	4" NPSH FS outlet x (2) 2.5" NH FS inlets	\$1,056.00
H220-40NHFS-25NHM	2-Way Siamese Single Clappered	4" NH FS outlet x (2) 2.5" NH male inlets	\$881.00
H220-40-30ST	2-Way Siamese Single Clappered	4" Storz/Lok outlet x (2) 3" Storz inlets	\$888.00
H220-45NHFS-25NHFS	2-Way Siamese Single Clappered	4.5" NH FS outlet x (2) 2.5" NH FS inlets	\$1,038.00
H220-50-25NH	2-Way Siamese Single Clappered	5" Storz/Lok outlet x (2) 2.5" NH FS inlets	\$1,219.00
H220-50-25NHM	2-Way Siamese Single Clappered	5" Storz/Lok outlet x (2) 2.5" NH male inlets	\$1,044.00
H220-50-25ST	2-Way Siamese Single Clappered	5" Storz/Lok outlet x (2) 2.5" Storz inlets	\$1,019.00
H220-50-30ST	2-Way Siamese Single Clappered	5" Storz/Lok outlet x (2) 3" Storz inlets	\$1,006.00
H220-50NHFS-25NHFS	2-Way Siamese Single Clappered	5" NH FS outlet x (2) 2.5" NH FS inlets	\$1,100.00
H220-60-25ST	2-Way Siamese Single Clappered	6" Storz/Lok outlet x (2) 2.5" Storz inlets	\$1,131.00
H220-60NHFS-25NHFS	2-Way Siamese Single Clappered	6" NH FS outlet x (2) 2.5" NH FS inlets	\$1,194.00
H220-60-30ST	2-Way Siamese Single Clappered	6" Storz/Lok outlet x (2) 3" Storz inlets	\$1,119.00

H220 - 2-Way Siamese - Non-Clappered

The Harrington Model H220LC two-way non-clappered siamese valve shall be designed for supplying one (1) LDH line from two (2) lines. The lightweight anodized aluminum body shall be powder-coated red in color. The valve has NH, NPSH, and Storz connections available in various sizes, with rocker lugs on female swivel connections. Locking provisions on 4" and larger Storz connections. The valve shall have a maximum of 250 PSI working pressure.

DIMENSIONS: 10.5"L x 9.5"W x 8"

H220-40SW-25NH/LC	2-Way Siamese Non-Clappered	4" Storz/Lok (PTS) x (2) 2.5" NH FS	\$1,275.00
H220-40NHFS-25NHM/LC	2-Way Siamese Non-Clappered	4" NH FS R/L x (2) 2.5" NH male	\$881.00
H220-45NHFS-25NHM/LC	2-Way Siamese Non-Clappered	4.5" NH FS R/L x (2) 2.5" NH male	\$863.00
H220-50-25NHGV/LC	2-Way Siamese Non-Clappered	5" Storz/Lok x (2) HHGV 2.5" NH male	\$2,519.00
H220-50-25NHM/LC	2-Way Siamese Non-Clappered	5" Storz/Lok x (2) 2.5" NH male	\$1,044.00
H220-50SW-25NH/LC	2-Way Siamese Non-Clappered	5" Storz/Lok (PTS) x (2) 2.5" NH FS	\$1,213.00



H330 - 3-Way Siamese - Clappered

The Harrington Model H330 three-way 'clappered' siamese valve shall be designed for supplying one (1) LDH line from three (3) lines; each inlet shall be clappered individually. The lightweight anodized aluminum body shall be powder-coated gray in color. The valve has NH and Storz connections available in various sizes, with rocker lugs on female swivel connections. The unit includes a carrying handle. Locking provisions on 4" and larger Storz connections. The clappers are stainless-steel assemblies, with "forged heads". The valve shall have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 15.5"L x 14"W x 9"H

H330-40-25NH	3-Way Siamese Clappered 4" Storz/Lok outlet x (3) 2.5" NH FS inlets	\$2,081.00
H330-40-25ST	3-Way Siamese Clappered 4" Storz/Lok outlet x (3) 2.5" Storz inlets	\$1,838.00
H330-40-30ST	3-Way Siamese Clappered 4" Storz/Lok outlet x (3) 3" Storz inlets	\$1,819.00
H330-50-25NH	3-Way Siamese Clappered 5" Storz/Lok outlet x (3) 2.5" NH FS inlets	\$2,013.00
H330-50-25ST	3-Way Siamese Clappered 5" Storz/Lok outlet x (3) 2.5" Storz inlets	\$1,706.00
H330-50-30ST	3-Way Siamese Clappered 5" Storz/Lok outlet x (3) 3" Storz inlets	\$1,688.00
H330-60-25NH	3-Way Siamese Clappered 6" Storz/Lok outlet x (3) 2.5" NH FS inlets	\$2,256.00
H330-60NHFS-25NHFS	3-Way Siamese Clappered 6" NH FS outlet x (3) 2.5" NH FS inlets	\$2,169.00
H330-60-25ST	3-Way Siamese Clappered 6" Storz/Lok outlet x (3) 2.5" Storz inlets	\$1,956.00
H330-60-30ST	3-Way Siamese Clappered 6" Storz/Lok outlet x (3) 3" Storz inlets	\$1,938.00

H440 - 4-Way Siamese - Clappered

The Harrington Model H440 four-way 'clappered' siamese valve shall be designed for supplying one (1) LDH line from four (4) smaller lines; each inlet is clappered individually. The lightweight anodized aluminum body shall be powder coated red in color. The clappers are stainless-steel assemblies, with "forged heads". The unit includes a carrying handle. The valve shall have NH and Storz connections available in various sizes, with rocker lugs on female swivel connections. Locking provisions on 4" and larger Storz connections. The valve shall have a maximum of 250 PSI working pressure.



APPROXIMATE DIMENSIONS: 15"L x 19"W x 9"H

H440-40-25NH	4-Way Siamese Clappered 4" Storz/Lok outlet x (4) 2.5" NH FS inlets	\$2,500.00
H440-40-25ST	4-Way Siamese Clappered 4" Storz/Lok outlet x (4) 2.5" Storz inlets	\$2,100.00
H440-40-30ST	4-Way Siamese Clappered 4" Storz/Lok outlet x (4) 3" Storz inlets	\$2,075.00
H440-50-25NH	4-Way Siamese Clappered 5" Storz/Lok outlet x (4) 2.5" NH FS inlets	\$2,431.00
H440-50-25ST	4-Way Siamese Clappered 5" Storz/Lok outlet x (4) 2.5" Storz inlets	\$2,025.00
H440-50-30ST	4-Way Siamese Clappered 5" Storz/Lok outlet x (4) 3" Storz inlets	\$2,000.00
H440-60-25NH	4-Way Siamese Clappered 6" Storz/Lok outlet x (4) 2.5" NH FS inlets	\$2,675.00
H440-60-25ST	4-Way Siamese Clappered 6" Storz/Lok outlet x (4) 2.5" Storz inlets	\$2,275.00
H440-60-30ST	4-Way Siamese Clappered 6" Storz/Lok outlet x (4) 3" Storz inlets	\$2,250.00
H440-60NHFS-25NHFS	4-Way Siamese Clappered 6" NH FS outlet x (4) 2.5" NH FS inlets	\$2,675.00



H30E - 30° Elbow Adapter - Female Swivel x Male



The Harrington Model H30E adapter shall incorporate a 30° elbow. The lightweight aluminum adapter shall have female swivel x male threaded connections and shall be hard-coated anodized body and shall be powder-coated gray in color. The adapter shall have NH, NPSH, and special thread connections in various sizes. Female swivel connections have rocker lugs or LH. The adapter shall have a maximum 250 PSI working pressure.

H30E-15NHM-15NH	Adapter 30° Elbow 1.5" NH male x 1.5" NH FS	\$338.00
H30E-25NHM-25NH	Adapter 30° Elbow 2.5" NH male x 2.5" NH FS	\$194.00
H30E-25NHFS-25NHFS	Adapter 30° Elbow 2.5" NH FS x 2.5" NH FS	\$338.00
H30E-25NHM-30NH	Adapter 30° Elbow 2.5" NH male x 3" NH FS	\$438.00
H30E-25NHM-30NPSH	Adapter 30° Elbow 2.5" NH male x 3" NPSH FS	\$438.00
H30E-30NHM-25NH	Adapter 30° Elbow 3" NH male x 2.5" NH FS	\$306.00
H30E-30NHM-30NH	Adapter 30° Elbow 3" NH male x 3" NH FS	\$456.00
H30E-30NHFS-30NHFS	Adapter 30° Elbow 3" NH FS x 3" NH FS	\$613.00
H30E-35NHM-35NH	Adapter 30° Elbow 3.5" NH male x 3.5" NH FS	\$550.00

H30E - 30° Elbow Adapter -- Storz x Threaded



The Harrington Model H30E Storz adapter shall incorporate a 30° elbow. The lightweight aluminum adapter shall have Storz x female swivel x rigid connections & male connections. The adapter shall be hard-coated anodized body and shall be powder-coated gray in color. The adapter shall have NH, NPSH, NPT, and special thread connections in various sizes. Female swivel connections have rocker lugs or LH. Storz connections over 4" shall be locking type. The adapter shall have a maximum 250 PSI working pressure.

H30E-25-25NH	Adapter 30° Elbow 2.5" Storz x 2.5" NH FS R/L	\$244.00
H30E-25-25NPSH	Adapter 30° Elbow 2.5" Storz x 2.5" NPSH FS R/L	\$244.00
H30E-25-25NHM	Adapter 30° Elbow 2.5" Storz x 2.5" NH male	\$244.00
H30E-25-30NH	Adapter 30° Elbow 2.5" Storz x 3" NH FS R/L	\$363.00
H30E-25-30NPSH	Adapter 30° Elbow 2.5" Storz x 3" NPSH FS R/L	\$363.00
H30E-30-25NH	Adapter 30° Elbow 3" Storz x 2.5" NH FS R/L	\$231.00
H30E-30-25NPSH	Adapter 30° Elbow 3" Storz x 2.5" NPSH FS R/L	\$231.00
H30E-30-30NH	Adapter 30° Elbow 3" Storz x 3" NH FS R/L	\$400.00
H30E-30-30NPSH	Adapter 30° Elbow 3" Storz x 3" NPSH FS R/L	\$400.00
H30E-40-25NH	Adapter 30° Elbow 4" Storz/Lok x 2.5" NH FS R/L	\$638.00
H30E-40-25NHM	Adapter 30° Elbow 4" Storz/Lok x 2.5" NH male	\$575.00
H30E-40-25NPSH	Adapter 30° Elbow 4" Storz/Lok x 2.5" NPSH FS R/L	\$638.00
H30E-40-30NH	Adapter 30° Elbow 4" Storz/Lok x 3" NH FS R/L	\$706.00
H30E-40-30NPT	Adapter 30° Elbow 4" Storz/Lok x 3" NPT female rigid	\$569.00
H30E-40-30NHM	Adapter 30° Elbow 4" Storz/Lok x 3" NH male	\$563.00
H30E-40-35NH	Adapter 30° Elbow 4" Storz/Lok x 3.5" NH FS R/L	\$681.00



H30E-40-40NH	Adapter 30° Elbow 4" Storz/Lok x 4" NH FS R/L	\$625.00
H30E-40-40NH/Cap	Adapter 30° Elbow 4" Storz/Lok Cap/Cbl x 4" NH FS R/L	\$813.00
H30E-40-40NPSH	Adapter 30° Elbow 4" Storz/Lok x 4" NPSH FS R/L	\$625.00
H30E-40-40NPSH/Cap	Adapter 30° Elbow 4" Storz/Lok Cap/Cbl x 4" NPSH FS R/L	\$813.00
H30E-40-40NPT	Adapter 30° Elbow 4" Storz/Lok x 4" NPT female rigid	\$444.00
H30E-40-40NPT/Cap	Adapter 30° Elbow 4" Storz/Lok Cap/Cbl x 4" NPT female rigid	\$665.00
H30E-40-40NPTM	Adapter 30° Elbow 4" Storz/Lok x 4" NPT male	\$594.00
H30E-40-40NPTM/Cap	Adapter 30° Elbow 4" Storz/Lok Cap/Cbl x 4" NPT male	\$781.00
H30E-40-45NH	Adapter 30° Elbow 4" Storz/Lok x 4.5" NH FS R/L	\$638.00
H30E-40-50NH	Adapter 30° Elbow 4" Storz/Lok x 5" NH FS R/L	\$838.00
H30E-40-60NH	Adapter 30° Elbow 4" Storz/Lok x 6" NH FS R/L	\$881.00
H30E-40-60NPSH	Adapter 30° Elbow 4" Storz/Lok x 6" NPSH FS R/L	\$881.00
H30E-40-60NPTF	Adapter 30° Elbow 4" Storz/Lok x 6" NPT female rigid	\$713.00
H30E-40-60NPT/Cap	Adapter 30° Elbow 4" Storz/Lok Cap/Cbl x 6" NPT female rigid	\$900.00
H30E-40-60NPTM	Adapter 30° Elbow 4" Storz/Lok x 6" NPT male	\$694.00
H30E-40-60NPTM/Cap	Adapter 30° Elbow 4" Storz/Lok Cap/Cbl x 6" NPT male	\$881.00
H30E-45-60NH (Storz 110)	Adapter 30° Elbow 4.5" Storz/Lok x 6" NH FS R/L	\$856.00
H30E-50-25NH	Adapter 30° Elbow 5" Storz/Lok x 2.5" NH FS R/L	\$656.00
H30E-50-25NH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 2.5" NH FS R/L	\$1,106.00
H30E-50-25NHM	Adapter 30° Elbow 5" Storz/Lok x 2.5" NH male	\$738.00
H30E-50-30NH	Adapter 30° Elbow 5" Storz/Lok x 3" NH FS R/L	\$706.00
H30E-50-30NHM	Adapter 30° Elbow 5" Storz/Lok x 3" NH male	\$731.00
H30E-50-30NH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 3" NH FS R/L	\$1,181.00
H30E-50-35NH	Adapter 30° Elbow 5" Storz/Lok x 3.5" NH FS R/L	\$819.00
H30E-50-35NH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 3.5" NH FS R/L	\$1,269.00
H30E-50-40NH	Adapter 30° Elbow 5" Storz/Lok x 4" NH FS R/L	\$731.00
H30E-50-40NH/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 4" NH FS R/L	\$997.00
H30E-50-40NH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 4" NH FS R/L	\$1,181.00
H30E-50-40NPSH	Adapter 30° Elbow 5" Storz/Lok x 4" NPSH FS R/L	\$731.00
H30E-50-40NPSH/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 4" NPSH FS R/L	\$997.00
H30E-50-40NPSH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 4" NPSH FS R/L	\$1,181.00
H30E-50-40NPT	Adapter 30° Elbow 5" Storz/Lok x 4" NPT female rigid	\$556.00
H30E-50-40NPT/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 4" NPT female rigid	\$850.00
H30E-50-40NPTM	Adapter 30° Elbow 5" Storz/Lok x 4" NPT male	\$600.00
H30E-50-40NPTM/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 4" NPT male	\$899.00
H30E-50-45NH	Adapter 30° Elbow 5" Storz/Lok x 4.5" NH FS R/L	\$756.00
H30E-50-45NH/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 4.5" NH FS R/L	\$1,031.00
H30E-50-45NH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 4.5" NH FS R/L	\$1,206.00
H30E-50-50NH	Adapter 30° Elbow 5" Storz/Lok x 5" NH FS R/L	\$775.00
H30E-50-50NH/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 5" NH FS R/L	\$1,040.00
H30E-50NHM-50NH	Adapter 30° Elbow 5" NH male x 5" NH FS R/L	\$669.00
H30E-50-50NH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 5" NH FS R/L	\$1,225.00
H30E-50-50NPSH	Adapter 30° Elbow 5" Storz/Lok x 5" NPSH FS R/L	\$775.00
H30E-50-50NPSH/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 5" NPSH FS R/L	\$1,040.00
H30E-50-50NPT	Adapter 30° Elbow 5" Storz/Lok x 5" NPT female rigid	\$1,013.00
H30E-50-50NPT/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 5" NPT female rigid	\$1,256.00



H30E-50-60NH	Adapter 30° Elbow 5" Storz/Lok x 6" NH FS R/L	\$806.00
H30E-50-60NH/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 6" NH FS R/L	\$1,061.00
H30E-50-60NH/FTS	Adapter 30° Elbow 5" Storz/Lok (FTS) x 6" NH FS R/L	\$1,256.00
H30E-50-60NPSH	Adapter 30° Elbow 5" Storz/Lok x 6" NPSH FS R/L	\$806.00
H30E-50-60NPSH/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 6" NPSH FS R/L	\$1,061.00
H30E-50-60NPT	Adapter 30° Elbow 5" Storz/Lok x 6" NPT female rigid	\$650.00
H30E-50-60NPT/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 6" NPT female rigid	\$950.00
H30E-50-60NPTM	Adapter 30° Elbow 5" Storz/Lok x 6" NPT male	\$625.00
H30E-50-60NPTM/Cap	Adapter 30° Elbow 5" Storz/Lok Cap/Cbl x 6" NPT male	\$932.00
H30E-60-40NH	Adapter 30° Elbow 6" Storz/Lok x 4" NH FS R/L	\$981.00
H30E-60-40NPSH	Adapter 30° Elbow 6" Storz/Lok x 4" NPSH FS R/L	\$981.00
H30E-60-40NPSH/Cap	Adapter 30° Elbow 6" Storz/Lok Cap/Cbl x 4" NPSH FS R/L	\$1,325.00
H30E-60-40NPT	Adapter 30° Elbow 6" Storz/Lok x 4" NPT female rigid	\$825.00
H30E-60-40NPT/Cap	Adapter 30° Elbow 6" Storz/Lok Cap/Cbl x 4" NPT female rigid	\$1,169.00
H30E-60-40NPTM	Adapter 30° Elbow 6" Storz/Lok x 4" NPT male	\$825.00
H30E-60-40NPTM/Cap	Adapter 30° Elbow 6" Storz/Lok Cap/Cbl x 4" NPT male	\$1,169.00
H30E-60-45NH	Adapter 30° Elbow 6" Storz/Lok x 4.5" NH FS R/L	\$1,000.00
H30E-60-50NH	Adapter 30° Elbow 6" Storz/Lok x 5" NH FS R/L	\$1,025.00
H30E-60-60NH	Adapter 30° Elbow 6" Storz/Lok x 6" NH FS R/L	\$1,038.00
H30E-60-60NPSH	Adapter 30° Elbow 6" Storz/Lok x 6" NPSH FS R/L	\$1,038.00
H30E-60-60NPSH/Cap	Adapter 30° Elbow 6" Storz/Lok Cap/Cbl x 6" NPSH FS R/L	\$1,381.00
H30E-60-60NPTF	Adapter 30° Elbow 6" Storz/Lok x 6" NPT female rigid	\$819.00
H30E-60-60NPTF/Cap	Adapter 30° Elbow 6" Storz/Lok Cap/Cbl x 6" NPT female rigid	\$1,163.00
H30E-60-60NPTM	Adapter 30° Elbow 6" Storz/Lok x 6" NPT male	\$819.00
H30E-60-60NPTM/Cap	Adapter 30° Elbow 6" Storz/Lok Cap/Cbl x 6" NPT male	\$1,163.00
H30E-60NHM-60NH	Adapter 30° Elbow 6" NH male x 6" NH FS R/L	\$900.00



H30E - Adapter - Storz x Storz (Part-Time-Swivel)



H30E-40-40ST	30° Elbow 4" Storz/Lok x 4" Storz/Lok (PTS)	\$1,000.00
H30E-50-50ST	30° Elbow 5" Storz/Lok x 5" Storz/Lok (PTS)	\$1,088.00



H30E - 30° Elbow Adapter - Storz x Female Swivel LH

The Harrington Model H30E Storz adapter shall incorporate a 30° elbow. The lightweight aluminum adapter shall have Storz x female swivel x rigid connections & male connections with long handle. The adapter shall be hard-coated anodized body and shall be powder-coated gray in color. The adapter shall have NH, NPSH, NPT, and special thread connections in various sizes. Female swivel connections have rocker lugs or LH. Storz connections over 4" shall be locking type. The adapter shall have a maximum 250 PSI working pressure.



H30E-25-25NHLH	Adapter 30° Elbow Adapter 2.5" Storz x 2.5" NH FS LH	\$269.00
H30E-25-30NHLH	Adapter 30° Elbow Adapter 2.5" Storz x 3" NH FS LH	\$494.00
H30E-30-25NHLH	Adapter 30° Elbow Adapter 3" Storz x 2.5" NH FS LH	\$263.00
H30E-30-30NHLH	Adapter 30° Elbow Adapter 3" Storz x 3" NH FS LH	\$450.00
H30E-40-25NHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 2.5" NH FS LH	\$669.00
H30E-40-25NPSHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 2.5" NPSH FS LH	\$669.00
H30E-40-30NHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 3" NH FS LH	\$738.00
H30E-40-35NHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 3.5" NH FS LH	\$681.00
H30E-40-40NHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 4" NH FS LH	\$644.00
H30E-40-45NHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 4.5" NH FS LH	\$650.00
H30E-40-50NHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 5" NH FS LH	\$838.00
H30E-40-60NHLH	Adapter 30° Elbow Adapter 4" Storz/Lok x 6" NH FS LH	\$888.00
H30E-50-25NHLH	Adapter 30° Elbow Adapter 5" Storz/Lok x 2.5" NH FS LH	\$694.00
H30E-50-25NHLH/FTS	Adapter 30° Elbow Adapter 5" Storz/Lok (FTS) x 2.5" NH FS LH	\$1,144.00
H30E-50-30NHLH	Adapter 30° Elbow Adapter 5" Storz/Lok x 3" NH FS LH	\$744.00
H30E-50-30NHLH/FTS	Adapter 30° Elbow Adapter 5" Storz/Lok (FTS) x 3" NH FS LH	\$1,194.00
H30E-50-35NHLH	Adapter 30° Elbow Adapter 5" Storz/Lok x 3.5" NH FS LH	\$844.00
H30E-50-35NHLH/FTS	Adapter 30° Elbow Adapter 5" Storz/Lok (FTS) x 3.5" NH FS LH	\$1,294.00
H30E-50-40NHLH	Adapter 30° Elbow Adapter 5" Storz/Lok x 4" NH FS LH	\$744.00
H30E-50-40NHLH/FTS	Adapter 30° Elbow Adapter 5" Storz/Lok (FTS) x 4" NH FS LH	\$1,194.00
H30E-50-45NHLH	Adapter 30° Elbow Adapter 5" Storz/Lok x 4.5" NH FS LH	\$769.00
H30E-50-45NHLH/FTS	Adapter 30° Elbow Adapter 5" Storz/Lok (FTS) x 4.5" NH FS LH	\$1,219.00
H30E-50-50NHLH	Adapter 30° Elbow Adapter 5" Storz/Lok x 5" NH FS LH	\$775.00
H30E-50-50NHLH/FTS	Adapter 30° Elbow Adapter 5" Storz/Lok (FTS) x 5" NH FS LH	\$1,225.00
H30E-50-60NHLH	Adapter 30° Elbow Adapter 5" Storz/Lok x 6" NH FS LH	\$819.00
H30E-50-60NHLH/FTS	Adapter 30° Elbow Adapter 5" Storz/Lok (FTS) x 6" NH FS LH	\$1,269.00
H30E-60-40NHLH	Adapter 30° Elbow Adapter 6" Storz/Lok x 4" NH FS LH	\$1,006.00
H30E-60-45NHLH	Adapter 30° Elbow Adapter 6" Storz/Lok x 4.5" NH FS LH	\$1,013.00
H30E-60-50NHLH	Adapter 30° Elbow Adapter 6" Storz/Lok x 5" NH FS LH	\$1,006.00
H30E-60-60NHLH	Adapter 30° Elbow Adapter 6" Storz/Lok x 6" NH FS LH	\$1,044.00
H30E-60NHM-60NHLH	Adapter 30° Elbow Adapter 6" NH male x 6" NH FS LH	\$900.00

SPECIAL THREADS: available on request. 1" to 6" = \$20.00



HPHA - Storz Hydrant Adapter - Integral Metal Face & Cap



The Harrington Model HPHA Storz metal-face hydrant adapter and cap are 'forged' for maximum strength and rated to a working pressure of 250 PSI. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. The adapter shall have a female rigid threaded connection with two (2) stainless steel set screws to prevent removal from the fire hydrant. The removable Storz blind cap shall be connected to the adapter with a reflective stainless-steel cable.

The hydrant adapter shall have threaded and Storz connections for 2.5" to 6" sizes. The assembly shall be "field installable" to provide for Storz hydrant connections from previous threaded hose connection. 250 PSI working pressure.

Made in the USA

HPHA40-40NH/Cap	Made in USA Hydrant Adapter Storz Metal-Face Cap/Cbl Dark Anodized	4" Storz x 4" NH Female with Storz	\$480.00
HPHA40-40xxx/Cap	Made in USA Hydrant Adapter Storz Metal-Face with Storz Cap/Cbl Dark Anodized	4" Storz x 4" special thread Female	\$518.00
HPHA40-45NH/Cap	Made in USA Hydrant Adapter Storz Metal-Face Storz Cap/Cbl Dark Anodized	4" Storz x 4.5" NH Female with	\$475.00
HPHA40-45xxx/Cap	Made in USA Hydrant Adapter Storz Metal-Face with Storz Cap/Cbl Dark Anodized	4" Storz x 4.5" special thread Female	\$580.00
HPHA40-50NH/Cap	Made in USA Hydrant Adapter Storz Metal-Face Cap/Cbl Dark Anodized	4" Storz x 5" NH Female with Storz	\$720.00
HPHA40-50-xxx/Cap	Made in USA Hydrant Adapter Storz Metal-Face with Storz Cap/Cbl Dark Anodized	4" Storz x 5" Special thread Female	\$760.00
HPHA50-40NH/Cap	Made in USA Hydrant Adapter Storz Metal-Face Cap/Cbl Dark Anodized	5" Storz x 4" NH Female with Storz	\$610.00
HPHA50-40xxx/Cap	Made in USA Hydrant Adapter Storz Metal-Face with Storz Cap/Cbl Dark Anodized	5" Storz x 4" special thread Female	\$650.00
HPHA50-45NH/Cap	Made in USA Hydrant Adapter Storz Metal-Face Storz Cap/Cbl Dark Anodized	5" Storz x 4.5" NH Female with	\$600.00
HPHA50-45xxx/Cap	Made in USA Hydrant Adapter Storz Metal-Face with Storz Cap/Cbl Dark Anodized	5" Storz x 4.5" special thread Female	\$650.00
HPHA50-50NH/Cap	Made in USA Hydrant Adapter Storz Metal-Face Cap/Cbl Dark Anodized	5" Storz x 5" NH Female with Storz	\$725.00
HPHA50-50xxx/Cap	Made in USA Hydrant Adapter Storz Metal-Face with Storz Cap/Cbl Dark Anodized	5" Storz x 5" special thread Female	\$980.00



HIHS - Storz Integral Hydrant Metal-Face Storz & Cap

The Harrington Model HIHS Storz metal-face hydrant nozzle is installed directly into the hydrant body. The metal-face hydrant nozzle with cap shall be made of cast brass and 'forged' aluminum for maximum strength and rated to a working pressure of 250 PSI. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum.

The brass shall be custom-machined for specific manufacturers of fire hydrant (as listed in our Part Number & Descriptions below). The removable Storz blind cap shall be connected to the adapter with a reflective stainless-steel cable. The hydrant adapter shall have threaded and Storz connections for 4" to 5" sizes.



Made in the USA

HIHS-CLOW-40-45	Made in USA 4" Storz Integral Hydrant Nozzle: 4 x Clow nozzle with Storz cap & reflective stainless steel aircraft cable	\$880.00
HIHS-CLOW-50-45	Made in USA 5" Storz Integral Hydrant Nozzle: 5 x Clow nozzle with Storz cap & reflective stainless steel aircraft cable	\$990.00
HIHS-EJIW-40-375	Made in USA 4" Storz Integral Hydrant Nozzle: 4 x East Jordan 3.75" nozzle with Storz cap & reflective stainless steel aircraft cable	\$880.00
HIHS-EJIW-40-45	Made in USA 4" Storz Integral Hydrant Nozzle: 4 x East Jordan 4.5" nozzle with Storz cap & reflective stainless steel aircraft cable	\$880.00
HIHS-EJIW-50-375	Made in USA 5" Storz Integral Hydrant Nozzle: 5 x East Jordan 3.75" nozzle with Storz cap & reflective stainless steel aircraft cable	\$990.00
HIHS-EJIW-50-45	Made in USA 5" Storz Integral Hydrant Nozzle: 5 x East Jordan 4.5" nozzle with Storz cap & reflective stainless steel aircraft cable	\$990.00
HIHS-KEN-40-45	Made in USA 4" Storz Integral Hydrant Nozzle: 4 x Kennedy nozzle with Storz cap & reflective stainless steel aircraft cable	\$880.00
HIHS-KEN-50-45	Made in USA 5" Storz Integral Hydrant Nozzle: 5 x Kennedy nozzle with Storz cap & reflective stainless steel aircraft cable	\$990.00
HIHS-M&H-40-45	Made in USA 4" Storz Integral Hydrant Nozzle: 4 x M & H nozzle with Storz cap & reflective stainless steel aircraft cable	\$880.00
HIHS-M&H-50-45	Made in USA 5" Storz Integral Hydrant Nozzle: 5 x M & H nozzle with Storz cap & reflective stainless steel aircraft cable	\$990.00
HIHS-MLR-40-45	Made in USA 4" Storz Integral Hydrant Nozzle: 4 x Mueller nozzle with Storz cap & reflective stainless steel aircraft cable	\$880.00
HIHS-MLR-50-45	Made in USA 5" Storz Integral Hydrant Nozzle: 5 x Mueller nozzle with Storz cap & reflective stainless steel aircraft cable	\$990.00
HIHS-WAT-40-45	Made in USA 4" Storz Integral Hydrant Nozzle: 4 x Waterous nozzle with Storz cap & reflective stainless steel aircraft cable	\$880.00
HIHS-WAT-50-45	Made in USA 5" Storz Integral Hydrant Nozzle: 5 x Waterous nozzle with Storz cap & reflective stainless steel aircraft cable	\$990.00



See wrenches on page #70



HSFS - Storz Straight Adapter - Female Swivel Rocker Lug



The Harrington Model HSFS Storz straight adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. The adapter shall have female swivel NH & NPSH threaded connections in various sizes from 1.5” to 6” sizes, with rocker lugs. Stainless-steel roller bearings (3.5” and under) and aluminum roller bearings (in sizes 4” and larger) shall be provided. Storz connections from 1.5” to 6” compliant with applicable NFPA standards. Storz locking provisions provided for sizes over 4”.

HSFS15-15NH	Storz Straight Adapter	1.5” Storz x 1.5” NH FS R/L	\$125.00
HSFS15-25NH	Storz Straight Adapter	1.5” Storz x 2.5” NH FS R/L	\$140.00
HSFS20-15NH	Storz Straight Adapter	2” Storz x 1.5” NH FS R/L	\$115.00
HSFS25-15NH	Storz Straight Adapter	2.5” Storz x 1.5” NH FS R/L	\$165.00
HSFS25-15NPSH	Storz Straight Adapter	2.5” Storz x 1.5” NPSH FS R/L	\$165.00
HSFS25-25NH	Storz Straight Adapter	2.5” Storz x 2.5” NH FS R/L	\$190.00
HSFS25-25NPSH	Storz Straight Adapter	2.5” Storz x 2.5” NPSH FS R/L	\$190.00
HSFS25-30NH	Storz Straight Adapter	2.5” Storz x 3” NH FS R/L	\$235.00
HSFS25-30NPSH	Storz Straight Adapter	2.5” Storz x 3” NPSH FS R/L	\$235.00
HSFS30-25NH	Storz Straight Adapter	3” Storz x 2.5” NH FS R/L	\$160.00
HSFS30-25NPSH	Storz Straight Adapter	3” Storz x 2.5” NPSH FS R/L	\$160.00
HSFS30-30NH	Storz Straight Adapter	3” Storz x 3” NH FS R/L	\$205.00
HSFS30-30NPSH	Storz Straight Adapter	3” Storz x 3” NPSH FS R/L	\$205.00
HSFS40-25NH	Storz Straight Adapter	4” Storz/Lok x 2.5” NH FS R/L	\$352.00
HSFS40-30NH	Storz Straight Adapter	4” Storz/Lok x 3” NH FS R/L	\$395.00
HSFS40-30NPSH	Storz Straight Adapter	4” Storz/Lok x 3” NPSH FS R/L	\$395.00
HSFS40-35NH	Storz Straight Adapter	4” Storz/Lok x 3.5” NH FS R/L	\$385.00
HSFS40-35NPSH	Storz Straight Adapter	4” Storz/Lok x 3.5” NPSH FS R/L	\$385.00
HSFS40-40NH	Storz Straight Adapter	4” Storz/Lok x 4” NH FS R/L	\$469.00
HSFS40-40NPSH	Storz Straight Adapter	4” Storz/Lok x 4” NPSH FS R/L	\$469.00
HSFS40-45NH	Storz Straight Adapter	4” Storz/Lok x 4.5” NH FS R/L	\$456.00
HSFS40-45NPSH	Storz Straight Adapter	4” Storz/Lok x 4.5” NPSH FS R/L	\$456.00
HSFS40-50NH	Storz Straight Adapter	4” Storz/Lok x 5” NH FS R/L	\$495.00
HSFS40-50NPSH	Storz Straight Adapter	4” Storz/Lok x 5” NPSH FS R/L	\$495.00
HSFS40-60NH	Storz Straight Adapter	4” Storz/Lok x 6” NH FS R/L	\$575.00
HSFS40-60NPSH	Storz Straight Adapter	4” Storz/Lok x 6” NPSH FS R/L	\$575.00
HSFS50-25NH	Storz Straight Adapter	5” Storz/Lok x 2.5” NH FS R/L	\$471.00
HSFS50-25NH/FTS	Storz Straight Adapter	5” Storz/Lok (FTS) x 2.5” NH FS R/L	\$810.00
HSFS50-25NPSH	Storz Straight Adapter	5” Storz/Lok x 2.5” NPSH FS R/L	\$471.00
HSFS50-30NH	Storz Straight Adapter	5” Storz/Lok x 3” NH FS R/L	\$489.00
HSFS50-30NH/FTS	Storz Straight Adapter	5” Storz/Lok (FTS) x 3” NH FS R/L	\$830.00
HSFS50-30NPSH	Storz Straight Adapter	5” Storz/Lok x 3” NPSH FS R/L	\$489.00
HSFS50-35NH	Storz Straight Adapter	5” Storz/Lok x 3.5” NH FS R/L	\$489.00
HSFS50-35NH/FTS	Storz Straight Adapter	5” Storz/Lok (FTS) x 3.5” NH FS R/L	\$830.00
HSFS50-35NPSH	Storz Straight Adapter	5” Storz/Lok x 3.5” NPSH FS R/L	\$489.00



HSFS50-40NH	Storz Straight Adapter 5" Storz/Lok x 4" NH FS R/L	\$540.00
HSFS50-40NPSH	Storz Straight Adapter 5" Storz/Lok x 4" NPSH FS R/L	\$540.00
HSFS50-45NH	Storz Straight Adapter 5" Storz/Lok x 4.5" NH FS R/L	\$514.00
HSFS50-45NPSH	Storz Straight Adapter 5" Storz/Lok x 4.5" NPSH FS R/L	\$514.00
HSFS50-50NH	Storz Straight Adapter 5" Storz/Lok x 5" NH FS R/L	\$591.00
HSFS50-50NPSH	Storz Straight Adapter 5" Storz/Lok x 5" NPSH FS R/L	\$591.00
HSFS50-60NH	Storz Straight Adapter 5" Storz/Lok x 6" NH FS R/L	\$662.00
HSFS50-60NPSH	Storz Straight Adapter 5" Storz/Lok x 6" NPSH FS R/L	\$662.00
HSFS60-40NH	Storz Straight Adapter 6" Storz/Lok x 4" NH FS R/L	\$760.00
HSFS60-40NPSH	Storz Straight Adapter 6" Storz/Lok x 4" NPSH FS R/L	\$760.00
HSFS60-45NH	Storz Straight Adapter 6" Storz/Lok x 4.5" NH FS R/L	\$720.00
HSFS60-45NPSH	Storz Straight Adapter 6" Storz/Lok x 4.5" NPSH FS R/L	\$720.00
HSFS60-50NH	Storz Straight Adapter 6" Storz/Lok x 5" NH FS R/L	\$855.00
HSFS60-50NPSH	Storz Straight Adapter 6" Storz/Lok x 5" NPSH FS R/L	\$855.00
HSFS60-60NH	Storz Straight Adapter 6" Storz/Lok x 6" NH FS R/L	\$800.00
HSFS60-60NPSH	Storz Straight Adapter 6" Storz/Lok x 6" NPSH FS R/L	\$800.00

HSFS - Straight Storz Adapter - FS LH

The Harrington Model HSFS straight Storz adapter shall be "forged" for maximum strength and rated for a working pressure of 250 PSI. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum, in sizes 2.5" to 6". Stainless-steel roller bearings (on 3.5" and under) and aluminum roller bearings (in sizes 4" and larger) shall be provided. Storz connections from 2.5" to 6" compliant to NFPA standards. Storz locking provisions provided for sizes over 4".



HSFS25-25NHLH	Storz Straight Adapter 2.5" Storz x 2.5" NH FS LH	\$190.00
HSFS25-30NHLH	Storz Straight Adapter 2.5" Storz x 3" NH FS LH	\$260.00
HSFS30-25NHLH	Storz Straight Adapter 3" Storz x 2.5" NH FS LH	\$185.00
HSFS30-30NHLH	Storz Straight Adapter 3" Storz x 3" NH FS LH	\$260.00
HSFS40-25NHLH	Storz Straight Adapter 4" Storz/Lok x 2.5" NH FS LH	\$383.00
HSFS40-30NHLH	Storz Straight Adapter 4" Storz/Lok x 3" NH FS LH	\$459.00
HSFS40-35NHLH	Storz Straight Adapter 4" Storz/Lok x 3.5" NH FS LH	\$385.00
HSFS40-40NHLH	Storz Straight Adapter 4" Storz/Lok x 4" NH FS LH	\$470.00
HSFS40-45NHLH	Storz Straight Adapter 4" Storz/Lok x 4.5" NH FS LH	\$455.00
HSFS40-50NHLH	Storz Straight Adapter 4" Storz/Lok x 5" NH FS LH	\$495.00
HSFS40-60NHLH	Storz Straight Adapter 4" Storz/Lok x 6" NH FS LH	\$575.00
HSFS50-25NHLH	Storz Straight Adapter 5" Storz/Lok x 2.5" NH FS LH	\$502.00
HSFS50-30NHLH	Storz Straight Adapter 5" Storz/Lok x 3" NH FS LH	\$551.00
HSFS50-35NHLH	Storz Straight Adapter 5" Storz/Lok x 3.5" NH FS LH	\$503.00
HSFS50-40NHLH	Storz Straight Adapter 5" Storz/Lok x 4" NH FS LH	\$540.00
HSFS50-45NHLH	Storz Straight Adapter 5" Storz/Lok x 4.5" NH FS LH	\$514.00
HSFS50-50NHLH	Storz Straight Adapter 5" Storz/Lok x 5" NH FS LH	\$591.00



HSFS50-60NHLH	Storz Straight Adapter 5" Storz/Lok x 6" NH FS LH	\$662.00
HSFS60-40NHLH	Storz Straight Adapter 6" Storz/Lok x 4" NH FS LH	\$765.00
HSFS60-45NHLH	Storz Straight Adapter 6" Storz/Lok x 4.5" NH FS LH	\$730.00
HSFS60-50NHLH	Storz Straight Adapter 6" Storz/Lok x 5" NH FS LH	\$840.00
HSFS60-60NHLH	Storz Straight Adapter 6" Storz/Lok x 6" NH FS LH	\$805.00

HSFR - Storz x Female Rigid Adapter



The Harrington Model HSFR straight Storz adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The adapter shall be hard coat anodized of Type #6061-T6 aluminum. The adapter shall have female ‘rigid’ NH, NPT, & NPSH threaded connections in various from 1” to 6” sizes with rocker lugs. Storz connections from 1” to 6” and compliant to applicable NFPA standards. Storz locking provisions provided for sizes over 4”.

HSFR10-10NH	Storz x Female Adapter 1" Storz (25) x 1" NH female rigid	\$90.00
HSFR10-10NPSH	Storz x Female Adapter 1" Storz (25) x 1" NPSH female rigid	\$90.00
HSFR10-10NPT	Storz x Female Adapter 1" Storz (25) x 1" NPT female rigid	\$104.00
HSFR15-10NH	Storz x Female Adapter 1.5" Storz x 1" NH female rigid	\$100.00
HSFR15-10NPT	Storz x Female Adapter 1.5" Storz x 1" NPT female rigid	\$100.00
HSFR15-15NH	Storz x Female Adapter 1.5" Storz x 1.5" NH female rigid	\$100.00
HSFR15-15NPSH	Storz x Female Adapter 1.5" Storz x 1.5" NPSH female rigid	\$100.00
HSFR15-15NPT	Storz x Female Adapter 1.5" Storz x 1.5" NPT female rigid	\$100.00
HSFR15-20NPT	Storz x Female Adapter 1.5" Storz x 2" NPT female rigid	\$150.00
HSFR15-25NH	Storz x Female Adapter 1.5" Storz x 2.5" NH female rigid	\$170.00
HSFR15-25NPT	Storz x Female Adapter 1.5" Storz x 2.5" NPT female rigid	\$170.00
HSFR20-15NH	Storz x Female Adapter 2" Storz x 1.5" NH female rigid	\$105.00
HSFR20-15NPSH	Storz x Female Adapter 2" Storz x 1.5" NPSH female rigid	\$105.00
HSFR20-15NPT	Storz x Female Adapter 2" Storz x 1.5" NT female rigid	\$105.00
HSFR20-20NPT	Storz x Female Adapter 2" Storz x 2" NPT female rigid	\$130.00
HSFR25-15NH	Storz x Female Adapter 2.5" Storz x 1.5" NH female rigid	\$115.00
HSFR25-15NPSH	Storz x Female Adapter 2.5" Storz x 1.5" NPSH female rigid	\$115.00
HSFR25-15NPT	Storz x Female Adapter 2.5" Storz x 1.5" NPT female rigid	\$115.00
HSFR25-20NPT	Storz x Female Adapter 2.5" Storz x 2" NPT female rigid	\$110.00
HSFR25-25NH	Storz x Female Adapter 2.5" Storz x 2.5" NH female rigid	\$115.00
HSFR25-25NPSH	Storz x Female Adapter 2.5" Storz x 2.5" NPSH female rigid	\$115.00
HSFR25-25NPT	Storz x Female Adapter 2.5" Storz x 2.5" NPT female rigid	\$115.00
HSFR25-30NH	Storz x Female Adapter 2.5" Storz x 3" NH female rigid	\$190.00
HSFR25-30NPSH	Storz x Female Adapter 2.5" Storz x 3" NPSH female rigid	\$190.00
HSFR25-30NPT	Storz x Female Adapter 2.5" Storz x 3" NPT female rigid	\$190.00
HSFR30-15NH	Storz x Female Adapter 3" Storz x 1.5" NH female rigid	\$95.00
HSFR30-15NPSH	Storz x Female Adapter 3" Storz x 1.5" NPSH female rigid	\$95.00
HSFR30-20NH	Storz x Female Adapter 3" Storz x 2" NH female rigid	\$120.00
HSFR30-20NPSH	Storz x Female Adapter 3" Storz x 2" NPSH female rigid	\$120.00



STORZ STRAIGHT ADAPTERS

HSFR30-20NPT	Storz x Female Adapter 3" Storz x 2" NPT female rigid	\$120.00
HSFR30-25NH	Storz x Female Adapter 3" Storz x 2.5" NH female rigid	\$110.00
HSFR30-25NPSH	Storz x Female Adapter 3" Storz x 2.5" NPSH female rigid	\$110.00
HSFR30-25NPT	Storz x Female Adapter 3" Storz x 2.5" NPT female rigid	\$110.00
HSFR30-30NH	Storz x Female Adapter 3" Storz x 3" NH female rigid	\$185.00
HSFR30-30NPSH	Storz x Female Adapter 3" Storz x 3" NPSH female rigid	\$185.00
HSFR30-30NPT	Storz x Female Adapter 3" Storz x 3" NPT female rigid	\$185.00
HSFR40-25NH	Storz x Female Adapter 4" Storz/Lok x 2.5" NH female rigid	\$293.00
HSFR40-25NPT	Storz x Female Adapter 4" Storz/Lok x 2.5" NPT female rigid	\$293.00
HSFR40-30NH	Storz x Female Adapter 4" Storz/Lok x 3" NH female rigid	\$294.00
HSFR40-30NPSH	Storz x Female Adapter 4" Storz/Lok x 3" NPSH female rigid	\$294.00
HSFR40-30NPT	Storz x Female Adapter 4" Storz/Lok x 3" NPT female rigid	\$294.00
HSFR40-35NH	Storz x Female Adapter 4" Storz/Lok x 3.5" NH female rigid	\$303.00
HSFR40-35NPSH	Storz x Female Adapter 4" Storz/Lok x 3.5" NPSH female rigid	\$303.00
HSFR40-40NH	Storz x Female Adapter 4" Storz/Lok x 4" NH female rigid	\$346.00
HSFR40-40NPSH	Storz x Female Adapter 4" Storz/Lok x 4" NPSH female rigid	\$346.00
HSFR40-40NPT	Storz x Female Adapter 4" Storz/Lok x 4" NPT female rigid	\$205.00
HSFR40-40NPT/Cap	Storz x Female Adapter 4" Storz/Lok Cap/Cbl x 4" NPT female rigid	\$420.00
HSFR40-45NH	Storz x Female Adapter 4" Storz/Lok x 4.5" NH female rigid	\$410.00
HSFR40-45NPSH	Storz x Female Adapter 4" Storz/Lok x 4.5" NPSH female rigid	\$410.00
HSFR40-50NH	Storz x Female Adapter 4" Storz/Lok x 5" NH female rigid	\$623.00
HSFR40-50NPT	Storz x Female Adapter 4" Storz/Lok x 5" NPT female rigid	\$623.00
HSFR40-60NH	Storz x Female Adapter 4" Storz/Lok x 6" NH female rigid	\$470.00
HSFR40-60NPSH	Storz x Female Adapter 4" Storz/Lok x 6" NPSH female rigid	\$470.00
HSFR40-60NPT	Storz x Female Adapter 4" Storz/Lok x 6" NPT female rigid	\$470.00
HSFR40-60NPT/Cap	Storz x Female Adapter 4" Storz/Lok Cap/Cbl x 6" NPT female rigid	\$676.00
HSFR45-40NH	Storz x Female Adapter 4.5" Storz/Lokx 4" NH female rigid	\$320.00
HSFR45-40NPSH	Storz x Female Adapter 4.5" Storz/Lokx 4" NPSH female rigid	\$320.00
HSFR45-40NPT	Storz x Female Adapter 4.5" Storz/Lokx 4" NPT female rigid	\$320.00
HSFR45-45NH	Storz x Female Adapter 4.5" Storz/Lokx 4.5" NH female rigid	\$370.00
HSFR45-50NH	Storz x Female Adapter 4.5" Storz/Lokx 5" NH female rigid	\$580.00
HSFR45-60NH	Storz x Female Adapter 4.5" Storz/Lokx 6" NH female rigid	\$435.00
HSFR50-25NH	Storz x Female Adapter 5" Storz/Lok x 2.5" NH female rigid	\$391.00
HSFR50-25NH/FTS	Storz x Female Adapter 5" Storz/Lok (FTS) x 2.5" NH female rigid	\$889.00
HSFR50-25NPSH	Storz x Female Adapter 5" Storz/Lok x 2.5" NPSH female rigid	\$391.00
HSFR50-25NPT	Storz x Female Adapter 5" Storz/Lok x 2.5" NPT female rigid	\$391.00
HSFR50-30NH	Storz x Female Adapter 5" Storz/Lok x 3" NH female rigid	\$384.00
HSFR50-30NH/FTS	Storz x Female Adapter 5" Storz/Lok (FTS) x 3" NH female rigid	\$879.00
HSFR50-30NPSH	Storz x Female Adapter 5" Storz/Lok x 3" NPSH female rigid	\$384.00
HSFR50-30NPT	Storz x Female Adapter 5" Storz/Lok x 3" NPT female rigid	\$381.00
HSFR50-35NH	Storz x Female Adapter 5" Storz/Lok x 3.5" NH female rigid	\$418.00
HSFR50-35NH/FTS	Storz x Female Adapter 5" Storz/Lok (FTS) x 3.5" NH female rigid	\$914.00
HSFR50-35NPSH	Storz x Female Adapter 5" Storz/Lok x 3.5" NPSH female rigid	\$418.00
HSFR50-40NH	Storz x Female Adapter 5" Storz/Lok x 4" NH female rigid	\$443.00
HSFR50-40NH/FTS	Storz x Female Adapter 5" Storz/Lok (FTS) x 4" NH female rigid	\$944.00
HSFR50-40NPSH	Storz x Female Adapter 5" Storz/Lok x 4" NPSH female rigid	\$443.00



HSFR50-40NPT	Storz x Female Adapter	5" Storz/Lok x 4" NPT female rigid	\$443.00
HSFR50-40NPT/Cap	Storz x Female Adapter	5" Storz/Lok Cap/Cbl x 4" NPT female rigid	\$753.00
HSFR50-40NPT/FTS	Storz x Female Adapter	5" Storz/Lok (FTS) x 4" NPT female rigid	\$944.00
HSFR50-40NPT/SAS	Storz x Female Adapter	5" Storz/Lok with screen x 4" NPT female rigid	\$533.00
HSFR50-45NH	Storz x Female Adapter	5" Storz/Lok x 4.5" NH female rigid	\$449.00
HSFR50-45NH/FTS	Storz x Female Adapter	5" Storz/Lok (FTS) x 4.5" NH female rigid	\$949.00
HSFR50-45NPSH	Storz x Female Adapter	5" Storz/Lok x 4.5" NPSH female rigid	\$449.00
HSFR50-45NPT	Storz x Female Adapter	5" Storz/Lok x 4.5" NPT female rigid	\$449.00
HSFR50-50NH	Storz x Female Adapter	5" Storz/Lok x 5" NH female rigid	\$462.00
HSFR50-50NH/FTS	Storz x Female Adapter	5" Storz/Lok (FTS) x 5" NH female rigid	\$959.00
HSFR50-50NPSH	Storz x Female Adapter	5" Storz/Lok x 5" NPSH female rigid	\$462.00
HSFR50-50NPT	Storz x Female Adapter	5" Storz/Lok x 5" NPT female rigid	\$462.00
HSFR50-50NPT/Cap	Storz x Female Adapter	5" Storz/Lok Cap/Cbl x 5" NPT female rigid	\$772.00
HSFR50-60NH	Storz x Female Adapter	5" Storz/Lok x 6" NH female rigid	\$579.00
HSFR50-60NH/FTS	Storz x Female Adapter	5" Storz/Lok (FTS) x 6" NH female rigid	\$1,084.00
HSFR50-60NPSH	Storz x Female Adapter	5" Storz/Lok x 6" NPSH female rigid	\$565.00
HSFR50-60NPT	Storz x Female Adapter	5" Storz/Lok x 6" NPT female rigid	\$565.00
HSFR50-60NPT/Cap	Storz x Female Adapter	5" Storz/Lok Cap/Cbl x 6" NPT female rigid	\$785.00
HSFR60-40NH	Storz x Female Adapter	6" Storz/Lok x 4" NH female rigid	\$705.00
HSFR60-40NPSH	Storz x Female Adapter	6" Storz/Lok x 4" NPSH female rigid	\$705.00
HSFR60-40NPT	Storz x Female Adapter	6" Storz/Lok x 4" NPT female rigid	\$705.00
HSFR60-45NH	Storz x Female Adapter	6" Storz/Lok x 4.5" NH female rigid	\$665.00
HSFR60-50NH	Storz x Female Adapter	6" Storz/Lok x 5" NH female rigid	\$725.00
HSFR60-50NPSH	Storz x Female Adapter	6" Storz/Lok x 5" NPSH female rigid	\$725.00
HSFR60-50NPT	Storz x Female Adapter	6" Storz/Lok x 5" NPT female rigid	\$725.00
HSFR60-60NH	Storz x Female Adapter	6" Storz/Lok x 6" NH female rigid	\$630.00
HSFR60-60NPSH	Storz x Female Adapter	6" Storz/Lok x 6" NPSH female rigid	\$630.00
HSFR60-60NPT	Storz x Female Adapter	6" Storz/Lok x 6" NPT female rigid	\$630.00
HSFR60-60NPT/Cap	Storz x Female Adapter	6" Storz/Lok Cap/Cbl x 6" NPT female rigid	\$974.00

HSMR - Storz x Male Rigid Adapter



The Harrington Model HSMR straight Storz adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. The adapter shall have male thread NH, NPT, & NPSH connections in various from 1.5” to 6” size. Storz connections from 1.5” to 6” shall be compliant to applicable NFPA standards. Storz locking provisions provided for sizes over 4”.

HSMR15-15NH	Storz x Male Rigid Adapter	1.5" Storz x 1.5" NH male	\$90.00
HSMR15-15NPSH	Storz x Male Rigid Adapter	1.5" Storz x 1.5" NPSH male	\$90.00
HSMR15-15NPT	Storz x Male Rigid Adapter	1.5" Storz x 1.5" NPT male	\$90.00
HSMR15-25NH	Storz x Male Rigid Adapter	1.5" Storz x 2.5" NH male	\$105.00



STORZ STRAIGHT ADAPTERS

HSMR15-25NPT	Storz x Male Rigid Adapter 1.5" Storz x 2.5" NPT male	\$105.00
HSMR20-15NH	Storz x Male Rigid Adapter 2" Storz x 1.5" NH male	\$90.00
HSMR20-15NPSH	Storz x Male Rigid Adapter 2" Storz x 1.5" NPSH male	\$90.00
HSMR20-15NPT	Storz x Male Rigid Adapter 2" Storz x 1.5" NPT male	\$90.00
HSMR20-20BSP	Storz x Male Rigid Adapter 2" Storz x 2" BSP male	\$90.00
HSMR20-25NH	Storz x Male Rigid Adapter 2" Storz x 2.5" NH male	\$100.00
HSMR25-15NH	Storz x Male Rigid Adapter 2.5" Storz x 1.5" NH male	\$125.00
HSMR25-25NH	Storz x Male Rigid Adapter 2.5" Storz x 2.5" NH male	\$105.00
HSMR25-25NPT	Storz x Male Rigid Adapter 2.5" Storz x 2.5" NPT male	\$105.00
HSMR25-30NH	Storz x Male Rigid Adapter 2.5" Storz x 3" NH male	\$165.00
HSMR25-30NPSH	Storz x Male Rigid Adapter 2.5" Storz x 3" NPSH male	\$165.00
HSMR25-30NPT	Storz x Male Rigid Adapter 2.5" Storz x 3" NPT male	\$165.00
HSMR30-25NH	Storz x Male Rigid Adapter 3" Storz x 2.5" NH male	\$100.00
HSMR30-25NPT	Storz x Male Rigid Adapter 3" Storz x 2.5" NPT male	\$100.00
HSMR30-30NH	Storz x Male Rigid Adapter 3" Storz x 3" NH male	\$155.00
HSMR30-30NPSH	Storz x Male Rigid Adapter 3" Storz x 3" NPSH male	\$155.00
HSMR30-30NPT	Storz x Male Rigid Adapter 3" Storz x 3" NPT male	\$155.00
HSMR40-25NH	Storz x Male Rigid Adapter 4" Storz/Lok x 2.5" NH male	\$303.00
HSMR40-25NPSH	Storz x Male Rigid Adapter 4" Storz/Lok x 2.5" NPSH male	\$303.00
HSMR40-25NPT	Storz x Male Rigid Adapter 4" Storz/Lok x 2.5" NPT male	\$303.00
HSMR40-30NH	Storz x Male Rigid Adapter 4" Storz/Lok x 3" NH male	\$302.00
HSMR40-30NPSH	Storz x Male Rigid Adapter 4" Storz/Lok x 3" NPSH male	\$302.00
HSMR40-30NPT	Storz x Male Rigid Adapter 4" Storz/Lok x 3" NPT male	\$302.00
HSMR40-35NH	Storz x Male Rigid Adapter 4" Storz/Lok x 3.5" NH male	\$305.00
HSMR40-40BSP/SL	Storz x Male Rigid Adapter 4" Storz/Lok x 4" BSP male	\$302.00
HSMR40-40NH	Storz x Male Rigid Adapter 4" Storz/Lok x 4" NH male	\$307.00
HSMR40-40NPSH	Storz x Male Rigid Adapter 4" Storz/Lok x 4" NPSH male	\$307.00
HSMR40-40NPT	Storz x Male Rigid Adapter 4" Storz/Lok x 4" NPT male	\$307.00
HSMR40-40NPT/Cap	Storz x Male Rigid Adapter 4" Storz/Lok Cap/Cbl x 4" NPT male	\$528.00
HSMR40-40NPT	Storz x Male Rigid Adapter 4" Storz/Lok (PTS) x 4" NPT male	\$642.00
HSMR40-45NH	Storz x Male Rigid Adapter 4" Storz/Lok x 4.5" NH male	\$354.00
HSMR40-50NH	Storz x Male Rigid Adapter 4" Storz/Lok x 5" NH male	\$375.00
HSMR40-50NPSH	Storz x Male Rigid Adapter 4" Storz/Lok x 5" NPSH male	\$375.00
HSMR40-50NPT	Storz x Male Rigid Adapter 4" Storz/Lok x 5" NPT male	\$375.00
HSMR40-60NH	Storz x Male Rigid Adapter 4" Storz/Lok x 6" NH male	\$380.00
HSMR40-60NPT	Storz x Male Rigid Adapter 4" Storz/Lok x 6" NPT male	\$380.00
HSMR40-60NPT/Cap	Storz x Male Rigid Adapter 4" Storz/Lok Cap/Cbl x 6" NPT male	\$601.00
HSMR45-25NH	Storz x Male Rigid Adapter 4.5" Storz/Lok x 2.5" NH male	\$275.00
HSMR45-25NPT	Storz x Male Rigid Adapter 4.5" Storz/Lok x 2.5" NPT male	\$275.00
HSMR45-30NH	Storz x Male Rigid Adapter 4.5" Storz/Lok x 3" NH male	\$275.00
HSMR45-30NPSH	Storz x Male Rigid Adapter 4.5" Storz/Lok x 3" NPSH male	\$275.00
HSMR45-30NPT	Storz x Male Rigid Adapter 4.5" Storz/Lok x 3" NPT male	\$275.00
HSMR45-40NPSH	Storz x Male Rigid Adapter 4.5" Storz/Lok x 4" NPSH male	\$275.00
HSMR45-40NPT	Storz x Male Rigid Adapter 4.5" Storz/Lok x 4" NPT male	\$275.00
HSMR45-45NH	Storz x Male Rigid Adapter 4.5" Storz/Lok x 4.5" NH male	\$330.00



HSMR45-50NH	Storz x Male Rigid Adapter 4.5" Storz/Lok x 5" NH male	\$350.00
HSMR45-60NH	Storz x Male Rigid Adapter 4.5" Storz/Lok x 6" NH male	\$355.00
HSMR50-25NH	Storz x Male Rigid Adapter 5" Storz/Lok x 2.5" NH male	\$412.00
HSMR50-25NPSH	Storz x Male Rigid Adapter 5" Storz/Lok x 2.5" NPSH male	\$412.00
HSMR50-25NPT	Storz x Male Rigid Adapter 5" Storz/Lok x 2.5" NPT male	\$412.00
HSMR50-30NH	Storz x Male Rigid Adapter 5" Storz/Lok x 3" NH male	\$381.00
HSMR50-30NPSH	Storz x Male Rigid Adapter 5" Storz/Lok x 3" NPSH male	\$381.00
HSMR50-30NPT	Storz x Male Rigid Adapter 5" Storz/Lok x 3" NPT male	\$381.00
HSMR50-35NH	Storz x Male Rigid Adapter 5" Storz/Lok x 3.5" NH male	\$410.00
HSMR50-35NPSH	Storz x Male Rigid Adapter 5" Storz/Lok x 3.5" NPSH male	\$410.00
HSMR50-40BSP/SL	Storz x Male Rigid Adapter 5" Storz/Lok x 4" BSP male rigid	\$416.00
HSMR50-40BSP4	Storz x Male Rigid Adapter 5" Storz/Lok (PTS) x 4" BSP male	\$416.00
HSMR50-40NH	Storz x Male Rigid Adapter 5" Storz/Lok x 4" NH male	\$410.00
HSMR50-40NH/FTS	Storz x Male Rigid Adapter 5" Storz/Lok (FTS) x 4" NH male	\$909.00
HSMR50-40NPSH	Storz x Male Rigid Adapter 5" Storz/Lok x 4" NPSH male	\$410.00
HSMR50-40NPT	Storz x Male Rigid Adapter 5" Storz/Lok x 4" NPT male	\$410.00
HSMR50-40NPT/Cap	Storz x Male Rigid Adapter 5" Storz/Lok Cap/Cbl x 4" NPT male	\$720.00
HSMR50-45NH	Storz x Male Rigid Adapter 5" Storz/Lok x 4.5" NH male	\$452.00
HSMR50-45NH/FTS	Storz x Male Rigid Adapter 5" Storz/Lok (FTS) x 4.5" NH male	\$949.00
HSMR50-50NH	Storz x Male Rigid Adapter 5" Storz/Lok x 5" NH male	\$460.00
HSMR50-50NPSH	Storz x Male Rigid Adapter 5" Storz/Lok x 5" NPSH male	\$460.00
HSMR50-50NPT	Storz x Male Rigid Adapter 5" Storz/Lok x 5" NPT male	\$460.00
HSMR50-50NPT/Cap	Storz x Male Rigid Adapter 5" Storz/Lok Cap/Cbl x 5" NPT male	\$756.00
HSMR50-60NH	Storz x Male Rigid Adapter 5" Storz/Lok x 6" NH male	\$498.00
HSMR50-60NPSH	Storz x Male Rigid Adapter 5" Storz/Lok x 6" NPSH male	\$498.00
HSMR50-60NPT	Storz x Male Rigid Adapter 5" Storz/Lok x 6" NPT male	\$498.00
HSMR50-60NPT/Cap	Storz x Male Rigid Adapter 5" Storz/Lok Cap/Cbl x 6" NPT male	\$808.00
HSMR60-40NH	Storz x Male Rigid Adapter 6" Storz/Lok x 4" NH male	\$670.00
HSMR60-40NPT	Storz x Male Rigid Adapter 6" Storz/Lok x 4" NPT male	\$670.00
HSMR60-45NH	Storz x Male Rigid Adapter 6" Storz/Lok x 4.5" NH male	\$715.00
HSMR60-50NH	Storz x Male Rigid Adapter 6" Storz/Lok x 5" NH male	\$625.00
HSMR60-50NPT	Storz x Male Rigid Adapter 6" Storz/Lok x 5" NPT male	\$625.00
HSMR60-60NH	Storz x Male Rigid Adapter 6" Storz/Lok x 6" NH male	\$635.00
HSMR60-60NPT	Storz x Male Rigid Adapter 6" Storz/Lok x 6" NPT male	\$635.00
HSMR60-60NPT/Cap	Storz x Male Rigid Adapter 6" Storz/Lok Cap/Cbl x 6" NPT male	\$977.00



HFL-FF Flat-Face Flange x Storz Adapter

The Harrington Model HFL-FF adapter are available with either straight or 30-degree elbow Storz connections. The Storz shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The 150# carbon steel flange shall be stripped and cleaned of any manufacturing oils, providing a good base for primer adhesion. A Zinc rich primer coat shall be applied, sealing the entire carbon steel flange. After threads are cut, a powder-coated finish shall be applied to the entire flange in black in color. Flanges are available either in “Flat-Face” design, in sizes from 2.5” to 6”. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Provided in sizes from 2.5” to 6”, including NFPA compliant Storz connections with locking provisions for sizes over 4”. All units are supplied with or without blind cap and cable.



HFL-FF-30-25ST/Cap	3" Flat-Faced 150# Steel Flange x Aluminum 2.5" Storz Cap/Cbl	\$427.00
HFL-FF-30-30ST/Cap	3" Flat-Faced 150# Steel Flange x Aluminum 3" Storz Cap/Cbl	\$436.00
HFL-FF-40-40ST/Cap	4" Flat-Faced 150# Steel Flange x Aluminum 4" Storz/Lok Cap/Cbl	\$680.00
HFL-FF-404030E/Cap	4" Flat-Faced 150# Steel Flange x Aluminum 30° Elbow 4" Storz/Lok Cap/Cbl	\$932.00
HFL-FF-40-50ST/Cap	4" Flat-Faced 150# Steel Flange x Aluminum 5" Storz/Lok Cap/Cbl	\$950.00
HFL-FF-405030E/Cap	4" Flat-Faced 150# Steel Flange x Aluminum 30° Elbow 5" Storz/Lok Cap/Cbl	\$1,113.00
HFL-FF-50-50ST/Cap	5" Flat-Faced 150# Steel Flange x Aluminum 5" Storz/Lok Cap/Cbl	\$1,071.00
HFL-FF-60-50ST	6" Flat-Faced 150# Steel Flange x Aluminum 5" Storz/Lok	\$790.00
HFL-FF-60-50ST/Cap	6" Flat-Faced 150# Steel Flange x Aluminum 5" Storz/Lok Cap/Cbl	\$1,103.00
HFL-FF-605030E/Cap	6" Flat-Faced 150# Steel Flange x Aluminum 30° Elbow 5" Storz/Lok Cap/Cbl	\$1,283.00
HFL-FF-60-60ST	6" Flat-Faced 150# Steel Flange x Aluminum 6" Storz/Lok	\$675.00
HFL-FF-60-60ST/Cap	6" Flat-Faced 150# Steel Flange x Aluminum 6" Storz/Lok Cap/Cbl	\$1,040.00
HFL-FF-606030E/Cap	6" Flat-Faced 150# Steel Flange x Aluminum 30° Elbow 6" Storz/Lok Cap/Cbl	\$1,500.00

HFL-RF Raised-Face Flange x Storz Adapter

The Harrington Model HFL-RF adapter are available with either straight or 30-degree elbow Storz connections. The adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The 150# carbon steel flange shall be stripped and cleaned of any manufacturing oils, providing a good base for primer adhesion. A zinc-rich primer coat shall be applied, sealing the entire carbon steel flange. After threads are cut, a powder-coated finish shall be applied to the entire flange in black in color. Flanges are available either in “Raised-Face” design, in sizes from 2.5” to 6”. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Provided in sizes from 2.5” to 6”, including NFPA compliant Storz connections with locking provisions for sizes over 4”. All units are supplied with blind cap and cable.



HFL-RF-40-40ST/Cap	4" Raised-Faced 150# Steel Flange x Aluminum 4" Storz/Lok Cap/Cbl	\$680.00
HFL-RF-404030E/Cap	4" Raised-Faced 150# Steel Flange x Aluminum 30° Elbow 4" Storz/Lok Cap/Cbl	\$932.00
HFL-RF-40-50ST/Cap	4" Raised-Faced 150# Steel Flange x Aluminum 5" Storz/Lok Cap/Cbl	\$950.00
HFL-RF-405030E/Cap	4" Raised-Faced 150# Steel Flange x Aluminum 30° Elbow 5" Storz/Lok Cap/Cbl	\$1,113.00
HFL-RF-50-50ST/Cap	5" Raised-Faced 150# Steel Flange x Aluminum 5" Storz/Lok Cap/Cbl	\$1,071.00
HFL-RF-60-50ST	6" Raised-Faced 150# Steel Flange x Aluminum 5" Storz/Lok	\$790.00
HFL-RF-60-50ST/Cap	6" Raised-Faced 150# Steel Flange x Aluminum 5" Storz/Lok Cap/Cbl	\$1,103.00



HFL-RF-605030E/Cap	6" Raised-Faced 150# Steel Flange x Aluminum 30° Elbow 5" Storz/Lok Cap/Cbl	\$1,283.00
HFL-RF-60-60ST	6" Raised-Faced 150# Steel Flange x Aluminum 6" Storz/Lok	\$675.00
HFL-RF-60-60ST/Cap	6" Raised-Faced 150# Steel Flange x Aluminum 6" Storz/Lok Cap/Cbl	\$1,040.00
HFL-RF-606030E/Cap	6" Raised-Faced 150# Steel Flange x Aluminum 30° Elbow 6" Storz/Lok Cap/Cbl	\$1,500.00

HFL-FF Flat-Faced Flange x Male or Female Threaded Adapter



The Harrington Model HFL-RF adapter are available with either straight or 30-degree elbow Storz connections. The adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The 150# carbon steel flange shall be stripped and cleaned of any manufacturing oils, providing a good base for primer adhesion. A zinc-rich primer coat shall be applied, sealing the entire carbon steel flange. After threads are cut, a powder-coated finish shall be applied to the entire flange in black in color. Flanges are available either in “Raised-Face” design, in sizes from 2.5” to 6”. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Provided in sizes from 2.5” to 6”, including NFPA compliant Storz connections with locking provisions for sizes over 4”. All units are supplied with blind cap and cable.

HFL-FF-40-45NHM	4" Flat-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH Male	\$400.00
HFL-FF-60-45NHM	6" Flat-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH Male	\$585.00
HFL-FF-60-60NHM	6" Flat-Faced 150# Carbon Steel Flange x Aluminum 6" NH Male	\$490.00
HFL-FF-40-45NHFS	4" Flat-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH FS R/L	\$520.00
HFL-FF-60-45NHFS	6" Flat-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH FS R/L	\$610.00
HFL-FF-60-60NHFS	6" Flat-Faced 150# Carbon Steel Flange x Aluminum 6" NH FS R/L	\$475.00

HFL-RF Raised-Faced Flange x Male or Female Threaded Adapter



The Harrington Model HFL-RF straight adapter shall have ‘male NH’ or special thread options. The adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The 150# carbon steel flange shall be stripped and cleaned of any manufacturing oils, providing a good base for primer adhesion. A zinc-rich primer coat shall be applied, sealing the entire carbon steel flange. After threads are cut, a powder coated finish shall be applied to the entire flange in red or black in color. Flanges are available either in “Flat-Face” or “Raised-Face” design, in 2.5” or 6” sizes. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. The NH female and male adapter shall be in sizes from 2.5” or 6” sizes. Blind caps and full-time swivels available as options.

HFL-RF-40-45NHM	4" Raised-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH Male	\$400.00
HFL-RF-60-45NHM	6" Raised-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH Male	\$585.00
HFL-RF-60-60NHM	6" Raised-Faced 150# Carbon Steel Flange x Aluminum 6" NH Male	\$490.00
HFL-RF-40-45NHFS	4" Raised-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH FS R/L	\$520.00
HFL-RF-60-45NHFS	6" Raised-Faced 150# Carbon Steel Flange x Aluminum 4.5" NH FS R/L	\$610.00
HFL-RF-60-60NHFS	6" Raised-Faced 150# Carbon Steel Flange x Aluminum 6" NH FS R/L	\$475.00



HSTS - Storz x Storz Adapters

The Harrington Model HSTS straight Storz adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Storz connections in various sizes from 1” to 8” and are NFPA compliant with Storz locking provisions provided for sizes over 4”. Various types of reducing and rigid adapters, full-time-swivel, and screens are available.



HSTS15-10R	Storz x Storz Adapter 1.5” Storz x 1” Storz rigid	\$200.00
HSTS20-15R	Storz x Storz Adapter 2” Storz x 1.5” Storz rigid	\$169.00
HSTS25-10R	Storz x Storz Adapter 2.5” Storz x 1” Storz rigid	\$338.00
HSTS25-15R	Storz x Storz Adapter 2.5” Storz x 1.5” Storz rigid	\$206.00
HSTS25-20R	Storz x Storz Adapter 2.5” Storz x 2” Storz rigid	\$200.00
HSTS30-20R	Storz x Storz Adapter 3” Storz x 2” Storz rigid	\$194.00
HSTS30-25R	Storz x Storz Adapter 3” Storz x 2.5” Storz rigid	\$163.00
HSTS40-25R	Storz x Storz Adapter 4” Storz/Lok x 2.5” Storz rigid	\$317.00
HSTS40-30R	Storz x Storz Adapter 4” Storz/Lok x 3” Storz rigid	\$317.00
HSTS40-40/SAS	Storz x Storz Adapter 4” Storz/Lok Screen x 4” Storz/Lok rigid	\$568.00
HSTS45-25R	Storz x Storz Adapter 4.5” Storz/Lok x 2.5” Storz rigid	\$363.00
HSTS45-30R	Storz x Storz Adapter 4.5” Storz/Lok x 3” Storz rigid	\$356.00
HSTS45-40R	Storz x Storz Adapter 4.5” Storz/Lok x 4” Storz/Lok rigid	\$594.00
HSTS50-25R	Storz x Storz Adapter 5” Storz/Lok x 2.5” Storz rigid	\$445.00
HSTS50-30R	Storz x Storz Adapter 5” Storz/Lok x 3” Storz rigid	\$445.00
HSTS50-40R	Storz x Storz Adapter 5” Storz/Lok x 4” Storz/Lok rigid	\$626.00
HSTS50-40/FTS	Storz x Storz Adapter 5” Storz/Lok (FTS) x 4” Storz/Lok rigid	\$1,109.00
HSTS50-45R	Storz x Storz Adapter 5” Storz/Lok x 4.5” Storz/Lok rigid	\$570.00
HSTS50-50/SAS	Storz x Storz Adapter 5” Storz/Lok Screen x 5” Storz/Lok rigid	\$806.00
HSTS50-50/FTS	Storz x Storz Adapter 5” Storz/Lok (FTS) x 5” Storz/Lok rigid	\$1,204.00
HSTS60-25R	Storz x Storz Adapter 6” Storz/Lok x 2.5” Storz rigid	\$645.00
HSTS60-30R	Storz x Storz Adapter 6” Storz/Lok x 3” Storz rigid	\$640.00
HSTS60-40R	Storz x Storz Adapter 6” Storz/Lok x 4” Storz/Lok rigid	\$765.00
HSTS60-45R	Storz x Storz Adapter 6” Storz/Lok x 4.5” Storz/Lok rigid	\$745.00
HSTS60-50R	Storz x Storz Adapter 6” Storz/Lok x 5” Storz/Lok rigid	\$787.00
HSTS60-50/FTS	Storz x Storz Adapter 6” Storz/Lok rigid x 5” Storz/Lok Full Time Swivel	\$1,379.00
HSTS60-60/SAS	Storz x Storz Adapter 6” Storz/Lok Screen x 6” Storz/Lok rigid	\$1,090.00



HSFR - Storz x BSP Female Rigid Adapter



The Harrington Model HSFR Storz x BSP adapter shall be “forged” for maximum strength and rated for a working pressure of 250 PSI. The adapter shall be hard coat anodized of Type #6061-T6 aluminum. Storz connections in various sizes from 1” to 8” and are NFPA compliant with Storz locking provisions provided for sizes over 4”. BSP connections available from in sizes from 0.50” to 6”. Various types of reducing and rigid adapters, full-time-swivel, and screens are available.

HSFR10-050BSP	Storz x BSP Female Adapter 1” Storz x 0.5” BSP Female rigid	\$60.00
HSFR10-10BSP	Storz x BSP Female Adapter 1” Storz x 1” BSP Female rigid	\$65.00
HSFR15-15BSP	Storz x BSP Female Adapter 1.5” Storz x 1.5” BSP Female rigid	\$65.00
HSFR15-15BSPB	Storz x BSP Female Adapter 1.5” Storz x 1.5” BSP Female rigid Brass	\$135.00
HSFR15-20BSP	Storz x BSP Female Adapter 1.5” Storz x 2” BSP Female rigid	\$119.00
HSFR20-15BSP	Storz x BSP Female Adapter 2” Storz x 1.5” BSP Female rigid	\$69.00
HSFR20-20BSP	Storz x BSP Female Adapter 2” Storz x 2” BSP Female rigid	\$50.00
HSFR25-15BSP	Storz x BSP Female Adapter 2.5” Storz x 1.5” BSP Female rigid	\$125.00
HSFR25-20BSP	Storz x BSP Female Adapter 2.5” Storz x 2” BSP Female rigid	\$69.00
HSFR25-25BSP	Storz x BSP Female Adapter 2.5” Storz x 2.5” BSP Female rigid	\$63.00
HSFR25-25BSP/SL	Storz x BSP Female Adapter 2.5” Storz with lock x 2.5” BSP Female rigid	\$175.00
HSFR25-30BSP	Storz x BSP Female Adapter 2.5” Storz x 3” BSP Female rigid	\$175.00
HSFR30-20BSP	Storz x BSP Female Adapter 3” Storz x 2” BSP Female rigid	\$85.00
HSFR30-25BSP	Storz x BSP Female Adapter 3” Storz (75) x 2.5” BSP Female rigid	\$60.00
HSFR30-25BSP/SL	Storz x BSP Female Adapter 3” Storz (75) with lock x 2.5” BSP Female rigid	\$175.00
HSFR30-30BSP	Storz x BSP Female Adapter 3” Storz (75) x 3” BSP Female rigid	\$65.00
HSFR40-25BSP	Storz x BSP Female Adapter 4” Storz (100) with lock x 2.5” BSP Female rigid	\$310.00
HSFR40-40BSP4N	Storz x BSP Female Adapter 4” Storz (100) with lock x 4” BSP Female rigid Clear Anodized	\$210.00
HSFR40-40BSP4N/BL	Storz x BSP Female Adapter 4” Storz (100) with lock x 4” BSP Female rigid Black Anodized	\$212.00
HSFR40-50BSP/SL	Storz x BSP Female Adapter 4” Storz (100) with lock x 5” BSP Female rigid	\$345.00
HSFR40-60BSP/SL	Storz x BSP Female Adapter 4” Storz (100) with lock x 6” BSP Female rigid	\$395.00
HSFR45-40BSP/SL(Storz 110)	Storz x BSP Female Adapter 4.5” Storz (110) with lock x 4” BSP Female rigid	\$185.00
HSFR45-50BSP/SL(Storz 110)	Storz x BSP Female Adapter 4.5” Storz (110) with lock x 5” BSP Female rigid	\$315.00
HSFR50-40BSP/SL	Storz x BSP Female Adapter 5” Storz (125) with lock 4” BSP Female rigid	\$395.00
HSFR50-40BSP/FTS	Storz x BSP Female Adapter 5” Storz (125) with lock Full Time Swivel x 4” BSP Female rigid	\$910.00
HSFR50-50BSP5N	Storz x BSP Female Adapter 5” Storz (125) with lock x 5” BSP Female rigid Clear Anodized	\$295.00
HSFR50-50BSP5N/BL	Storz x BSP Female Adapter 5” Storz (125) with lock x 5” BSP Female rigid Black Anodized	\$298.00
HSFR50-60BSP/SL	Storz x BSP Female Adapter 5” Storz (125) with lock x 6” BSP Female rigid	\$475.00
HSFR60-40BSP/SL	Storz x BSP Female Adapter 3 Lug 6” Storz (150) with lock x 4” BSP Female rigid	\$563.00
HSFR60-50BSP/SL	Storz x BSP Female Adapter 3 Lug 6” Storz (150) with lock x 5” BSP female rigid	\$594.00
HSFR60-60BSP6F	Storz x BSP Female Adapter 3 Lug 6” Storz (150) with lock x 6” BSP female rigid	\$425.00
HSFR80-80BSP-US	Storz x BSP Female Adapter 8” Storz (205) with lock x 8” BSP female rigid Clear Anodized	\$2,005.00



HFTS - 5" Full-Time Swivel x BSP Female Adapters

HFTS50-40BSP/SL	Storz x BSP Female Adapter 5" Storz/Lok (FTS) x 4" BSP Female	\$906.00
HFTS50-50BSP/SL	Storz x BSP Female Adapter 5" Storz/Lok (FTS) x 5" BSP Female	\$794.00

HSAS - Storz Suction Screens

The Harrington Model HSAS Storz adapter suction screen assembled with a stainless-steel screen with a metal ring for 4", 5", and 6" sizes.

HSAS-40	Screens 4" Storz Adapters Stainless Steel	\$81.00
HSAS-50	Screens 5" Storz Adapters Stainless Steel	\$88.00
HSAS-60	Screens 6" Storz Adapters Stainless Steel	\$100.00



HBC - Storz Blind Caps

The Harrington Model HBC Storz blind cap shall be "forged" for maximum strength and rated for a working pressure of 250 PSI. The lightweight aluminum shall be hard-coated anodized, in both clear and dark color. Storz connections in various sizes from 1" to 8". Available options for either chains or stainless-steel reflective cable Optional .250" bleeder drain.

HBC-10	1" Storz Blind Cap/Chain	\$81.00
HBC-15	1.5" Storz Blind Cap/Chain	\$63.00
HBC-20	2" Storz Blind Cap/Chain	\$50.00
HBC-25	2.5" Storz Blind Cap/Chain	\$63.00
HBC-30	3" Storz Blind Cap/Chain	\$69.00
HBC-40	4" Storz blind Cap/Chain	\$221.00
HBC-40-PC	4" Storz Blind Cap/Chain .250" Bleeder	\$321.00
HBC-40-US	4" Storz Blind Cap w/ reflective cable and S hook - Clear anodized	\$221.00
HBC-40D-US	4" Storz Blind Cap w/ reflective cable and S hook - Dark Anodized	\$221.00
HBC-40-US-BA	4" Storz Blind cap w/ reflective cable and S hook - Black Anodized	\$221.00
HBC-45	4.5" Storz Blind Cap/Chain	\$225.00
HBC-50	5" Storz Blind Cap/Chain	\$310.00
HBC-50-PC	5" Storz Blind Cap/Chain .250" Bleeder	\$395.00
HBC-50-PC8	5" Storz Blind Cap/Cbl .125" Bleeder	\$395.00
HBC-50-US	5" Storz Blind Cap w/ reflective cable and S hook - Clear anodized	\$310.00
HBC-50D-US	5" Storz Blind Cap w/ reflective cable and S hook - Dark Anodized	\$310.00
HBC-50-US-BA	5" Storz Blind cap w/ reflective cable and S hook - Black Anodized	\$310.00
HBC-60	6" Storz Blind Cap/Cbl- 3-Lugs	\$385.00
HBC-60-PC	6" Storz Blind Cap .250" Bleeder 3-Lugs	\$488.00
HBC-80-US	8" Storz Blind Cap/Cbl - 3-Lugs	\$2,370.00



H35 - Double-Female Swivel Threaded Adapter- Rocker Lug



The Harrington Model H35 double-female swivel threaded adapter is offered in various sizes from GHT to 6" NH & NPSH threads or special threads, with rocker lugs on each female swivel. All threaded adapters are hard coated anodized of Type #6061-T6 light-weight aluminum. Adapters 3.5" and under in size utilize stainless-steel ball bearings and sizes 4" and larger have aluminum roller bearings (no plastic). Adapter shall have a maximum of 250 PSI working pressure. Laser etching available at 'No Charge'.

H35-10NH-10NH	1" NH Double-FS Adapter R/L x 1" NH FS R/L	\$65.00
H35-15NH-10NH	1.5" NH Double-FS Adapter R/L x 1" NH FS R/L	\$115.00
H35-15NH-15NH	1.5" NH Double-FS Adapter R/L x 1.5" NH FS R/L	\$80.00
H35-15NH-15NPSH/PLUG	1.5" NH Double-FS Adapter R/L x 1.5" NPSH FS R/L / 1.5" NPSH male plug	\$135.00
H35-15NPSH-15NPSH	1.5" NPSH Double-FS Adapter R/L x 1.5" NPSH FS R/L	\$80.00
H35-20NH-15NH	2" NH Double-FS Adapter R/L x 1.5" NH FS R/L	\$115.00
H35-20NH-20NH	2" NH Double-FS Adapter R/L x 2" NH FS R/L	\$115.00
H35-25NH-15NH	2.5" NH Double-FS Adapter R/L x 1.5" NH FS R/L	\$125.00
H35-25NH-20NH	2.5" NH Double-FS Adapter R/L x 2" NH FS R/L	\$125.00
H35-25NH-25NH	2.5" NH Double-FS Adapter R/L x 2.5" NH FS R/L	\$110.00
H35-25NPSH-25NPSH	2.5" NPSH Double-FS Adapter R/L x 2.5" NPSH FS R/L	\$110.00
H35-30NH-25NH	3" NH Double-FS Adapter R/L x 2.5" NH FS R/L	\$230.00
H35-30NH-30NH	3" NH Double-FS Adapter R/L x 3" NH FS R/L	\$195.00
H35-35NH-25NH	3.5" NH Double-FS Adapter R/L x 2.5" NH FS R/L	\$315.00
H35-35NH-30NH	3.5" NH Double-FS Adapter R/L x 3" NH FS R/L	\$340.00
H35-35NH-35NH	3.5" NH Double-FS Adapter R/L x 3.5" NH FS R/L	\$315.00
H35-40NH-25NH	4" NH Double-FS Adapter R/L x 2.5" NH FS R/L	\$320.00
H35-40NH-30NH	4" NH Double-FS Adapter R/L x 3" NH FS R/L	\$370.00
H35-40NH-35NH	4" NH Double-FS Adapter R/L x 3.5" NH FS R/L	\$385.00
H35-40NH-40NH	4" NH Double-FS Adapter R/L x 4" NH FS R/L	\$400.00
H35-45NH-25NH	4.5" NH Double-FS Adapter R/L x 2.5" NH FS R/L	\$405.00
H35-45NH-30NH	4.5" NH Double-FS Adapter R/L x 3" NH FS R/L	\$425.00
H35-45NH-35NH	4.5" NH Double-FS Adapter R/L x 3.5" NH FS R/L	\$410.00
H35-45NH-40NH	4.5" NH Double-FS Adapter R/L x 4" NH FS R/L	\$395.00
H35-45NH-45NH	4.5" NH Double-FS Adapter R/L x 4.5" NH FS R/L	\$355.00
H35-50NH-25NH	5" NH Double-FS Adapter R/L x 2.5" NH FS R/L	\$475.00
H35-50NH-30NH	5" NH Double-FS Adapter R/L x 3" NH FS R/L	\$525.00
H35-50NH-35NH	5" NH Double-FS Adapter R/L x 3.5" NH FS R/L	\$530.00
H35-50NH-40NH	5" NH Double-FS Adapter R/L x 4" NH FS R/L	\$600.00
H35-50NH-45NH	5" NH Double-FS Adapter R/L x 4.5" NH FS R/L	\$725.00
H35-50NH-50NH	5" NH Double-FS Adapter R/L x 5" NH FS R/L	\$575.00
H35-60NH-25NH	6" NH Double-FS Adapter R/L x 2.5" NH FS R/L	\$820.00
H35-60NH-30NH	6" NH Double-FS Adapter R/L x 3" NH FS R/L	\$765.00
H35-60NH-35NH	6" NH Double-FS Adapter R/L x 3.5" NH FS R/L	\$745.00
H35-60NH-40NH	6" NH Double-FS Adapter R/L x 4" NH FS R/L	\$735.00
H35-60NH-45NH	6" NH Double-FS Adapter R/L x 4.5" NH FS R/L	\$745.00
H35-60NH-50NH	6" NH Double-FS Adapter R/L x 5" NH FS R/L	\$670.00
H35-60NH-60NH	6" NH Double-FS Adapter R/L x 6" NH FS R/L	\$605.00



H36 - Double Male Adapter - Rocker Lug

The Harrington Model H36 threaded double-male adapter is offered in various sizes from GHT to 6" NH, NPT & NPSH threads or special threads, with a single row of rocker lugs. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Adapters have a maximum of 250 PSI working pressure. Laser etching available at No Charge.



H36-10NH-GHT	1" NH Double-Male Adapter R/L x garden hose male	\$50.00
H36-10NH-10NH	1" NH Double-Male Adapter R/L x 1" NH male	\$55.00
H36-15NH-GHT	1.5" NH Double-Male Adapter R/L x garden hose male	\$110.00
H36-15NH-10NH	1.5" NH Double-Male Adapter R/L x 1" NH male	\$105.00
H36-15NH-15NH	1.5" NH Double-Male Adapter R/L x 1.5" NH male	\$45.00
H36-15NPSH-15NPSH	1.5" NPSH Double-Male Adapter R/L x 1.5" NPSH male	\$45.00
H36-20NH-GHT	2" NH Double-Male Adapter R/L x garden hose male	\$110.00
H36-20NH-10NH	2" NH Double-Male Adapter R/L x 1" NH male	\$105.00
H36-20NH-15NH	2" NH Double-Male Adapter R/L x 1.5" NH male	\$85.00
H36-20NH-20NH	2" NH Double-Male Adapter R/L x 2" NH male	\$85.00
H36-25NH-GHT	2.5" NH Double-Male Adapter R/L x garden hose male	\$110.00
H36-25NH-10NH	2.5" NH Double-Male Adapter R/L x 1" NH male	\$105.00
H36-25NH-15NH	2.5" NH Double-Male Adapter R/L x 1.5" NH male	\$90.00
H36-25NH-20NH	2.5" NH Double-Male Adapter R/L x 2" NH male	\$125.00
H36-25NH-25NH	2.5" NH Double-Male Adapter R/L x 2.5" NH male	\$60.00
H36-30NH-20NH	3" NH Double-Male Adapter R/L x 2" NH male	\$225.00
H36-30NH-25NH	3" NH Double-Male Adapter R/L x 2.5" NH male	\$160.00
H36-30NH-30NH	3" NH Double-Male Adapter R/L x 3" NH male	\$150.00
H36-35NH-25NH	3.5" NH Double-Male Adapter R/L x 2.5" NH male	\$225.00
H36-35NH-30NH	3.5" NH Double-Male Adapter R/L x 3" NH male	\$290.00
H36-35NH-35NH	3.5" NH Double-Male Adapter R/L x 3.5" NH male	\$245.00
H36-40NH-25NH	4" NH Double-Male Adapter R/L x 2.5" NH male	\$250.00
H36-40NH-30NH	4" NH Double-Male Adapter R/L x 3" NH male	\$340.00
H36-40NH-35NH	4" NH Double-Male Adapter R/L x 3.5" NH male	\$285.00
H36-40NH-40NH	4" NH Double-Male Adapter R/L x 4" NH male	\$270.00
H36-45NH-25NH	4.5" NH Double-Male Adapter R/L x 2.5" NH male	\$280.00
H36-45NH-30NH	4.5" NH Double-Male Adapter R/L x 3" NH male	\$330.00
H36-45NH-35NH	4.5" NH Double-Male Adapter R/L x 3.5" NH male	\$315.00
H36-45NH-40NH	4.5" NH Double-Male Adapter R/L x 4" NH male	\$375.00
H36-45NH-45NH	4.5" NH Double-Male Adapter R/L x 4.5" NH male	\$295.00
H36-50NH-25NH	5" NH Double-Male Adapter R/L x 2.5" NH male	\$580.00
H36-50NH-30NH	5" NH Double-Male Adapter R/L x 3" NH male	\$755.00
H36-50NH-35NH	5" NH Double-Male Adapter R/L x 3.5" NH male	\$720.00
H36-50NH-40NH	5" NH Double-Male Adapter R/L x 4" NH male	\$385.00
H36-50NH-45NH	5" NH Double-Male Adapter R/L x 4.5" NH male	\$395.00
H36-50NH-50NH	5" NH Double-Male Adapter R/L x 5" NH male	\$325.00
H36-60NH-25NH	6" NH Double-Male Adapter R/L x 2.5" NH male	\$610.00
H36-60NH-30NH	6" NH Double-Male Adapter R/L x 3" NH male	\$610.00
H36-60NH-35NH	6" NH Double-Male Adapter R/L x 3.5" NH male	\$630.00



H36-60NH-40NH	6" NH Double-Male Adapter R/L x 4" NH male	\$480.00
H36-60NH-45NH	6" NH Double-Male Adapter R/L x 4.5" NH male	\$465.00
H36-60NH-50NH	6" NH Double-Male Adapter R/L x 5" NH male	\$385.00
H36-60NH-60NH	6" NH Double-Male Adapter R/L x 6" NH male	\$520.00



H37 - Female Rigid X Male Adapter - Rocker Lug



The Harrington Model H37 rigid female x male threaded adapter is offered in various sizes from GHT to 1" to 6" NH, NPT & NPSH threads or special threads, with a single row of rocker lugs. GHT adapters are included in this section. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Adapters have a maximum of 250 PSI working pressure. Laser etching available at No Charge.

H37-GHTM-GHT	Garden Hose Male Adapter x garden hose female rigid R/L	\$60.00
H37-GHTM-10NH	Garden Hose Male Adapter x 1" NH female rigid R/L	\$60.00
H37-GHTM-15NH	Garden Hose Male Adapter x 1.5" NH female rigid R/L	\$65.00
H37-GHTM-20NH	Garden Hose Male Adapter x 2" NH female rigid R/L	\$105.00
H37-GHTM-25NH	Garden Hose Male Adapter x 2.5" NH female rigid R/L	\$120.00
H37-10NHM-GHT	1" NH Male Adapter x garden hose female rigid R/L	\$95.00
H37-10NHM-10NH	1" NH Male Adapter x 1" NH female rigid R/L	\$55.00
H37-10NHM-15NH	1" NH Male Adapter x 1.5" NH female rigid R/L	\$75.00
H37-10NHM-20NH	1" NH Male Adapter x 2" NH female rigid R/L	\$95.00
H37-10NHM-25NH	1" NH Male Adapter x 2.5" NH female rigid R/L	\$115.00
H37-15NHM-GHT	1.5" NH Male Adapter x garden hose female rigid R/L	\$70.00
H37-15NHM-10NH	1.5" NH Male Adapter x 1" NH female rigid R/L	\$70.00
H37-15NHM-15NH	1.5" NH Male Adapter x 1.5" NH female rigid R/L	\$65.00
H37-15NHM-20NH	1.5" NH Male Adapter x 2" NH female rigid R/L	\$70.00
H37-15NHM-25NH	1.5" NH Male Adapter x 2.5" NH female rigid R/L	\$80.00
H37-15NPSHM-25NH	1.5" NPSH Male Adapter x 2.5" NH female rigid R/L	\$80.00
H37-15NHM-30NH	1.5" NH Male Adapter x 3" NH female rigid R/L	\$205.00
H37-15NHM-35NH	1.5" NH Male Adapter x 3.5" NH female rigid R/L	\$235.00
H37-20NHM-GHT	2" NH Male Adapter x garden hose female rigid R/L	\$95.00
H37-20NHM-10NH	2" NH Male Adapter x 1" NH female rigid R/L	\$100.00
H37-20NHM-15NH	2" NH Male Adapter x 1.5" NH female rigid R/L	\$65.00
H37-20NHM-20NH	2" NH Male Adapter x 2" NH female rigid R/L	\$95.00



H37-20NHM-25NH	2" NH Male Adapter x 2.5" NH female rigid R/L	\$80.00
H37-20NHM-30NH	2" NH Male Adapter x 3" NH female rigid R/L	\$225.00
H37-25NHM-GHT	2.5" NH Male Adapter x garden hose female rigid R/L	\$105.00
H37-25NHM-10NH	2.5" NH Male Adapter x 1" NH female rigid R/L	\$100.00
H37-25NHM-15NH	2.5" NH Male Adapter x 1.5" NH female rigid R/L	\$80.00
H37-25NHM-20NH	2.5" NH Male Adapter x 2" NH female rigid R/L	\$105.00
H37-25NHM-25NH	2.5" NH Male Adapter x 2.5" NH female rigid R/L	\$75.00
H37-25NHM-30NH	2.5" NH Male Adapter x 3" NH female rigid R/L	\$155.00
H37-25NHM-35NH	2.5" NH Male Adapter x 3.5" NH female rigid R/L	\$165.00
H37-25NHM-40NH	2.5" NH Male Adapter x 4" NH female rigid R/L	\$285.00
H37-25NHM-45NH	2.5" NH Male Adapter x 4.5" NH female rigid R/L	\$325.00
H37-25NHM-50NH	2.5" NH Male Adapter x 5" NH female rigid R/L	\$410.00
H37-25NHM-60NH	2.5" NH Male Adapter x 6" NH female rigid R/L	\$850.00
H37-30NHM-15NH	3" NH Male Adapter x 1.5" NH female rigid R/L	\$210.00
H37-30NHM-20NH	3" NH Male Adapter x 2" NH female rigid R/L	\$215.00
H37-30NHM-25NH	3" NH Male Adapter x 2.5" NH female rigid R/L	\$135.00
H37-30NHM-30NH	3" NH Male Adapter x 3" NH female rigid R/L	\$150.00
H37-30NHM-35NH	3" NH Male Adapter x 3.5" NH female rigid R/L	\$335.00
H37-30NHM-40NH	3" NH Male Adapter x 4" NH female rigid R/L	\$360.00
H37-30NHM-45NH	3" NH Male Adapter x 4.5" NH female rigid R/L	\$410.00
H37-30NHM-50NH	3" NH Male Adapter x 5" NH female rigid R/L	\$410.00
H37-30NHM-60NH	3" NH Male Adapter x 6" NH female rigid R/L	\$810.00
H37-35NHM-25NH	3.5" NH Male Adapter x 2.5" NH female rigid R/L	\$160.00
H37-35NHM-30NH	3.5" NH Male Adapter x 3" NH female rigid R/L	\$330.00
H37-35NHM-35NH	3.5" NH Male Adapter x 3.5" NH female rigid R/L	\$285.00
H37-35NHM-40NH	3.5" NH Male Adapter x 4" NH female rigid R/L	\$360.00
H37-35NHM-45NH	3.5" NH Male Adapter x 4.5" NH female rigid R/L	\$395.00
H37-35NHM-50NH	3.5" NH Male Adapter x 5" NH female rigid R/L	\$440.00
H37-35NHM-60NH	3.5" NH Male Adapter x 6" NH female rigid R/L	\$825.00
H37-40NHM-25NH	4" NH Male Adapter x 2.5" NH female rigid R/L	\$290.00
H37-40NHM-30NH	4" NH Male Adapter x 3" NH female rigid R/L	\$355.00
H37-40NHM-35NH	4" NH Male Adapter x 3.5" NH female rigid R/L	\$350.00
H37-40NHM-40NH	4" NH Male Adapter x 4" NH female rigid R/L	\$325.00
H37-40NHM-45NH	4" NH Male Adapter x 4.5" NH female rigid R/L	\$280.00
H37-40NHM-50NH	4" NH Male Adapter x 5" NH female rigid R/L	\$405.00
H37-40NHM-60NH	4" NH Male Adapter x 6" NH female rigid R/L	\$565.00
H37-45NHM-25NH	4.5" NH Male Adapter x 2.5" NH female rigid R/L	\$300.00
H37-45NHM-30NH	4.5" NH Male Adapter x 3" NH female rigid R/L	\$430.00
H37-45NHM-35NH	4.5" NH Male Adapter x 3.5" NH female rigid R/L	\$400.00
H37-45NHM-40NH	4.5" NH Male Adapter x 4" NH female rigid R/L	\$420.00
H37-45NHM-45NH	4.5" NH Male Adapter x 4.5" NH female rigid R/L	\$405.00
H37-45NHM-50NH	4.5" NH Male Adapter x 5" NH female rigid R/L	\$480.00
H37-45NHM-60NH	4.5" NH Male Adapter x 6" NH female rigid R/L	\$605.00
H37-50NHM-25NH	5" NH Male Adapter x 2.5" NH female rigid R/L	\$350.00
H37-50NHM-30NH	5" NH Male Adapter x 3" NH female rigid R/L	\$475.00
H37-50NHM-35NH	5" NH Male Adapter x 3.5" NH female rigid R/L	\$415.00



H37-50NHM-40NH	5" NH Male Adapter x 4" NH female rigid R/L	\$470.00
H37-50NHM-45NH	5" NH Male Adapter x 4.5" NH female rigid R/L	\$505.00
H37-50NHM-50NH	5" NH Male Adapter x 5" NH female rigid R/L	\$460.00
H37-50NHM-60NH	5" NH Male Adapter x 6" NH female rigid R/L	\$575.00
H37-60NHM-25NH	6" NH Male Adapter x 2.5" NH female rigid R/L	\$500.00
H37-60NHM-30NH	6" NH Male Adapter x 3" NH female rigid R/L	\$510.00
H37-60NHM-35NH	6" NH Male Adapter x 3.5" NH female rigid R/L	\$570.00
H37-60NHM-40NH	6" NH Male Adapter x 4" NH female rigid R/L	\$615.00
H37-60NHM-45NH	6" NH Male Adapter x 4.5" NH female rigid R/L	\$625.00
H37-60NHM-50NH	6" NH Male Adapter x 5" NH female rigid R/L	\$695.00
H37-60NHM-60NH	6" NH Male Adapter x 6" NH female rigid R/L	\$770.00



H53 - Female Swivel Rocker Lug x Female Rigid Adapter



The Harrington Model H53 rigid female x female swivel threaded adapter is offered in various sizes from 1.5" to 6" NH, NPSH threads, and NPT on rigid female swivels or special threads, with dual rows of rocker lugs. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Adapters have a maximum of 250 PSI working pressure. Laser etching available at No Charge.

H53-15NH-15NH	1.5" NH FS R/L Adapter x 1.5" NH female rigid R/L	\$95.00
H53-15NPSH-15NPSH	1.5" NPSH FS R/L Adapter x 1.5" NPSH female rigid R/L	\$95.00
H53-15NH-20NH	1.5" NH FS R/L Adapter x 2" NH female rigid R/L	\$115.00
H53-15NH-25NH	1.5" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$140.00
H53-20NH-15NH	2" NH FS R/L Adapter x 1.5" NH female rigid R/L	\$125.00
H53-20NH-20NH	2" NH FS R/L Adapter x 2" NH female rigid R/L	\$125.00
H53-20NH-25NH	2" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$190.00
H53-25NH-15NH	2.5" NH FS R/L Adapter x 1.5" NH female rigid R/L	\$165.00
H53-25NH-20NH	2.5" NH FS R/L Adapter x 2" NH female rigid R/L	\$195.00
H53-25NH-25NH	2.5" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$205.00
H53-25NH-30NH	2.5" NH FS R/L Adapter x 3" NH female rigid R/L	\$275.00
H53-25NH-35NH	2.5" NH FS R/L Adapter x 3.5" NH female rigid R/L	\$330.00
H53-25NH-40NH	2.5" NH FS R/L Adapter x 4" NH female rigid R/L	\$300.00
H53-25NH-45NH	2.5" NH FS R/L Adapter x 4.5" NH female rigid R/L	\$425.00



H53-25NH-50NH	2.5" NH FS R/L Adapter x 5" NH female rigid R/L	\$740.00
H53-25NH-60NH	2.5" NH FS R/L Adapter x 6" NH female rigid R/L	\$875.00
H53-30NH-25NH	3" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$280.00
H53-30NH-30NH	3" NH FS R/L Adapter x 3" NH female rigid R/L	\$260.00
H53-30NH-35NH	3" NH FS R/L Adapter x 3.5" NH female rigid R/L	\$405.00
H53-30NH-40NH	3" NH FS R/L Adapter x 4" NH female rigid R/L	\$520.00
H53-30NH-45NH	3" NH FS R/L Adapter x 4.5" NH female rigid R/L	\$560.00
H53-30NH-50NH	3" NH FS R/L Adapter x 5" NH female rigid R/L	\$695.00
H53-30NH-60NH	3" NH FS R/L Adapter x 6" NH female rigid R/L	\$830.00
H53-35NH-25NH	3.5" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$330.00
H53-35NH-30NH	3.5" NH FS R/L Adapter x 3" NH female rigid R/L	\$405.00
H53-35NH-35NH	3.5" NH FS R/L Adapter x 3.5" NH female rigid R/L	\$465.00
H53-35NH-40NH	3.5" NH FS R/L Adapter x 4" NH female rigid R/L	\$645.00
H53-35NH-45NH	3.5" NH FS R/L Adapter x 4.5" NH female rigid R/L	\$735.00
H53-35NH-50NH	3.5" NH FS R/L Adapter x 5" NH female rigid R/L	\$770.00
H53-35NH-60NH	3.5" NH FS R/L Adapter x 6" NH female rigid R/L	\$1,075.00
H53-40NH-25NH	4" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$340.00
H53-40NH-30NH	4" NH FS R/L Adapter x 3" NH female rigid R/L	\$460.00
H53-40NH-35NH	4" NH FS R/L Adapter x 3.5" NH female rigid R/L	\$650.00
H53-40NH-40NH	4" NH FS R/L Adapter x 4" NH female rigid R/L	\$565.00
H53-40NH-45NH	4" NH FS R/L Adapter x 4.5" NH female rigid R/L	\$665.00
H53-40NH-50NH	4" NH FS R/L Adapter x 5" NH female rigid R/L	\$885.00
H53-40NH-60NH	4" NH FS R/L Adapter x 6" NH female rigid R/L	\$895.00
H53-45NH-25NH	4.5" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$470.00
H53-45NH-30NH	4.5" NH FS R/L Adapter x 3" NH female rigid R/L	\$540.00
H53-45NH-35NH	4.5" NH FS R/L Adapter x 3.5" NH female rigid R/L	\$695.00
H53-45NH-40NH	4.5" NH FS R/L Adapter x 4" NH female rigid R/L	\$595.00
H53-45NH-45NH	4.5" NH FS R/L Adapter x 4.5" NH female rigid R/L	\$610.00
H53-45NH-50NH	4.5" NH FS R/L Adapter x 5" NH female rigid R/L	\$855.00
H53-45NH-60NH	4.5" NH FS R/L Adapter x 6" NH female rigid R/L	\$1,005.00
H53-50NH-25NH	5" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$705.00
H53-50NH-30NH	5" NH FS R/L Adapter x 3" NH female rigid R/L	\$600.00
H53-50NH-35NH	5" NH FS R/L Adapter x 3.5" NH female rigid R/L	\$705.00
H53-50NH-40NH	5" NH FS R/L Adapter x 4" NH female rigid R/L	\$765.00
H53-50NH-45NH	5" NH FS R/L Adapter x 4.5" NH female rigid R/L	\$850.00
H53-50NH-50NH	5" NH FS R/L Adapter x 5" NH female rigid R/L	\$950.00
H53-50NH-60NH	5" NH FS R/L Adapter x 6" NH female rigid R/L	\$935.00
H53-60NH-25NH	6" NH FS R/L Adapter x 2.5" NH female rigid R/L	\$955.00
H53-60NH-30NH	6" NH FS R/L Adapter x 3" NH female rigid R/L	\$1,020.00
H53-60NH-35NH	6" NH FS R/L Adapter x 3.5" NH female rigid R/L	\$1,035.00
H53-60NH-40NH	6" NH FS R/L Adapter x 4" NH female rigid R/L	\$855.00
H53-60NH-45NH	6" NH FS R/L Adapter x 4.5" NH female rigid R/L	\$1,005.00
H53-60NH-50NH	6" NH FS R/L Adapter x 5" NH female rigid R/L	\$935.00
H53-60NH-60NH	6" NH FS R/L Adapter x 6" NH female rigid R/L	\$1,035.00



H53L - FS LH x Female Rigid Rocker Lug



The Harrington Model H53L rigid female x female swivel threaded adapter is offered in various sizes from 1.5" to 6" NH, NPSH, NPT or special threads, with rocker lugs on rigid female & LHs on swivel female. All threaded adapters are hard coated anodized of Type #6061-T6 lightweight aluminum. All adapters 3.5" and under in size utilize stainless-steel ball bearings and 4" and larger sizes have aluminum roller bearings (no plastic). Adapters have a maximum of 250 PSI working pressure. Laser etching available at No Charge.

H53L-25NH-15NH	2.5" NH FS LH x 1.5" NH female rigid R/L	\$175.00
H53L-25NH-20NH	2.5" NH FS LH x 2" NH female rigid R/L	\$200.00
H53L-25NH-25NH	2.5" NH FS LH x 2.5" NH female rigid R/L	\$215.00
H53L-25NH-30NH	2.5" NH FS LH x 3" NH female rigid R/L	\$280.00
H53L-25NH-35NH	2.5" NH FS LH x 3.5" NH female rigid R/L	\$350.00
H53L-25NH-40NH	2.5" NH FS LH x 4" NH female rigid R/L	\$310.00
H53L-25NH-45NH	2.5" NH FS LH x 4.5" NH female rigid R/L	\$450.00
H53L-25NH-50NH	2.5" NH FS LH x 5" NH female rigid R/L	\$800.00
H53L-25NH-60NH	2.5" NH FS LH x 6" NH female rigid R/L	\$890.00
H53L-30NH-25NH	3" NH FS LH x 2.5" NH female rigid R/L	\$290.00
H53L-30NH-30NH	3" NH FS LH x 3" NH female rigid R/L	\$265.00
H53L-30NH-35NH	3" NH FS LH x 3.5" NH female rigid R/L	\$430.00
H53L-30NH-40NH	3" NH FS LH x 4" NH female rigid R/L	\$555.00
H53L-30NH-45NH	3" NH FS LH x 4.5" NH female rigid R/L	\$600.00
H53L-30NH-50NH	3" NH FS LH x 5" NH female rigid R/L	\$585.00
H53L-30NH-60NH	3" NH FS LH x 6" NH female rigid R/L	\$920.00
H53L-35NH-25NH	3.5" NH FS LH x 2.5" NH female rigid R/L	\$350.00
H53L-35NH-30NH	3.5" NH FS LH x 3" NH female rigid R/L	\$415.00
H53L-35NH-35NH	3.5" NH FS LH x 3.5" NH female rigid R/L	\$500.00
H53L-35NH-40NH	3.5" NH FS LH x 4" NH female rigid R/L	\$710.00
H53L-35NH-45NH	3.5" NH FS LH x 4.5" NH female rigid R/L	\$805.00
H53L-35NH-50NH	3.5" NH FS LH x 5" NH female rigid R/L	\$885.00
H53L-35NH-60NH	3.5" NH FS LH x 6" NH female rigid R/L	\$1,195.00
H53L-40NH-25NH	4" NH FS LH x 2.5" NH female rigid R/L	\$355.00
H53L-40NH-30NH	4" NH FS LH x 3" NH female rigid R/L	\$495.00
H53L-40NH-35NH	4" NH FS LH x 3.5" NH female rigid R/L	\$695.00
H53L-40NH-40NH	4" NH FS LH x 4" NH female rigid R/L	\$610.00
H53L-40NH-45NH	4" NH FS LH x 4.5" NH female rigid R/L	\$730.00
H53L-40NH-50NH	4" NH FS LH x 5" NH female rigid R/L	\$955.00
H53L-40NH-60NH	4" NH FS LH x 6" NH female rigid R/L	\$995.00
H53L-45NH-25NH	4.5" NH FS LH x 2.5" NH female rigid R/L	\$495.00
H53L-45NH-30NH	4.5" NH FS LH x 3" NH female rigid R/L	\$565.00
H53L-45NH-35NH	4.5" NH FS LH x 3.5" NH female rigid R/L	\$740.00
H53L-45NH-40NH	4.5" NH FS LH x 4" NH female rigid R/L	\$625.00
H53L-45NH-45NH	4.5" NH FS LH x 4.5" NH female rigid R/L	\$645.00



H53L-45NH-50NH	4.5" NH FS LH x 5" NH female rigid R/L	\$885.00
H53L-45NH-60NH	4.5" NH FS LH x 6" NH female rigid R/L	\$990.00
H53L-50NH-25NH	5" NH FS LH x 2.5" NH female rigid R/L	\$615.00
H53L-50NH-30NH	5" NH FS LH x 3" NH female rigid R/L	\$630.00
H53L-50NH-35NH	5" NH FS LH x 3.5" NH female rigid R/L	\$750.00
H53L-50NH-40NH	5" NH FS LH x 4" NH female rigid R/L	\$815.00
H53L-50NH-45NH	5" NH FS LH x 4.5" NH female rigid R/L	\$885.00
H53L-50NH-50NH	5" NH FS LH x 5" NH female rigid R/L	\$990.00
H53L-50NH-60NH	5" NH FS LH x 6" NH female rigid R/L	\$970.00
H53L-60NH-25NH	6" NH FS LH x 2.5" NH female rigid R/L	\$975.00
H53L-60NH-30NH	6" NH FS LH x 3" NH female rigid R/L	\$1,075.00
H53L-60NH-35NH	6" NH FS LH x 3.5" NH female rigid R/L	\$1,085.00
H53L-60NH-40NH	6" NH FS LH x 4" NH female rigid R/L	\$915.00
H53L-60NH-45NH	6" NH FS LH x 4.5" NH female rigid R/L	\$1,060.00
H53L-60NH-50NH	6" NH FS LH x 5" NH female rigid R/L	\$955.00
H53L-60NH-60NH	6" NH FS LH x 6" NH female rigid R/L	\$1,060.00



SPECIAL THREADS: available on request. 1" to 6" = \$20.00



H54 - Male x Female Swivel Adapter - Rocker Lug



The Harrington Model H54 female swivel x male threaded adapter is offered in various sizes from 1.5" to 6" NH, NPSH, NPT or special threads, with rocker lugs female swivel & rocker lug on male. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. All adapters 3.5" and under in size utilize stainless steel ball bearings and 4" and larger sizes use aluminum roller bearings (no plastic). Adapters have a maximum of 250 PSI working pressure. Laser etching available at No Charge.

H54-15NHM-15NH	1.5" NH Male R/L Adapter x 1.5" NH FS R/L	\$95.00
H54-15NHM-20NH	1.5" NH Male R/L Adapter x 2" NH FS R/L	\$110.00
H54-15NHM-25NH	1.5" NH Male R/L Adapter x 2.5" NH FS R/L	\$120.00
H54-20NHM-15NH	2" NH Male R/L Adapter x 1.5" NH FS R/L	\$110.00
H54-20NHM-20NH	2" NH Male R/L Adapter x 2" NH FS R/L	\$115.00
H54-20NHM-25NH	2" NH Male R/L Adapter x 2.5" NH FS R/L	\$190.00
H54-25NHM-15NH	2.5" NH Male R/L Adapter x 1.5" NH FS R/L	\$130.00
H54-25NHM-20NH	2.5" NH Male R/L Adapter x 2" NH FS R/L	\$185.00
H54-25NHM-25NH	2.5" NH Male R/L Adapter x 2.5" NH FS R/L	\$195.00
H54-25NHM-30NH	2.5" NH Male R/L Adapter x 3" NH FS R/L	\$275.00
H54-25NHM-35NH	2.5" NH Male R/L Adapter x 3.5" NH FS R/L	\$335.00
H54-25NHM-40NH	2.5" NH Male R/L Adapter x 4" NH FS R/L	\$480.00
H54-25NHM-45NH	2.5" NH Male R/L Adapter x 4.5" NH FS R/L	\$480.00
H54-25NHM-50NH	2.5" NH Male R/L Adapter x 5" NH FS R/L	\$605.00
H54-25NHM-60NH	2.5" NH Male R/L Adapter x 6" NH FS R/L	\$1,005.00
H54-30NHM-25NH	3" NH Male R/L Adapter x 2.5" NH FS R/L	\$270.00
H54-30NHM-30NH	3" NH Male R/L Adapter x 3" NH FS R/L	\$250.00
H54-30NHM-35NH	3" NH Male R/L Adapter x 3.5" NH FS R/L	\$405.00
H54-30NHM-40NH	3" NH Male R/L Adapter x 4" NH FS R/L	\$525.00
H54-30NHM-45NH	3" NH Male R/L Adapter x 4.5" NH FS R/L	\$495.00
H54-30NHM-50NH	3" NH Male R/L Adapter x 5" NH FS R/L	\$615.00
H54-30NHM-60NH	3" NH Male R/L Adapter x 6" NH FS R/L	\$1,125.00
H54-35NHM-25NH	3.5" NH Male R/L Adapter x 2.5" NH FS R/L	\$330.00
H54-35NHM-30NH	3.5" NH Male R/L Adapter x 3" NH FS R/L	\$405.00
H54-35NHM-35NH	3.5" NH Male R/L Adapter x 3.5" NH FS R/L	\$475.00
H54-35NHM-40NH	3.5" NH Male R/L Adapter x 4" NH FS R/L	\$610.00
H54-35NHM-45NH	3.5" NH Male R/L Adapter x 4.5" NH FS R/L	\$720.00
H54-35NHM-50NH	3.5" NH Male R/L Adapter x 5" NH FS R/L	\$735.00
H54-35NHM-60NH	3.5" NH Male R/L Adapter x 6" NH FS R/L	\$1,085.00
H54-40NHM-25NH	4" NH Male R/L Adapter x 2.5" NH FS R/L	\$295.00
H54-40NHM-30NH	4" NH Male R/L Adapter x 3" NH FS R/L	\$525.00
H54-40NHM-35NH	4" NH Male R/L Adapter x 3.5" NH FS R/L	\$675.00
H54-40NHM-40NH	4" NH Male R/L Adapter x 4" NH FS R/L	\$575.00
H54-40NHM-45NH	4" NH Male R/L Adapter x 4.5" NH FS R/L	\$610.00
H54-40NHM-50NH	4" NH Male R/L Adapter x 5" NH FS R/L	\$805.00
H54-40NHM-60NH	4" NH Male R/L Adapter x 6" NH FS R/L	\$875.00



H54-45NHM-25NH	4.5" NH Male R/L Adapter x 2.5" NH FS R/L	\$430.00
H54-45NHM-30NH	4.5" NH Male R/L Adapter x 3" NH FS R/L	\$580.00
H54-45NHM-35NH	4.5" NH Male R/L Adapter x 3.5" NH FS R/L	\$770.00
H54-45NHM-40NH	4.5" NH Male R/L Adapter x 4" NH FS R/L	\$680.00
H54-45NHM-45NH	4.5" NH Male R/L Adapter x 4.5" NH FS R/L	\$625.00
H54-45NHM-50NH	4.5" NH Male R/L Adapter x 5" NH FS R/L	\$855.00
H54-45NHM-60NH	4.5" NH Male R/L Adapter x 6" NH FS R/L	\$1,025.00
H54-50NHM-25NH	5" NH Male R/L Adapter x 2.5" NH FS R/L	\$775.00
H54-50NHM-30NH	5" NH Male R/L Adapter x 3" NH FS R/L	\$730.00
H54-50NHM-35NH	5" NH Male R/L Adapter x 3.5" NH FS R/L	\$850.00
H54-50NHM-40NH	5" NH Male R/L Adapter x 4" NH FS R/L	\$920.00
H54-50NHM-45NH	5" NH Male R/L Adapter x 4.5" NH FS R/L	\$885.00
H54-50NHM-50NH	5" NH Male R/L Adapter x 5" NH FS R/L	\$995.00
H54-50NHM-60NH	5" NH Male R/L Adapter x 6" NH FS R/L	\$955.00
H54-60NHM-25NH	6" NH Male R/L Adapter x 2.5" NH FS R/L	\$940.00
H54-60NHM-30NH	6" NH Male R/L Adapter x 3" NH FS R/L	\$890.00
H54-60NHM-35NH	6" NH Male R/L Adapter x 3.5" NH FS R/L	\$1,155.00
H54-60NHM-40NH	6" NH Male R/L Adapter x 4" NH FS R/L	\$935.00
H54-60NHM-45NH	6" NH Male R/L Adapter x 4.5" NH FS R/L	\$1,055.00
H54-60NHM-50NH	6" NH Male R/L Adapter x 5" NH FS R/L	\$955.00
H54-60NHM-60NH	6" NH Male R/L Adapter x 6" NH FS R/L	\$1,065.00



H54L - Male R/L x FS LH Adapter

The Harrington Model H54L male threaded x female swivel adapter is offered in various sizes from 1.5" to 6" NH, NPSH, NPT or special threads, with LHs female swivel & rocker lug on male. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. All adapters 3.5" and under in size utilize stainless-steel ball bearings and 4" and larger sizes use aluminum roller bearings (no plastic). Adapters have a maximum of 250 PSI working pressure. Laser lettering etching available at No Charge.



H54L-25NHM-25NH	2.5" NH Male R/L Adapter x 2.5" NH FS LH	\$230.00
H54L-25NHM-30NH	2.5" NH Male R/L Adapter x 3" NH FS LH	\$300.00
H54L-25NHM-35NH	2.5" NH Male R/L Adapter x 3.5" NH FS LH	\$365.00
H54L-25NHM-40NH	2.5" NH Male R/L Adapter x 4" NH FS LH	\$425.00
H54L-25NHM-45NH	2.5" NH Male R/L Adapter x 4.5" NH FS LH	\$490.00



H54L-25NHM-50NH	2.5" NH Male R/L Adapter x 5" NH FS LH	\$750.00
H54L-25NHM-60NH	2.5" NH Male R/L Adapter x 6" NH FS LH	\$1,025.00
H54L-30NHM-25NH	3" NH Male R/L Adapter x 2.5" NH FS LH	\$300.00
H54L-30NHM-30NH	3" NH Male R/L Adapter x 3" NH FS LH	\$280.00
H54L-30NHM-35NH	3" NH Male R/L Adapter x 3.5" NH FS LH	\$440.00
H54L-30NHM-40NH	3" NH Male R/L Adapter x 4" NH FS LH	\$745.00
H54L-30NHM-45NH	3" NH Male R/L Adapter x 4.5" NH FS LH	\$585.00
H54L-30NHM-50NH	3" NH Male R/L Adapter x 5" NH FS LH	\$645.00
H54L-30NHM-60NH	3" NH Male R/L Adapter x 6" NH FS LH	\$1,110.00
H54L-35NHM-25NH	3.5" NH Male R/L Adapter x 2.5" NH FS LH	\$360.00
H54L-35NHM-30NH	3.5" NH Male R/L Adapter x 3" NH FS LH	\$435.00
H54L-35NHM-35NH	3.5" NH Male R/L Adapter x 3.5" NH FS LH	\$510.00
H54L-35NHM-40NH	3.5" NH Male R/L Adapter x 4" NH FS LH	\$700.00
H54L-35NHM-45NH	3.5" NH Male R/L Adapter x 4.5" NH FS LH	\$770.00
H54L-35NHM-50NH	3.5" NH Male R/L Adapter x 5" NH FS LH	\$755.00
H54L-35NHM-60NH	3.5" NH Male R/L Adapter x 6" NH FS LH	\$1,110.00
H54L-40NHM-25NH	4" NH Male R/L Adapter x 2.5" NH FS LH	\$360.00
H54L-40NHM-30NH	4" NH Male R/L Adapter x 3" NH FS LH	\$565.00
H54L-40NHM-35NH	4" NH Male R/L Adapter x 3.5" NH FS LH	\$710.00
H54L-40NHM-40NH	4" NH Male R/L Adapter x 4" NH FS LH	\$615.00
H54L-40NHM-45NH	4" NH Male R/L Adapter x 4.5" NH FS LH	\$640.00
H54L-40NHM-50NH	4" NH Male R/L Adapter x 5" NH FS LH	\$820.00
H54L-40NHM-60NH	4" NH Male R/L Adapter x 6" NH FS LH	\$925.00
H54L-45NHM-25NH	4.5" NH Male R/L Adapter x 2.5" NH FS LH	\$460.00
H54L-45NHM-30NH	4.5" NH Male R/L Adapter x 3" NH FS LH	\$605.00
H54L-45NHM-35NH	4.5" NH Male R/L Adapter x 3.5" NH FS LH	\$805.00
H54L-45NHM-40NH	4.5" NH Male R/L Adapter x 4" NH FS LH	\$715.00
H54L-45NHM-45NH	4.5" NH Male R/L Adapter x 4.5" NH FS LH	\$715.00
H54L-45NHM-50NH	4.5" NH Male R/L Adapter x 5" NH FS LH	\$915.00
H54L-45NHM-60NH	4.5" NH Male R/L Adapter x 6" NH FS LH	\$1,105.00
H54L-50NHM-25NH	5" NH Male R/L Adapter x 2.5" NH FS LH	\$745.00
H54L-50NHM-30NH	5" NH Male R/L Adapter x 3" NH FS LH	\$750.00
H54L-50NHM-35NH	5" NH Male R/L Adapter x 3.5" NH FS LH	\$880.00
H54L-50NHM-40NH	5" NH Male R/L Adapter x 4" NH FS LH	\$950.00
H54L-50NHM-45NH	5" NH Male R/L Adapter x 4.5" NH FS LH	\$920.00
H54L-50NHM-50NH	5" NH Male R/L Adapter x 5" NH FS LH	\$1,025.00
H54L-50NHM-60NH	5" NH Male R/L Adapter x 6" NH FS LH	\$1,025.00
H54L-60NHM-25NH	6" NH Male R/L Adapter x 2.5" NH FS LH	\$955.00
H54L-60NHM-30NH	6" NH Male R/L Adapter x 3" NH FS LH	\$900.00
H54L-60NHM-35NH	6" NH Male R/L Adapter x 3.5" NH FS LH	\$1,180.00
H54L-60NHM-40NH	6" NH Male R/L Adapter x 4" NH FS LH	\$940.00
H54L-60NHM-45NH	6" NH Male R/L Adapter x 4.5" NH FS LH	\$1,080.00
H54L-60NHM-50NH	6" NH Male R/L Adapter x 5" NH FS LH	\$1,030.00
H54L-60NHM-60NH	6" NH Male R/L Adapter x 6" NH FS LH	\$1,080.00



H56L - NH Male x Female Rigid LH Adapter



The Harrington Model H56L rigid female with LHs x male threaded adapter is offered in various sizes from 2.5" to 6" NH, NPSH, NPT or special threads. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Adapters have a maximum of 250 PSI working pressure. Laser etching available at No charge.

H56L-25NHM-25NH	2.5" NH Male Adapter x 2.5" NH female rigid LH	\$230.00
H56L-25NHM-30NH	2.5" NH Male Adapter x 3" NH female rigid LH	\$250.00
H56L-25NHM-35NH	2.5" NH Male Adapter x 3.5" NH female rigid LH	\$265.00
H56L-25NHM-40NH	2.5" NH Male Adapter x 4" NH female rigid LH	\$380.00
H56L-25NHM-45NH	2.5" NH Male Adapter x 4.5" NH female rigid LH	\$400.00
H56L-25NHM-50NH	2.5" NH Male Adapter x 5" NH female rigid LH	\$520.00
H56L-25NHM-60NH	2.5" NH Male Adapter x 6" NH female rigid LH	\$970.00
H56L-30NHM-25NH	3" NH Male Adapter x 2.5" NH female rigid LH	\$225.00
H56L-30NHM-30NH	3" NH Male Adapter x 3" NH female rigid LH	\$245.00
H56L-30NHM-35NH	3" NH Male Adapter x 3.5" NH female rigid LH	\$420.00
H56L-30NHM-40NH	3" NH Male Adapter x 4" NH female rigid LH	\$460.00
H56L-30NHM-45NH	3" NH Male Adapter x 4.5" NH female rigid LH	\$505.00
H56L-30NHM-50NH	3" NH Male Adapter x 5" NH female rigid LH	\$670.00
H56L-30NHM-60NH	3" NH Male Adapter x 6" NH female rigid LH	\$915.00
H56L-35NHM-25NH	3.5" NH Male Adapter x 2.5" NH female rigid LH	\$260.00
H56L-35NHM-30NH	3.5" NH Male Adapter x 3" NH female rigid LH	\$430.00
H56L-35NHM-35NH	3.5" NH Male Adapter x 3.5" NH female rigid LH	\$395.00
H56L-35NHM-40NH	3.5" NH Male Adapter x 4" NH female rigid LH	\$460.00
H56L-35NHM-45NH	3.5" NH Male Adapter x 4.5" NH female rigid LH	\$730.00
H56L-35NHM-50NH	3.5" NH Male Adapter x 5" NH female rigid LH	\$540.00
H56L-35NHM-60NH	3.5" NH Male Adapter x 6" NH female rigid LH	\$890.00
H56L-40NHM-25NH	4" NH Male Adapter x 2.5" NH female rigid LH	\$390.00
H56L-40NHM-30NH	4" NH Male Adapter x 3" NH female rigid LH	\$425.00
H56L-40NHM-35NH	4" NH Male Adapter x 3.5" NH female rigid LH	\$475.00
H56L-40NHM-40NH	4" NH Male Adapter x 4" NH female rigid LH	\$430.00
H56L-40NHM-45NH	4" NH Male Adapter x 4.5" NH female rigid LH	\$465.00
H56L-40NHM-50NH	4" NH Male Adapter x 5" NH female rigid LH	\$485.00
H56L-40NHM-60NH	4" NH Male Adapter x 6" NH female rigid LH	\$655.00
H56L-45NHM-25NH	4.5" NH Male Adapter x 2.5" NH female rigid LH	\$425.00
H56L-45NHM-30NH	4.5" NH Male Adapter x 3" NH female rigid LH	\$525.00
H56L-45NHM-35NH	4.5" NH Male Adapter x 3.5" NH female rigid LH	\$530.00
H56L-45NHM-40NH	4.5" NH Male Adapter x 4" NH female rigid LH	\$525.00
H56L-45NHM-45NH	4.5" NH Male Adapter x 4.5" NH female rigid LH	\$505.00
H56L-45NHM-50NH	4.5" NH Male Adapter x 5" NH female rigid LH	\$565.00
H56L-45NHM-60NH	4.5" NH Male Adapter x 6" NH female rigid LH	\$700.00
H56L-50NHM-25NH	5" NH Male Adapter x 2.5" NH female rigid LH	\$625.00
H56L-50NHM-30NH	5" NH Male Adapter x 3" NH female rigid LH	\$575.00



H56L-50NHM-35NH	5" NH Male Adapter x 3.5" NH female rigid LH	\$520.00
H56L-50NHM-40NH	5" NH Male Adapter x 4" NH female rigid LH	\$570.00
H56L-50NHM-45NH	5" NH Male Adapter x 4.5" NH female rigid LH	\$610.00
H56L-50NHM-50NH	5" NH Male Adapter x 5" NH female rigid LH	\$700.00
H56L-50NHM-60NH	5" NH Male Adapter x 6" NH female rigid LH	\$795.00
H56L-60NHM-25NH	6" NH Male Adapter x 2.5" NH female rigid LH	\$765.00
H56L-60NHM-30NH	6" NH Male Adapter x 3" NH female rigid LH	\$750.00
H56L-60NHM-35NH	6" NH Male Adapter x 3.5" NH female rigid LH	\$710.00
H56L-60NHM-40NH	6" NH Male Adapter x 4" NH female rigid LH	\$710.00
H56L-60NHM-45NH	6" NH Male Adapter x 4.5" NH female rigid LH	\$730.00
H56L-60NHM-50NH	6" NH Male Adapter x 5" NH female rigid LH	\$820.00
H56L-60NHM-60NH	6" NH Male Adapter x 6" NH female rigid LH	\$885.00

H57L - Double-Female Swivel LH x Female Swivel LH Adapter



The Harrington Model H57L double-swivel female with dual LHs threaded adapter is offered in various sizes from 2.5" to 6" NH, NPSH or special threads. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. All adapters 3.5" and under in size utilize stainless-steel ball bearings and 4" and larger sizes have aluminum roller bearings (no plastic). Adapters have a maximum of 250 PSI working pressure. Laser etching available at No Charge.

H57L-25NH-25NH	2.5" NH Double-FS LH Adapter x 2.5" NH FS LH	\$185.00
H57L-30NH-25NH	3" NH Double-FS LH Adapter x 2.5" NH FS LH	\$290.00
H57L-30NH-30NH	3" NH Double-FS LH Adapter x 3" NH FS LH	\$270.00
H57L-35NH-25NH	3.5" NH Double-FS LH Adapter x 2.5" NH FS LH	\$410.00
H57L-35NH-30NH	3.5" NH Double-FS LH Adapter x 3" NH FS LH	\$460.00
H57L-35NH-35NH	3.5" NH Double-FS LH Adapter x 3.5" NH FS LH	\$440.00
H57L-40NH-25NH	4" NH Double-FS LH Adapter x 2.5" NH FS LH	\$440.00
H57L-40NH-30NH	4" NH Double-FS LH Adapter x 3" NH FS LH	\$525.00
H57L-40NH-35NH	4" NH Double-FS LH Adapter x 3.5" NH FS LH	\$575.00
H57L-40NH-40NH	4" NH Double-FS LH Adapter x 4" NH FS LH	\$470.00
H57L-45NH-25NH	4.5" NH Double-FS LH Adapter x 2.5" NH FS LH	\$395.00
H57L-45NH-30NH	4.5" NH Double-FS LH Adapter x 3" NH FS LH	\$535.00
H57L-45NH-35NH	4.5" NH Double-FS LH Adapter x 3.5" NH FS LH	\$635.00
H57L-45NH-40NH	4.5" NH Double-FS LH Adapter x 4" NH FS LH	\$620.00
H57L-45NH-45NH	4.5" NH Double-FS LH Adapter x 4.5" NH FS LH	\$575.00
H57L-50NH-25NH	5" NH Double-FS LH Adapter x 2.5" NH FS LH	\$570.00
H57L-50NH-30NH	5" NH Double-FS LH Adapter x 3" NH FS LH	\$575.00
H57L-50NH-35NH	5" NH Double-FS LH Adapter x 3.5" NH FS LH	\$640.00
H57L-50NH-40NH	5" NH Double-FS LH Adapter x 4" NH FS LH	\$565.00



H57L-50NH-45NH	5" NH Double-FS LH Adapter x 4.5" NH FS LH	\$615.00
H57L-50NH-50NH	5" NH Double-FS LH Adapter x 5" NH FS LH	\$725.00
H57L-60NH-25NH	6" NH Double-FS LH Adapter x 2.5" NH FS LH	\$815.00
H57L-60NH-30NH	6" NH Double-FS LH Adapter x 3" NH FS LH	\$760.00
H57L-60NH-35NH	6" NH Double-FS LH Adapter x 3.5" NH FS LH	\$800.00
H57L-60NH-40NH	6" NH Double-FS LH Adapter x 4" NH FS LH	\$715.00
H57L-60NH-45NH	6" NH Double-FS LH Adapter x 4.5" NH FS LH	\$730.00
H57L-60NH-50NH	6" NH Double-FS LH Adapter x 5" NH FS LH	\$810.00
H57L-60NH-60NH	6" NH Double-FS LH Adapter x 6" NH FS LH	\$825.00

SPECIAL THREADS: available on request. 1" to 6" = \$20.00



HTBC - Female Threaded Blind Caps

The Harrington Model HTBC and HTP threaded female blind cap & male plugs are offered in various sizes from 1" to 6" NH & NPSH threads or special threads, with rocker lugs or LHs. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum. Caps and plugs shall include a chain. Optional brass bleeder valve available. Laser etching available at No Charge.



HTBC-10NH	1" NH Female Cap/Chain	\$110.00
HTBC-15NH	1.5" NH Female Cap/Chain	\$90.00
HTBC-15NH-PC	1.5" NH Female Cap .250" Bleeder	\$210.00
HTBC-15-xxx	1.5" Special Thread Female Cap/Chain	\$115.00
HTBC-15NPSH	1.5" NPSH Female Cap/Chain	\$90.00
HTBC-20NH	2" NH Female Cap/Chain	\$125.00
HTBC-25NH	2.5" NH Female Cap/Chain	\$105.00
HTBC-25NHLH	2.5" NH Female LH Cap/Chain	\$165.00
HTBC-25NPSH	2.5" NPSH Female Cap/Chain	\$105.00
HTBC-25NH-PC	2.5" NH Female .250" Bleeder	\$225.00
HTBC-25-xxx	2.5" Special Thread Female Cap/Chain	\$135.00
HTBC-25-xxx-PC	2.5" special thread Female Cap .250" Bleeder	\$250.00
HTBC-30NH	3" NH Female Cap/Chain	\$255.00
HTBC-30NHLH	3" NH Female LH Cap/Chain	\$305.00
HTBC-35NH	3.5" NH Female Cap/Chain	\$330.00
HTBC-35NHLH	3.5" NH Female LH Cap/Chain	\$395.00
HTBC-40NH	4" NH Female Cap/Chain	\$370.00
HTBC-40NHLH	4" NH Female LH Cap/Chain	\$440.00
HTBC-45NH	4.5" NH Female Cap/Chain	\$390.00
HTBC-45NHLH	4.5" NH Female LH Cap/Chain	\$460.00
HTBC-50NH	5" NH Female Cap/Chain	\$440.00
HTBC-50NHLH	5" NH Female LH Cap/Chain	\$480.00
HTBC-60NH	6" NH Female Cap/Chain	\$500.00
HTBC-60NHLH	6" NH Female LH Cap/Chain	\$530.00

HTP - Male Threaded Plugs

HTP-10NH	1" NH Male Plug/Chain	\$110.00
HTP-15NH	1.5" NH Male Plug/Chain	\$55.00
HTP-15NPSH	1.5" NPSH Male Plug/Chain	\$55.00
HTP-15-xxx	1.5" Special Thread Male Plug/Chain	\$125.00
HTP-20NH	2" NH Male Plug/Chain	\$140.00
HTP-25NH	2.5" NH Male Plug/Chain	\$95.00
HTP-25-xxx	2.5" Special Thread Male Plug/Chain	\$190.00
HTP-30NH	3" NH Male Plug/Chain	\$185.00
HTP-35NH	3.5" NH Male Plug/Chain	\$200.00
HTP-40NH	4" NH Male Plug/Chain	\$280.00
HTP-45NH	4.5" NH Male Plug/Chain	\$345.00
HTP-50NH	5" NH Male Plug/Chain	\$325.00
HTP-60NH	6" NH Male Plug/Chain	\$445.00



HSH - Suction Hose - with Male R/L x Female R/L or LH Threaded Cplgs

The Harrington Model HSH 'Flex-Lite' PVC hard suction hose sizes from 1.5" to 6" in diameter and custom lengths up to 20' long. Available in NH or NPSH female swivel with standard or optional folding LHs and rocker lug couplings on male end. MEETS OR EXCEEDS NFPA 1961 STANDARDS.



Hose specification Material: Rigid PVC helical & accordion-type rings continuously encapsulated with soft PVC clear covering. Operator visibility: Suction hose shall provide 'operator' 100% visual indication of water movement during the "priming process" along full length of suction hose. High UV inhibitors: shall be provided and suitable for use in working temperature range of -40 to 140 degrees F. The bend-radius varies with diameter and is best in the industry. **Made in the USA. NOTE:** PVC flexible suction hose is NOT designed for positive water pressure (fire hydrants or pumper relay) and must be used for "draft suction" only.

Coupling specification Material: Threaded couplings shall be constructed of Type #6061-T6 extruded aluminum. Couplings shall be hard-coat anodized. Extended shanks shall be installed for hose reinforcement. Couplings shall be attached with internal brass expansion rings with beveled edges for 1.5" to 3.5" sizes. Coupling collars shall be attached with Allen wrench bolts with "O" rings for sealing purposes on 4" to 6" sizes. Coupling collars shall be aluminum (plastic collars not acceptable) with beveled edges for easy removal from a vehicle. Folding handles available as option. Couplings shall support at least (3) lengths of suction hose in a vertical position. Made in the

HSH-15NHRL-10	1.5" Flex-Lite PVC Suction Hose 1.5" NH Male R/L x FS R/L 10 ft. long	\$134.00
HSH-15NHRL-15	1.5" Flex-Lite PVC Suction Hose 1.5" NH Male R/L x FS R/L 15 ft. long	\$163.00
HSH-15NHRL-20	1.5" Flex-Lite PVC Suction Hose 1.5" NH Male R/L x FS R/L 20 ft. long	\$192.00
HSH-15NHRL-25	1.5" Flex-Lite PVC Suction Hose 1.5" NH Male R/L x FS R/L 25 ft. long	\$221.00
HSH-20NHRL-10	2" Flex-Lite PVC Suction Hose 2" NH Male R/L x FS R/L 10 ft. long	\$203.00
HSH-20NHRL-15	2" Flex-Lite PVC Suction Hose 2" NH Male R/L x FS R/L 15 ft. long	\$241.00
HSH-20NHRL-20	2" Flex-Lite PVC Suction Hose 2" NH Male R/L x FS R/L 20 ft. long	\$278.00
HSH-20NHRL-25	2" Flex-Lite PVC Suction Hose 2" NH Male R/L x FS R/L 25 ft. long	\$316.00
HSH-20NPSHRL-10	2" Flex-Lite PVC Suction Hose 2" NPSH Male R/L x FS R/L 10 ft. long	\$203.00
HSH-20NPSHRL-15	2" Flex-Lite PVC Suction Hose 2" NPSH Male R/L x FS R/L 15 ft. long	\$241.00
HSH-20NPSHRL-20	2" Flex-Lite PVC Suction Hose 2" NPSH Male R/L x FS R/L 20 ft. long	\$278.00
HSH-20NPSHRL-25	2" Flex-Lite PVC Suction Hose 2" NPSH Male R/L x FS R/L 25 ft. long	\$316.00
HSH-25NH-10	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 10 ft.	\$330.00
HSH-25NH-15	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 15 ft.	\$384.00
HSH-25NH-20	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 20 ft.	\$437.00
HSH-25NH-25	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 25 ft.	\$491.00
HSH-25NHRL-10	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 10 ft. long	\$268.00
HSH-25NHRL-15	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 15 ft. long	\$328.00
HSH-25NHRL-20	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 20 ft. long	\$389.00
HSH-25NHRL-25	2.5" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 25 ft. long	\$450.00
HSH-25NPSHRL-10	2.5" Flex-Lite PVC Suction Hose 2.5" NPSH Male R/L x FS R/L 10 ft. long	\$268.00
HSH-25NPSHRL-15	2.5" Flex-Lite PVC Suction Hose 2.5" NPSH Male R/L x FS R/L 15 ft. long	\$328.00
HSH-25NPSHRL-20	2.5" Flex-Lite PVC Suction Hose 2.5" NPSH Male R/L x FS R/L 20 ft. long	\$389.00
HSH-25NPSHRL-25	2.5" Flex-Lite PVC Suction Hose 2.5" NPSH Male R/L x FS R/L 25 ft. long	\$450.00



HSH-30-25NH-10	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 10 ft.	\$519.00
HSH-30-25NH-15	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 15 ft.	\$596.00
HSH-30-25NH-20	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 20 ft.	\$672.00
HSH-30-25NH-25	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x Female LH 25 ft.	\$749.00
HSH-30-25NHRL-10	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 10 ft. long	\$504.00
HSH-30-25NHRL-15	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 15 ft. long	\$580.00
HSH-30-25NHRL-20	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 20 ft. long	\$657.00
HSH-30-25NHRL-25	3" Flex-Lite PVC Suction Hose 2.5" NH Male R/L x FS R/L 25 ft. long	\$733.00
HSH-30NH-10	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x Female LH 10 ft. long	\$755.00
HSH-30NH-15	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x Female LH 15 ft. long	\$831.00
HSH-30NH-20	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x Female LH 20 ft. long	\$908.00
HSH-30NH-25	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x Female LH 25 ft. long	\$984.00
HSH-30NHRL-10	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x FS R/L 10 ft. long	\$739.00
HSH-30NHRL-15	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x FS R/L 15 ft. long	\$816.00
HSH-30NHRL-20	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x FS R/L 20 ft. long	\$892.00
HSH-30NHRL-25	3" Flex-Lite PVC Suction Hose 3" NH Male R/L x FS R/L 25 ft. long	\$969.00
HSH-40NH-10	4" Flex-Lite PVC Suction Hose 4" NH Male R/L x Female LH 10 ft. long	\$1,004.00
HSH-40NH-15	4" Flex-Lite PVC Suction Hose 4" NH Male R/L x Female LH 15 ft. long	\$1,121.00
HSH-40NH-20	4" Flex-Lite PVC Suction Hose 4" NH Male R/L x Female LH 20 ft. long	\$1,238.00
HSH-40NHRL-10	4" Flex-Lite PVC Suction Hose 4" Male R/L x FS R/L 10 ft. long	\$988.00
HSH-40NHRL-15	4" Flex-Lite PVC Suction Hose 4" Male R/L x FS R/L 15 ft. long	\$1,105.00
HSH-40NHRL-20	4" Flex-Lite PVC Suction Hose 4" Male R/L x FS R/L 20 ft. long	\$1,223.00
HSH-50-45NH-10	5" Flex-Lite PVC Suction Hose 4.5" NH Male R/L x Female LH 10 ft. long	\$1,362.00
HSH-50-45NH-15	5" Flex-Lite PVC Suction Hose 4.5" NH Male R/L x Female LH 15 ft. long	\$1,555.00
HSH-50-45NH-20	5" Flex-Lite PVC Suction Hose 4.5" NH Male R/L x Female LH 20 ft. long	\$1,748.00
HSH-50NH-10	5" Flex-Lite PVC Suction Hose 5" Male R/L x Female LH 10 ft. long	\$1,313.00
HSH-50NH-15	5" Flex-Lite PVC Suction Hose 5" Male R/L x Female LH 15 ft. long	\$1,506.00
HSH-50NH-20	5" Flex-Lite PVC Suction Hose 5" Male R/L x Female LH 20 ft. long	\$1,699.00
HSH-50NHRL-10	5" Flex-Lite PVC Suction Hose 5" Male R/L x FS R/L 10 ft. long	\$1,298.00
HSH-50NHRL-15	5" Flex-Lite PVC Suction Hose 5" Male R/L x FS R/L 15 ft. long	\$1,491.00
HSH-50NHRL-20	5" Flex-Lite PVC Suction Hose 5" Male R/L x FS R/L 20 ft. long	\$1,683.00
HSH-60NH-10	6" Flex-Lite PVC Suction Hose 6" Male R/L x Female LH 10 ft. long	\$1,350.00
HSH-60NH-15	6" Flex-Lite PVC Suction Hose 6" Male R/L x Female LH 15 ft. long	\$1,700.00
HSH-60NH-20	6" Flex-Lite PVC Suction Hose 6" Male R/L x Female LH 20 ft. long	\$1,959.00
HSH-60NHRL-10	6" Flex-Lite PVC Suction Hose 6" Male R/L x FS R/L 10 ft. long	\$1,437.00
HSH-60NHRL-15	6" Flex-Lite PVC Suction Hose 6" Male R/L x FS R/L 15 ft. long	\$1,696.00
HSH-60NHRL-20	6" Flex-Lite PVC Suction Hose 6" Male R/L x FS R/L 20 ft. long	\$1,955.00
HSH-60NH/FH-10	6" Flex-Lite PVC Suction Hose 6" NH Male R/L x Female Folding L/H 10 ft	\$1,580.00
HSH-60NH/FH-15	6" Flex-Lite PVC Suction Hose 6" NH Male R/L x Female Folding L/H 15 ft	\$1,840.00
HSH-60NH/FH-20	6" Flex-Lite PVC Suction Hose 6" NH Male R/L x Female Folding L/H 20 ft	\$2,100.00



HSHS - Suction Hose with Storz Couplings

The Harrington Model HSHS 'Flex-Lite' PVC hard suction hose sizes from 2.5" to 6" in diameter and custom lengths up to 20' long. Available in Storz couplings, with 4" and larger locking type. **MEETS OR EXCEEDS NFPA 1961 STANDARDS.**



Hose Specifications Material: Rigid PVC helical & accordion-type rings continuously encapsulated with soft PVC clear covering. Operator visibility: Suction hose shall provide 'operator' 100% visual indication of water movement during the "priming process" along full-length of suction hose. High UV inhibitors: shall be provided and suitable for use in working temperature range of -40 to 140 degrees F. The bend radius varies with diameter and is the best in the industry. **Made in the USA. NOTE:** PVC flexible suction hose is NOT designed for positive water pressure (fire hydrants or pumper relay) and must be used for "draft-suction" only.

Coupling Specifications Material: threaded couplings shall be constructed of Type #6061-T6 extruded aluminum. Couplings shall be hard-coat anodized. Extended shanks shall be installed for hose reinforcement. Couplings shall be attached with internal brass expansion rings with beveled edges for 1.5" to 3.5" sizes. Coupling collars shall be attached with Allen wrench bolts with "O" rings for sealing purposes on 4" to 6" sizes. Coupling collars shall be aluminum (plastic collars not acceptable) with beveled edges for easy removal from a vehicle. Couplings shall support at least (3) lengths of suction hose in a vertical position. **Made in the USA.**



HSHS-25ST-10	2.5" Flex-Lite PVC Suction Hose Couplings 2.5" Storz 10 ft. long	\$475.00
HSHS-25ST-15	2.5" Flex-Lite PVC Suction Hose Couplings 2.5" Storz 15 ft. long	\$529.00
HSHS-25ST-20	2.5" Flex-Lite PVC Suction Hose Couplings 2.5" Storz 20 ft. long	\$584.00
HSHS-25ST-25	2.5" Flex-Lite PVC Suction Hose Couplings 2.5" Storz 25 ft. long	\$639.00
HSHS-30ST-10	3" Flex-Lite PVC Suction Hose Couplings 3" Storz 10 ft. long	\$822.00
HSHS-30ST-15	3" Flex-Lite PVC Suction Hose Couplings 3" Storz 50 ft. long	\$887.00
HSHS-30ST-20	3" Flex-Lite PVC Suction Hose Couplings 3" Storz 20 ft. long	\$953.00
HSHS-30ST-25	3" Flex-Lite PVC Suction Hose Couplings 3" Storz 25 ft. long	\$1,018.00
HSHS-40ST-10	4" Flex-Lite PVC Suction Hose Couplings 4" Storz/Lok 10 ft. long	\$1,678.00
HSHS-40ST-15	4" Flex-Lite PVC Suction Hose Couplings 4" Storz/Lok 15 ft. long	\$1,796.00
HSHS-40ST-20	4" Flex-Lite PVC Suction Hose Couplings 4" Storz/Lok 20 ft. long	\$1,893.00
HSHS-45ST-10	4" Flex-Lite PVC Suction Hose Couplings 4.5" Storz/Lok 10 ft. long	\$1,504.00
HSHS-45ST-15	4" Flex-Lite PVC Suction Hose Couplings 4.5" Storz/Lok 15 ft. long	\$1,622.00
HSHS-45ST-20	4" Flex-Lite PVC Suction Hose Couplings 4.5" Storz/Lok 20 ft. long	\$1,739.00
HSHS-50ST-10	5" Flex-Lite PVC Suction Hose Couplings 5" Storz/Lok 10 ft. long	\$1,973.00
HSHS-50ST-15	5" Flex-Lite PVC Suction Hose Couplings 5" Storz/Lok 15 ft. long	\$2,166.00
HSHS-50ST-20	5" Flex-Lite PVC Suction Hose Couplings 5" Storz/Lok 20 ft. long	\$2,359.00
HSHS-60-50ST-10	6" Flex-Lite PVC Suction Hose Couplings 5" Storz/Lok 10 ft. long	\$2,600.00
HSHS-60-50ST-15	6" Flex-Lite PVC Suction Hose Couplings 5" Storz/Lok 15 ft. long	\$2,950.00
HSHS-60-50ST-20	6" Flex-Lite PVC Suction Hose Couplings 5" Storz/Lok 20 ft. long	\$3,200.00
HSHS-60ST-10	6" Flex-Lite PVC Suction Hose Couplings 6" Storz/Lok 10 ft. long	\$2,200.00
HSHS-60ST-15	6" Flex-Lite PVC Suction Hose Couplings 6" Storz/Lok 15 ft. long	\$2,538.00
HSHS-60ST-20	6" Flex-Lite PVC Suction Hose Couplings 6" Storz/Lok 20 ft. long	\$2,797.00
HSHS-60ST/FH-10	6" Flex-Lite PVC Suction Hose Couplings 6" Storz Folding LH 10 ft long	\$2,711.00



HSHS-60ST/FH-15	6" Flex-Lite PVC Suction Hose Couplings 6" Storz Folding LH 15 ft long	\$2,970.00
HSHS-60ST/FH-20	6" Flex-Lite PVC Suction Hose Couplings 6" Storz Folding LH 20 ft long	\$3,229.00

Suction Hose — Shipping

1. Standard 10' length hose is measured from end of coupling to end of coupling
2. Special custom short or long lengths can be made, just call for pricing.
3. Suction Hose Sizes: 1.5" to 3" x <10 feet in length can be shipped via UPS or Fed-Ex ground.
4. NOTE: 4", 5", and 6" hoses must ship via truck.
5. Hoses longer than 10 feet shall result in higher freight rates.
6. 5" & 6" hoses are shipped flat & straight to reduce possible damage to hose in transit.
7. Storz x NH connections on one length can be supplied, just call factory for pricing.
8. No shipments permitted to personal residences.
9. For freight quotes, send the following details:

Part number and quantity of EACH item
Provide ZIP CODE for ship-to location
EMAIL to: shipquote@harrinc.com



6" SUCTION HOSE - BEND RADIUS EXAMPLE



HTBS - Barrel Strainer - Female Rigid

The Harrington Model HTBS barrel strainer is available in 2.5" to 6" sizes with NH or special threads. The strainer is built with 3/16" aluminum tubing with 3/8" punched holes. The end of the strainer is closed with a 1" rope ring provided. The length of strainer and flow capacity varies with each size. The female thread is hard anodized aluminum and equipped with rocker lugs. A foot valve is an available option in 2.5" and 4" sizes. **Made in the USA.**



HTBS-25NH	2.5" Barrel Suction 2.5" NH Female rigid	\$220.00
HTBS-FV-25NH	2.5" Barrel Suction 2.5" NH Female rigid Foot Valve	\$685.00
HTBS-30NH	3" Barrel Suction 3" NH Female rigid	\$265.00
HTBS-FV-30NH	3" Barrel Suction 3" NH Female rigid Foot Valve	\$715.00
HTBS-40NH	4" Barrel Suction 4" NH Female rigid	\$315.00
HTBS-FV-40NH	4" Barrel Suction 4" NH Female rigid Foot Valve	\$815.00
HTBS-45NH	4.5" Barrel Suction 4.5" NH Female rigid	\$410.00
HTBS-50NH	5" Barrel Suction 5" NH Female rigid	\$420.00
HTBS-60NH	6" Barrel Suction 6" NH Female rigid	\$410.00

HSBS - Barrel Strainer - Storz

HSBS-25ST	2.5" Barrel Strainer 2.5" Storz rigid	\$235.00
HSBS-30ST	3" Barrel Strainer 3" Storz rigid	\$230.00
HSBS-40ST	4" Barrel Strainer 4" Storz rigid	\$525.00
HSBS-50ST	5" Barrel Strainer 5" Storz rigid	\$640.00
HSBS-60ST	6" Barrel Strainer 6" Storz rigid	\$700.00



HWMBBS - Basket Strainer/Diffuser - Threaded

The Harrington Model HWMBBS basket strainer and diffuser is available in 2.5" to 6" sizes with NH or special threads. The strainer thread assembly is hard anodized lightweight aluminum, with rocker lugs. The basket strainer features a stainless-steel mesh screen with 3/8" holes. The dimensions of the strainer and flow capacity varies with each size and designed to reduce debris from entering a fire pump. This same device can be used to diffuse water when testing fire hydrants, allowing the flow to be safely diffused. **Made in the USA.**



HWMBBS-25NH	2.5" NH Female Basket Suction Strainer-Diffuser	\$385.00
HWMBBS-30NH	3" NH Female Basket Suction Strainer-Diffuser	\$400.00
HWMBBS-35NH	3.5" NH Female Basket Suction Strainer-Diffuser	\$415.00
HWMBBS-40NH	4" NH Female Basket Suction Strainer-Diffuser	\$455.00
HWMBBS-45NH	4.5" NH Female Basket Suction Strainer-Diffuser	\$470.00
HWMBBS-50NH	5" NH Female Basket Suction Strainer-Diffuser	\$565.00
HWMBBS-60NH	6" NH Female Basket Suction Strainer-Diffuser	\$620.00



HTLLS - Threaded & Storz - Low-Level Strainer with Jet Siphon



The Harrington Model HTLLS and HSLLS low-level strainer are equipped with a 1.5" NH or NPSH female swivel and male plug & chain, to provide a siphon-jet connection. Strainer is available in 2.5" to 6" sizes with NH female swivel connection and LHs, as well as with Storz 4", 5", and 6". The strainer feature a large 'base skid plate' for protection, with a surrounding 4-sided screen with 3/8" holes for water entry into the strainer. The 90-degree aluminum elbow pipe connects to the hard anodized aluminum female swivel assembly. The jet siphon connects to the vertical elbow to increase water flow in suction hose. The strainer is powder-coated red in color. **Made in the USA.**



HTLLS-25NHLH	2.5" Low Level Strainer 2.5" NH Female LH swivel 1.5" NH siphon jet	\$810.00
HTLLS-30NHLH	3" Low Level Strainer 3" NH Female LH swivel 1.5" NH siphon jet	\$855.00
HTLLS-40NHLH	4" Low Level Strainer 4" NH Female LH swivel 1.5" NH siphon jet	\$940.00
HTLLS-45NHLH	4.5" Low Level Strainer 4.5" NH Female LH swivel 1.5" NH siphon jet	\$1,140.00
HTLLS-50NHLH	5" Low Level Strainer 5" NH Female LH swivel 1.5" NH siphon jet	\$1,130.00
HTLLS-60NHLH	6" Low Level Strainer 6" NH Female LH swivel 1.5" NH siphon jet	\$1,170.00
HSLLS-40ST	4" Low Level Strainer 4" Storz rigid 1.5" NH siphon jet	\$1,340.00
HSLLS-50ST	5" Low Level Strainer 5" Storz rigid 1.5" NH siphon jet	\$1,235.00
HSLLS-60ST	6" Low Level Strainer 6" Storz rigid 1.5" NH siphon jet	\$1,045.00

HTFBS - Threaded & HSFBS - Storz Floating Strainer



The Harrington Model HTFBS & HSFBS floating barrel strainer is available in 2.5" to 6" sizes with NH FS LH and Storz connection. The NH connection shall be hard anodized aluminum. The floating strainer is built with light-wall aluminum tubing in a "U" shape for flotation purposes. The suction barrel shall be a hinge-mounted unit in center of flotation pipe, with a round aluminum barrel-design strainer, with 3/8" holes in bottom, below the water surface. A carrying handle shall be provided. The dimensions of strainer and flow capacity varies with each size. The strainer shall be powder-coated red in color. **Made in the USA.**



HTFBS-25NHLH	2.5" Floating Strainer 2.5" NH female LH swivel	\$835.00
HTFBS-30NHLH	3" Floating Strainer 3" NH female LH swivel	\$870.00
HTFBS-40NHLH	4" Floating Strainer 4" NH female LH swivel	\$1,400.00
HTFBS-45NHLH	4.5" Floating Strainer 4.5" NH female LH swivel	\$1,395.00
HTFBS-50NHLH	5" Floating Strainer 5" NH female LH swivel	\$1,385.00
HTFBS-60NHLH	6" Floating Strainer 6" NH female LH swivel	\$1,485.00
HSFBS-40ST	4" Floating Strainer 4" Storz rigid	\$1,620.00
HSFBS-45ST	4.5" Floating Strainer 4.5" Storz rigid	\$1,600.00
HSFBS-50ST	5" Floating Strainer 5" Storz rigid	\$1,705.00
HSFBS-60ST	6" Floating Strainer 6" Storz rigid	\$1,585.00



HPSE90 - Pressure/Suction Elbow

The Harrington Model HPSE90: 90-degree pressure / suction elbow can be utilized for suction and discharge applications providing a compact transition from the fire pump to folding tank or secondary pumper. The inlet shall be from 4" to 6" NH FS LH and the discharge shall be available in NH 4" to 6". Rocker lugs are available. The adapter shall be hard-coat anodized of Type #6061-T6 aluminum and powder-coated black. The elbow shall be rated to 250 PSI working pressure and shall comply to applicable NFPA standards. Made in the USA.



Elbows have 3" and 6" extension adapters for special applications and installation on fire apparatus.

HPSE90-50NHM-50NHFS LH	90° Pressure/Suction Elbow 5" NH Male x 5" NH FS LH	\$1,320.00
HPSE90-50ST-50ST/S	90° Pressure/Suction Elbow 5" Storz x 5" Storz Swivel	\$2,000.00
HPSE90-50ST-60NHFS LH	90° Pressure/Suction Elbow 5" Storz/Lok x 6" NH FS LH	\$1,620.00
HPSE90-60NHM-50NHFS LH	90° Pressure/Suction Elbow 6" NH Male x 5" NH FS LH	\$1,280.00
HPSE90-60NHM-60NHFS RL	90° Pressure/Suction Elbow 6" NH Male x 6" NH FS R/L	\$1,350.00
HPSE90-60NHM-60NHFS LH	90° Pressure/Suction Elbow 6" NH Male x 6" NH FS LH	\$1,350.00
HPSE90-3-60NHM-60NHFS LH	90° Pressure/Suction Elbow 6" NH Male x 6" NH FS LH 3" Extension	\$1,510.00
HPSE90-6-60NHM-60NHFS LH	90° Pressure/Suction Elbow 6" NH Male x 6" NH FS LH with 6" Extension	\$1,720.00

HFE - 45° Flushing Elbow

The Harrington Model HFE45 45-degree elbow can be utilized for fire hydrant flushing applications. The inlet shall range from 2.5" to 6" NH FS LH and discharge outlet shall be available in 4" to 6". Rocker lugs are available. The elbow and connections shall be hard anodized cast aluminum and powder-coated black.



HFE-25NHLH	45° Elbow x 2.5" NH FS LH	\$250.00
------------	---------------------------	----------



HHSN - Wildland Nozzles



The Harrington Model HHSN wildland nozzle shall be constructed of lightweight aluminum or brass (refer to exact model in part number). All models have 'twist-to-shutoff' design and are provided with molded rubber teeth and bumper. The nozzles have choice of: 1", 1.5", and 2.5" NH or NPSH female swivel rocker lug, 2" male BSP, and 2" Storz connections. The nozzles are available in: 1" size for 25 GPM and 1.5, 2", and 2.5" sizes for 75-150 GPM models at 100 PSI. The 1.5" model shall have a flow rate of 75 GPM in a straight stream mode and 150 GPM in fog mode. "PG" models are pistol grip. Working pressures up to: 250 PSI.

HHSN-12-R20M	Wildland Nozzle HS-12 2" BSP male	\$306.00
HHSN-12-15NH	Wildland Nozzle HS-12 (75-150 GPM) 1.5" NH FS R/L	\$371.00
HHSN-12-15NPSH	Wildland Nozzle HS-12 (75-150 GPM) 1.5" NPSH FS R/L	\$371.00
HHSN-16-R20M	Wildland Nozzle HS-16 2" BSP male	\$306.00
HHSN-16-20ST	Wildland Nozzle HS-16 2" Storz	\$334.00
HHSN-16-25NH	Wildland Nozzle HS-16 2.5" NH FS R/L	\$438.00
HHSN-20-R20M	Wildland Nozzle H-20 2" BSP male	\$306.00
HHSN-20-25NH	Wildland Nozzle HS-20 2.5" NH FS R/L	\$438.00



HFI - Foam Proportioner

The Harrington Model HFI foam proportioner is offered in choice of: 1.5" and 2.5" NH and NPSH sizes, with flow range of 60 GPM, 125 GPM, and 250 GPM. The lightweight aluminum educator shall have female swivel and male threaded connections with rocker lugs. The nozzle shall have an operational water pressure starting as low as 100 PSI for various applications. Foam concentrate percentage control provided with settings of 0.5%, 1%, 3%, and 6%, for either Class A and B foam. The foam educator includes a clear pick-up tube with Storz connection and stainless-steel wand. Working pressure to 250 PSI.



HFI-Z2-15NH-KIT	Foam Proportioner 60 GPM 1.5" NH FS R/L inlet x 1.5" NH male outlet Pick-up Tube - S/S Wand	\$1,206.00
HFI-Z2-15NPSH-KIT	Foam Proportioner 60 GPM 1.5" NPSH FS R/L inlet x 1.5" NPSH male outlet Pick-up Tube - S/S Wand	\$1,206.00
HFI-Z4-15NH-KIT	Foam Proportioner 125 GPM 1.5" NH FS R/L inlet x 1.5" NH male outlet Pick-up Tube - S/S Wand	\$1,350.00
HFI-Z4-15NPSH-KIT	Foam Proportioner 125 GPM 1.5" NPSH FS R/L inlet x 1.5" NPSH male outlet Pick-up Tube - S/S Wand	\$1,350.00
HFI-Z4-25NH-KIT	Foam Proportioner 125 GPM 2.5" NH FS R/L inlet x 2.5" NH male outlet Pick-up Tube - S/S Wand	\$1,506.00
HFI-Z4-25NHFS-15NHM-KIT	Foam Proportioner 125 GPM 2.5" NH FS R/L inlet x 1.5" NH male outlet Pick-up Tube - S/S Wand	\$1,481.00
HFI-Z8-25NH-KIT	Foam Proportioner 250 GPM 2.5" NH FS R/L inlet x 2.5" NH male outlet Pick-up Tube - S/S Wand	\$2,163.00
HFPT-STD	Foam Pick-up Tube .750" PVC 5 ft long x Storz adapter 1" - 20" S/S Wand	\$125.00



HHFN - Low Expansion Foam Nozzle



The Harrington Model HHFN aluminum foam nozzle shall be designed for making air-aspirated low expansion foam at a 15:1 ratio. The nozzle shall provide for a long reach for added safety, available in sizes of 1.5" and 2.5", with NH and NPSH female swivel connection. The nozzle shall include a quarter turn ball shut-off valve and carrying handle. Flow rates available in 60 and 90 GPM @ 100 PSI for a 1.5" nozzle or 125 GPM @ 100 PSI for a 2.5" nozzle. Working pressure up to 250 PSI.

HHFN-S2-15NH	Foam Nozzle 60GPM Low Expansion 1.5" NH FS Shut-off Valve	\$783.00
HHFN-S2-15NPSH	Foam Nozzle 60GPM Low Expansion 1.5" NPSH FS Shut-off Valve	\$783.00
HHFN-S4-15NH	Foam Nozzle 125GPM Low Expansion 1.5" NH FS Shut-off Valve	\$953.00
HHFN-S4-15NPSH	Foam Nozzle 125GPM Low Expansion 1.5" NPSH FS Shut-off Valve	\$953.00
HHFN-S4-25NH	Foam Nozzle 125GPM Low Expansion 2.5" NH FS Shut-off Valve	\$1,054.00
HHFN-S8-25NH	Foam Nozzle 250GPM Low Expansion 2.5" NH FS Shut-off Valve	\$2,472.00

HMFN - Medium Expansion Foam Nozzle



The Harrington Model HMFN lightweight aluminum foam nozzle shall be designed for making air-aspirated medium-expansion foam at a 60:1 ratio. The nozzle shall have a large aluminum aeration tube to provide an excellent foam blanket over hazardous spills. The nozzle shall be available in sizes of 1.5" and 2.5", with NH and NPSH female swivel connection and rocker lugs. The nozzle includes a quarter-turn ball shut-off valve and carrying handle. Flow rates available in 60 and 95 GPM @ 100 PSI for a 1.5" nozzle and 125 GPM @ 100 PSI for a 2.5" nozzle. Working pressure up to 250 PSI.









HMFN-M2-15NH	Foam Nozzle 60GPM Medium Expansion 1.5" NH FS with shut-off valve	\$1,876.00
HMFN-M2-15NPSH	Foam Nozzle 60GPM Medium Expansion 1.5" NPSH FS with shut-off valve	\$1,876.00
HMFN-M4-15NH	Foam Nozzle 125GPM Medium Expansion 1.5" NH FS with shut-off valve	\$2,217.00
HMFN-M4-15NPSH	Foam Nozzle 125GPM Medium Expansion 1.5" NPSH FS with shut-off valve	\$2,217.00
HMFN-M4-25NH	Foam Nozzle 125GPM Medium Expansion 2.5" NH FS with shut-off valve	\$2,317.00



Spanner & Hydrant Wrenches (ONLY)

The Harrington custom-designed spanner and hydrant wrenches are provided for new or replacement purposes. Hydrant wrenches are for specific types of fire hydrants, in both manual (threaded type) or ratchet designs. NOTE: This page is for WRENCHES ONLY, please carefully and refer to the Harrington part numbers, catalog descriptions, and photos.

HSSW-15-25	Spanner Wrench, Single End, HARR, 1.5" to 2.5"	\$93.00
HSSW-20-30	Spanner Wrench, Single End, HARR, 2", 2.5", 3"	\$62.00
HSSW-101	Spanner Wrench, Single End, HARR, 2.5" to 5"	\$55.00
HSSW-41-61	Spanner Wrench, Single End, HARR, 4" to 6"	\$45.00
HSSW-50-60	Spanner Wrench, Single End, HARR, 5" and 6"	\$163.00
HSW-25	Spanner Wrench, 2.5"	\$75.00
HHSW-100	Spanner/Hydrant Wrench 4" and 5"	\$150.00
HSW-HW	Hydrant Wrench, Aluminum, Adjustable Nut	\$120.00
HWS-HW-HD	Hydrant Wrench, Steel Adjustable Nut	\$70.00
HHW-RAC	Hydrant Wrench Ratchet for Pentagon nuts or square nuts	\$520.00
PRY BARS	Hand Tools, HARR, PRY-BARS for connecting 8", 10", and 12" Storz couplings	\$155.00





HSSW-15-25		HHSW-100	
HSSW-20-30		HSW-HW	
HSSW-101		HSW-HW-HD	
HSSW-41-61		HHW-RAC	
HSSW-50-60		PRY BARS	
HSW-25			



Combination of Spanner & Hydrant Wrenches & Mounting Brackets

The Harrington spanner & hydrant wrenches and mounting brackets “combinations” are available in various types, part numbers, and applicable uses. Each is unique to coupling type and hose size. Hydrant wrenches are adjustable with LHs. In selection be careful of exact size of fire hose and type of wrench required.

HSSW-401	Spanner Wrenches and Mntg Brckt, (4) HSSW-101	\$325.00
HSSW-201	Spanner Wrenches and Mntg Brckt, (2) HSSW-101	\$215.00
HSSW-501	Spanner Wrenches and Mntg Brckt, (4) HSSW-41-61 Single End	\$280.00
HSWS-25	Spanner Wrenches and Mntg Brckt, (2)HSW-25 Spanners	\$295.00
HSWS-25-HW	Spanner and Hydrant Wrench/Mntg, (2)HSW-25 & #HSW-HW	\$440.00
HSSW-501-HSW	Spanner and Hydrant Wrench/Mntg, (4) HSSW-41-61 & (1)HHSW-100	\$555.00
HSWS-25-100	Spanner and Hydrant Wrench/Mntg, (2)HSW-25 and (1) HHSW-100	\$470.00

HSSW-401		HSSW-501-HSW	
HSSW-201		HSWS-25-HW	
HSSW-501		HSWS-25-100	
HSWS-25			



Mounting Brackets (ONLY) for Spanner & Hydrant Wrenches

The Harrington wrench mounting brackets are available in various types and part numbers, suitable for Harrington wrenches. Each mounting is specific to wrench combinations. In selection be careful of exact wrench and mounting bracket.

HSMB-100	Mounting Bracket for HSSW-101	\$105.00
HSMB-41-61	Mounting Bracket for HSSW-41-61	\$105.00
HSMB-41-61-HSW	Mounting Bracket for HSSW-41-61 & HHSW-100	\$225.00
HSMB-25	Mounting Bracket for HSW-25	\$145.00
HSMB-25-1	Mounting Bracket for HSW-25 & Hydrant Wrench	\$170.00



HSMB - Storz Mounting Brackets

The Harrington Model HSMB custom-built mounting brackets are designed specifically for Harrington #HSSW spanner wrenches. Refer to spanner wrenches to pick the appropriate brackets, which are designed with quick-release latches or fastening devices.

HSMB-15-25	1.5" and 2.5" Storz mounting bracket aluminum	\$125.00
HSMB-20-30	2" and 3" Storz mounting bracket POM plastic gray	\$31.00
HSMB-40	4" Storz mounting bracket aluminum	\$70.00
HSMB-50	5" Storz mounting bracket aluminum	\$90.00
HSMB-50-45	4.5" Storz mounting bracket POM plastic gray	\$25.00
HSMB-60	6" Storz mounting bracket aluminum	\$110.00



HPM - Post Mount for Water-Thieves, Ball & Hydrant Valves



The Harrington Model HPM-HV and #HPM-M post-type mounting have been custom-designed specifically for the Harrington #H700 hydrant valve, H301 and H400 water thieves.

HPM-HV	Post mount for H700 Hydrant Valves	\$345.00
HPM-M	Post mount for H301 and H400 Water-Thief	\$340.00

HTMB - Male NH Threaded Mounting Brackets



The Harrington Model HTMB threaded mounting brackets have been custom designed specifically for the Harrington adapters. The brackets bolt in place for both exterior and interior mounting locations. Made of all of aluminum construction in both male and female threaded configurations (only NH), in sizes from 1" to 6".



HTMB-10NHM	1" NH Male mounting bracket	\$60.00
HTMB-15NHM	1.5" NH Male mounting bracket	\$60.00
HTMB-20NHM	2" NH Male mounting bracket	\$65.00
HTMB-25NHM	2.5" NH Male mounting bracket	\$65.00
HTMB-30NHM	3" NH Male mounting bracket	\$145.00
HTMB-35NHM	3.5" NH Male mounting bracket	\$165.00
HTMB-40NHM	4" NH Male mounting bracket	\$185.00
HTMB-45NHM	4.5" NH Male mounting bracket	\$205.00
HTMB-50NHM	5" NH Male mounting bracket	\$220.00
HTMB-60NHM	6" NH Male mounting bracket	\$210.00

HTMB - Female NH Threaded Mounting Brackets



HTMB-10NHFS	1" NH FS mounting bracket	\$85.00
HTMB-15NHFS	1.5" NH FS mounting bracket	\$85.00
HTMB-20NHFS	2" NH FS mounting bracket	\$85.00
HTMB-25NHFS	2.5" NH FS mounting bracket	\$95.00
HTMB-30NHFS	3" NH FS mounting bracket	\$210.00
HTMB-35NHFS	3.5" NH FS mounting bracket	\$245.00
HTMB-40NHFS	4" NH FS mounting bracket	\$270.00
HTMB-45NHFS	4.5" NH FS mounting bracket	\$285.00
HTMB-50NHFS	5" NH FS mounting bracket	\$305.00
HTMB-60NHFS	6" NH FS mounting bracket	\$330.00



HHR - Hose Rollers

The Harrington Model HHR hose roller has been field tested and includes a 90-degree opening. The unit flattens fire hoses up to 5" LDH in diameter and squeezes out water, air, and breaks up ice accumulation. The heavy-duty roller is of lightweight aluminum construction, weighing under 5 lbs. Available in one-person HHR-1 or two-person HHR-2 models.



HHR-1	One-Man Hose Roller	\$335.00
HHR-2	Two-Man Hose Roller	\$300.00

HHW - Hose Washer

The Harrington Model HHW-300 self-feeding hose washer has been field-tested with an inlet water pressure as low as 60 PSI. The unit is equipped with two (2) cone-shaped pressure jets at the inlet and outlet, allowing the hose to be washed twice in one cycle. The impact of the pressure jets from the two angular gaps pushes the hose through the unit. The washer is built of aluminum construction, equipped with a carrying handle with a close-mesh screen at the water inlet to prevent penetration of debris.



The Harrington Model #HHW-500 washes 3" up to 5" hose with 2.5" NH or NPSH female swivel and rocker lug connection. NOTE: this unit does not self-feed the hose in and out of washer.

HHW-300-15NH	Hose Washer Up to 3" hose 1.5" NH FS R/L inlet	\$1,694.00
HHW-300-15NPSH	Hose Washer Up to 3" hose 1.5" NPSH FS R/L inlet	\$1,694.00
HHW-300-25NH	Hose Washer Up to 3" hose 2.5" NH FS R/L inlet	\$1,769.00
HHW-300-25NPSH	Hose Washer Up to 3" hose 2.5" NPSH FS R/L inlet	\$1,769.00
HHW-500-25NH	Hose Washer Up to 5" hose 2.5" NH FS R/L inlet	\$2,440.00

HWS - Water Curtain Nozzle

The Harrington Model HWS water curtain nozzle has been designed for "unmanned" operations for exposure protection between buildings, gaseous hazards, or cooling situation requirements.

- 1.5" 210 GPM at 75 PSI female swivel rocker lug inlet, in NH or NPSH threads
- 2.5" 370 GPM at 75 PSI female swivel rocker lug inlet, in NH or NPSH threads.



HWS-15NH	Water Curtain Nozzle 1.5" 210 GPM @ 75 PSI x 1.5" NH FS R/L	\$500.00
HWS-15NPSH	Water Curtain Nozzle 1.5" 210 GPM @ 75 PSI x 1.5" NH FS R/L	\$500.00
HWS-25NH	Water Curtain Nozzle 2.5" 370 GPM @ 75 PSI x 2.5" NH FS R/L	\$625.00



H37 - Haz-Mat Reducer - NH to 2 or 4 Garden Hose & Bleeder Cap



The Harrington Model H37 reducing Haz-Mat adapter shall have 1.5" or 2.5" female rigid NH threads with rocker lugs x (2 or 4) GHT valves. Rated for a working pressure of 250 PSI and the lightweight aluminum adapter shall be hard-coated dark anodized.

The Harrington Model H37 adapter shall have 2.5" female rigid NH female threads with rocker lugs x 2.5" NH male threads. Rated for a working pressure of 250 PSI and the lightweight aluminum adapter shall be hard-coated dark anodized. A .250" brass bleeder valve shall be provided.

H37-2XGHT-15NH	Haz-Mat Reducer 1.5" NH female x (2) Garden Hose Males Brass Shut-offs	\$120.00
H37-4XGHT-15NH	Haz-Mat Reducer 1.5" NH female x (4) Garden Hose Males Brass Shut-offs	\$165.00
H37-2XGHT-25NH	Haz-Mat Reducer 2.5" NH-female x (2) Garden Hose Males Brass Shut-offs	\$170.00

H37- Female Rocker Lug w/Bleeder Valve



H37-25NHM-25NH/BV	2.5" NH male x 2.5" NH female rigid rocker lug with bleeder valve	\$212.00
-------------------	---	----------

HSSS - Storz Suction Seals

The Harrington HSSS Storz suction seals are available in sizes from 1" to 6". The Harrington #HSPS Storz discharge pressure seals are available in sizes 2" to 6". The Harrington #HNHG threaded adapter gaskets are available in sizes 1" to 6".



HSSS-10	1" Storz (25) suction seal	\$5.00
HSSS-15	1.5" Storz (38) suction seal	\$7.00
HSSS-20	2" Storz (52) suction seal	\$7.00
HSSS-25	2.5" Storz (65) suction seal	\$11.00
HSSS-30	3" Storz (75) suction seal	\$11.00
HSSS-40	4" Storz (100) suction seal	\$26.00
HSSS-45	4.5" Storz (110) suction seal	\$26.00
HSSS-50	5" Storz (125) suction seal	\$29.00
HSSS-60	6" Storz (150) suction seal	\$33.00



HSPS - Storz Pressure Seals

HSPS-20	2" Storz (52) pressure seal	\$6.00
HSPS-25	2.5" Storz (65) pressure seal	\$6.00
HSPS-30	3" Storz (75) pressure seal	\$6.00
HSPS-40	4" Storz (100) pressure seal	\$12.00
HSPS-50	5" Storz (125) pressure seal	\$17.00
HSPS-60	6" Storz (150) pressure seal	\$37.00



HNHG - NH Pressure Gaskets

HNHG-10	1" NH gasket	\$2.00
HNHG-15	1.5" NH gasket	\$3.00
HNHG-20	2" NH gasket	\$4.00
HNHG-25	2.5" NH gasket	\$4.00
HNHG-30	3" NH gasket	\$4.00
HNHG-35	3.5" NH gasket	\$4.00
HNHG-40	4" NH gasket	\$4.00
HNHG-45	4.5" NH gasket	\$7.00
HNHG-50	5" NH gasket	\$8.00
HNHG-60	6" NH gasket	\$10.00



HBSPG - BSP Female Gaskets

HBSPG-15	1.5" BSP gasket	\$3.00
HBSPG-20	2" BSP gasket	\$3.00
HBSPG-25	2.5" BSP gasket	\$3.00
HBSPG-30	3" BSP gasket	\$4.00
HBSPG-40	4" BSP gasket	\$4.00
HBSPG-45	4.5" BSP gasket	\$5.00
HBSPG-50	5" BSP gasket	\$5.00
HBSPG-60	6" BSP gasket	\$6.00



AWG30291233	Handwheel with fold-down knob (H500S, H1000)	\$363.00
HRV-250-S	Pressure relief valve 75-250 PSI charcoal gray	\$650.00
HABV	Ball valve 0.75" BSP male x 0.75" BSP female (Bleeder valve .750")	\$69.00
HABS	0.75" screw down bleeder valve NPT	\$115.00
HILBV-40-40ST	4" Storz x 4" Storz in-line .750" bleeder valve	\$820.00
HILBV-50-50ST	5" Storz x 5" Storz in-line .750" bleeder valve	\$870.00
HSLA-RED	Red Storz/Lok Assembly Kit for 4", 5" and 6" Storz	\$40.00
Cable-RKIT	Reflective stainless steel aircraft cable for caps, 20" long (2) aluminum connectors	\$10.00
HPG-100-H	0-300 psi Glycerine Filled Pressure Gauge	\$80.00
HLG-15NH-15NH	Luminescent Line Gauge 0-300 psi gauge 1.5" NH male x 1.5" NH FS R/L	\$450.00
HLG-15-xxx-15-xxx	Luminescent Line Gauge 0-300 psi gauge 1.5" special thread male x 1.5" special FS R/L	\$655.00
HLG-25NH-25NH	Luminescent Line Gauge 0-300 psi gauge 2.5" NH male x 2.5" NH FS R/L	\$465.00
HLG-25-xxx-25-xxx	Luminescent Line Gauge 0-300 psi gauge 2.5" special thread male x 2.5" special thread FS R/L	\$725.00

		
AWG30291233	HRV-250-S	HABV
		
HILBV-50-50ST	HSLA-RED	Cable-RKIT
		
HPG-100-H	HLG-15NH-15NH	HABS



TERMS & CONDITIONS

1. **ORDERING:** All orders and change orders, must be in written EMAIL form. Item part numbers and descriptions must agree. PLEASE call or EMAIL for any special or non-standard configurations.

2. **PRICING:** Prices are subject to change at anytime, without notice. Please call or EMAIL to insure that you have the current price list. SPECIAL QUOTES will be valid for 30 days, longer if requested in writing. All custom configurations must be in writing with a quotation prior to ordering.

3. **ORDER SUBMISSION:** Orders are preferably submitted via EMAIL to: orders@harrinc.com.

4. **ORDER CONFIRMATION:** Acknowledgement of orders will be EMAILED on a daily basis. All discrepancies between the 'purchase order' and confirmation will be immediately followed-up in an EMAIL correction.

5. **TERMS:** Net 30 days, unless otherwise agreed upon prior to order entry. F.O.B. (EX-WORKS) Harrington, Inc. Erie, PA. Special shipping terms must be quoted and agreed in writing with the purchase order.

6. **TAX EXEMPTION:** If applicable, purchaser must send necessary forms to Harrington.

7. **FINANCIAL FORMS FOR NEW PURCHASERS:** Please contact Harrington main office to secure 'first time' new customer approval forms by EMAIL.

8. **DISTRIBUTION CHANNELS:** Harrington works in North America with specific distributors.

Please use our www.harrinc.com website to locate various distributors.

QUESTIONS ON ORDERING?

Harrington, Inc.
2630 West 21st Street
Erie, PA 16506
PHONE: 800-553-0078



STANDARD & SPECIAL THREADS

STANDARD THREADS: USA FIRE APPARATUS & FIREFIGHTING EQUIPMENT

NH (National Hose & National Standard Thread (NST) are the same)

NPSH (National Pipe Straight Thread)

NPT (National Pipe Thread & Iron Pipe Thread (IPT) are the same)

NOTE: 1" to 3.5" NPT (no charge)

NPT cannot swivel

SPECIAL THREADS: FIRE APPARATUS & FIREFIGHTING EQUIPMENT

USA 'Special' Custom-Cut Threads - available on request

Canadian Special Threads - available upon request

CUSTOM-CUT SPECIAL THREADS & MACHINING CHARGE

\$20 per thread for "EACH" appliance thread

4" to 6" NPT \$20 per thread for "EACH" appliance thread

*Note: Custom-Cut threads may require additional
production time*

Purchaser must supply:

THREADS PER INCH & OUTSIDE DIAMETER

information for special threads with purchase order



RETURNING NEW PRODUCT & REPAIRS

The Harrington repair department stands ready to serve you in anyway possible. Some of the ways include:

- 1. Warranty repair or replacement on new products.*
- 2. Refurbishing or rebuilding existing products we manufacture.*

The following procedures shall be followed carefully:

- All products being returned, whether for warranty consideration, refurbishment or rebuilding, must have a Return Goods Authorization (RGA) number, prior to the return of any product for any reason.*
- A 25% re-stocking charge may be assessed, depending on the nature of the return.*
- Product returns must be in new and resaleable condition.*
- Care must be made in the return packaging, so no damage is incurred during the return shipment.*
- Harrington reserves the right not to process the return, if it is determined that these conditions have not been made, and return the product(s) at the customer's expense.*

If you have a Harrington Inc. product that needs attention, please EMAIL your Distributor or call us at 1-800-553-0078 to request a RGA number. The form will be sent for you to complete and return with the product. Send all RGA and product returns to:

Harrington, Inc.
Don May, Service Coordinator
2630 West 21st Street
Erie, PA 16506
PHONE: 800-553-0078

www.harrinc.com



STANDARD WARRANTY

For the first two (2) years after the date of shipment, Harrington, Inc. warrants its products to be free from defects in material and workmanship when properly installed, operated, and maintained.

If during the warranty period, a product is discovered to be defective, Harrington will, at its option, replace or repair the warranted product, or grant the purchaser a credit for the product claimed to be defective. Harrington will have the sole discretion to determine whether the product was defective.

The warranty is null and void if the product is damaged due to abuse, misuse, negligence or accidental causes.

Harrington does not warrant merchantability or fitness for a particular purpose, no other warranty is expressed or implied. The buyer's exclusive remedy for any claim or damages in connection with the sale of Harrington products must be approved by the company. In no event shall Harrington be liable for any special incidental or Consequential damages whatsoever.

On request: Harrington shall provide a copy of our entire warranty provisions for all products. EMAIL a request to: info@harrinc.com, check our website, or call the factory for copy of the applicable warranties.



SHIPPING INFORMATION

Harrington strives to offer our customers an ‘excellent service’ commitment by shipping orders efficiently and accurately.

STANDARD SHIPPING METHOD: Our standard shipping method is UPS Ground. Expected transit times are shown on the USA/UPS map. Additional UPS services such as UPS Next Day Air, UPS 2nd Day Air, UPS 3rd Day Select, etc., are available and can be arranged at your request (additional charges apply). FED-Ex ground and express service are available on request.

SHIPPING CHARGES: The shipping method is determined by ‘size & weight’ of each item. Most items will be sent via UPS. Items that are too large or too heavy will be sent by LTL Freight. Any extra charges incurred for additional services, such as purchaser’s carrier or special handling by the carrier, must be paid the consignee. Items back-ordered shall be designated for “pre-paid” shipping costs. Back-ordered items will ship at no cost. Title and PPA risk of loss pass to the purchaser upon tender of the shipment to the carrier. Harrington will ship via your specified carrier, however, we reserve the right to not ship with certain carriers due to poor past experience of service.

FREIGHT SHIPMENTS: “F.O.B. Shipping Point” and EX-WORKS for export, are our standard shipping rules, without regard to who pays for the freight charges. The risk of loss lies with the purchaser. Harrington, Inc. will always ship F.O.B. ‘Shipping Point’ unless stipulated or otherwise by Harrington. It is incumbent upon the purchasing part (consignee) to make certain all shipment leaving the Harrington factory or the distribution center as “F.O.B. Shipping Point” are adequately insured, and the proper inspections and procedures are performed upon delivery of goods. Consignee must file claim for storage and/or damage freight with the carrier.

PAYMENT OR FREIGHT CHARGES: Freight charges will fall into one of the following classifications:

- **‘Free-Freight-Allowed’ (FFA):** Harrington pays all freight charges for orders classified as FFA.
- **‘Pre-Paid and Added (PPA):** Harrington pays the freight charges upon shipment. However, the charges will be included on the invoice for the items shipped and the customer will then reimburse Harrington.
- **‘Collect’ (COL):** Harrington will not pay any freight charges for the shipment. The receiving party will pay the charges when the goods are delivered.
- **‘Third-Party Billing (TPB):** is an account number and billing address is given by the purchaser.
- This would be a third-party account, an “umbrella” account that all shipping charges and claims would be responsible for.

INFORMATION REQUIRED: To avoid additional shipping costs please provide:

- Accurate address information
- Telephone number to delivery point address
- “Point-of-Contact” person at the delivery point address

SHIPPING COMPANIES: Harrington partners are: R & L Carriers, ESTES, SAIA, and XPO are preferred carriers. We will work with your third-party carrier or assist in using other carriers as requested.



SAFETY & WARNINGS



Cautions are used to indicate the presence of a hazard, which will or may cause minor injury or property damage if the notice is ignored.



Warnings denote that a potential hazard exists and indicates procedures that must be followed exactly to either eliminate or reduce the hazard, and to avoid serious personal injury, or prevent future safety problems with the product.



Dangers are used to indicate the presence of a hazard that will result in severe personal injury, death, or property damage if the notice is ignored.

IMPORTANT SAFETY & MAINTENANCE ITEMS FOR USER'S OF LDH EQUIPMENT

We cannot state too emphatically the need to follow certain guides in using large diameter hose and appliances. You should always consider the following points when using and training with large diameter hose and equipment:

- 1. All Harrington Storz "heads" are forged then hard-coat anodized. This provides maximum strength and the best in corrosion resistance. We do not supply cast Storz heads which can easily fracture and cause catastrophic failure. All Harrington equipment has a 250 PSI working pressure rating.*
- 2. Do not allow untrained personnel to operate or use large diameter hose and appliances.*
- 3. Always inspect all connections to ensure tightness, thus reducing the possibility of accidental disconnection.*
- 4. Always 'open and close' valves slowly, to reduce the possibility of damage or injury due to water hammer. Comply with applicable NFPA standards in purchasing LDH equipment and valves on "slow-closing" valve requirements.*
- 5. Always secure adapters, valves, and appliances with proper vehicle mounting brackets to prevent them from falling off vehicle and damage during mobile operations.*
- 6. Clean, lubricate, and perform necessary maintenance on all moving parts periodically. This is especially important for all intake valves left attached to the vehicle. Such valves should be removed from an apparatus at least once-a-year with both threads properly lubricated. "Lubricate SFL-1" is an extremely effective lubrication for metal to metal surfaces.*
- 7. Always store valves in the closed position when not in use.*
- 8. Test relief valves periodically to ensure they are relieving pressure for typical local conditions. Set the relief valves at a pressure of 25 PSI higher than maximum fire hydrant pressure or pressures encountered in pumper relay operations.*
- 9. When performing annual hose testing, be sure to use Storz test caps and adapters which are supplied by Harrington to prevent gasket failures. Inspection gaskets and replace as required, Storz and threaded gaskets are different and some are unique to only suction or only discharge couplings.*
- 10. These "guidelines" do NOT answer or address all safety related aspects in using LDH hose and equipment. If you have specific questions: please write or call Harrington direct and ask for information.*



ABBREVIATIONS

STORZ NUMBER	USA IN INCHES
10	1"
15	1.5"
20	2"
25	2.5"
30	3"
40	4"
45	4.5"
50	5"
60	6"
80	8"

ABBREV	DESCRIPTION
AL	Aluminum
BI	British Instanteous
BLDR	Bleeder
BR	Brass
BRCKT	Bracket
BSP	British Std Pipe Thread
CAP	Cap & chain or cable
D	DEPTH
DFM	Double Female
DM	Double Male
DRN	Drain
FF	Flat Face Flange
F	Female
FS	Female swivel
FTS	Full Time Swivel
GHT	Garden Hose Thread
H	HEIGHT
HLDR	HOLDER
HW	Hand-Wheel
INTK	Intake
L	LENGTH
lbs	Pounds
Lok	Storz Locking Device
LDH	Large Diameter Hose
LDR-LN	Leader-Line
LH	Long Handles
M	Male
MNTG	Mounting

ABBREV	DESCRIPTION
NH	National Hose
NHFR	NH female rigid
NHFS	NH female swivel
NHFS/LH	NH female swivel & long handle
NHM	NH male
NPSH	National Pipe Std Thread
NPSHFS	NPSH / female swivel
NPT	National Pipe Thread
NPTF/R	NPT / rigid female
OTLT	Outlet

PG	Pressure Gauge
PLUG	Plug / chain or cable
PRES/VAC	Pressure/Vacuum
PRV	Pressure Relief Valve
PSI	USA Pressure value
PTS	Part Time Swivel
R	Rigid
RFF	Raised-Face-Flange
RL	Rocker Lug
RLF VLV	Relief Valve
RV	Relief Valve
SAS	Screen
SH	Short handle
SPEC-THRD	Special Thread
Spnr Wrnch	Spanner Wrench
ST	Storz
ST/3LUG	Storz 3-Lug
ST/R	Storz Rigid
VAC	Vacuum
VLV	Valve
W	WIDTH
xxx	Special Thread

125 PSI	Standard relief valve setting PSI
250-S	Relief valve 250 PSI Max setting
25°	25 degree slant
30°	30 degree slant
45°	45 degree slant
90°	90 degree elbow



CAUTION

All designs, specifications, and dimensional data contained in this catalog are subject to change without notice. No additional warranties, express or implied, including warranties of mechanics for fitness for a particular purpose, are created by the descriptions of products on or in this catalog, nor is Harrington responsible for typographical errors.



AWG products are manufactured in Germany. All other products are built in North America. This Catalog is published only to be a descriptive “guideline” for Harrington products.

SAFETY FIRST!

Serious injury, death, and destruction of property can result from the improper selection or improper use of Harrington products described in this catalog.

Since Harrington has no control over the number and variety of applications for which it's products may be purchased or conditions under which they may be used. Harrington's liability on any claim, where in contract, including negligence, or otherwise, for any loss or damage shall in no case exceed the price paid for the product or any part thereof which give rise to claim.



As always, Harrington technical assistance and support is available at an instant!



HARRINGTON HISTORY

Hal Harrington & The USA Fire Industry

In the early 1970's, Hal Harrington pioneered the development of the Large Diameter Hose (LDH) concept in the United States. AWG was the original manufacturer of the Storz couplings for fire hose. When AWG began supplying the North American market in the early 1970's, valve availability was rather limited. By working with many fire departments of all sizes, both municipal and rural, paid and volunteer became obvious what types of valves were required.

As equipments were established, AWG designed and manufactured valves to meet the North American firefighting requirements. The valves in most common use today, were designed by AWG. In 1988, following Hal's fire hose manufacturing career, he founded Harrington, Inc. as the North American AWG representative. In his introductory Fire Engineering magazine, Hal is surrounded by a selection from the state-of-the-art AWG valve line, including a Piston Intake Valve displaying a glimpse of the future: a "Storz Lok" available in the 1980's.

Making the right connection!

Since 1988, Hal Harrington & his family have helped fire departments make the "right connections"! The TEAM is still at it and getting better all the time.

Harrington, Inc. offers a full line of genuine AWG designed and manufactured valves, adapters, and Storz connections. Harrington remains 'laser focused' on the vision that Hal instilled in each of our employees. In addition to AWG, Harrington makes a complimentary range of Made-in-North America adapters, suction hose & strainers, control valves, and hardware.

Welcome to our 2026 catalog & Team!


FIRE ENGINEERING "Leading the fire service since 1877"



Harrington is still your strongest resource with both experience and expertise to help your fire department to navigate our catalog of high quality products and assure you to make the ...

"Right Storz Connection!"





Harrington STORZ CONNECT



Hal Harrington revolutionized the U.S. fire market by introducing Storz connections in 1972, setting the standard for quick and secure LDH (Large Diameter Hose) connections. In 1988, Hal founded Harrington, Inc. to provide these connections, along with a wide range of essential fire appliances and adapters. Today, Harrington proudly continues Hal's vision, providing the highest quality LDH valves and adapters to the U.S. Fire Industry, and beyond.

MAINTAINING YOUR HIGH STANDARDS!

Harrington Connects Essential Departments to educate and provide an intelligent strategy for Emergency Response Connections.

FIRE 
Fire Department
~ Storz **WITH** locks

 **WATER**
Fire Hydrant
~ Storz **WITHOUT** locks

 **SPRINKLER**
FDC / NPT / 150#
~ Storz **WITHOUT** locks



Connect with Harrington... Harrington has designs on the future.



Harrington, Inc.

2630 West 21st Street
Erie, PA 16506-2908 USA



800-553-0078
814-838-3957

www.harrinc.com
info@harrinc.com

